

X-Tower Scaffold Tower



[Representative image of product]

The X-Tower is approved to EN1004 and can be erected in three minutes by one person with the minimum of training from the ground for maximum safety. The compact design can be stored and transported inside a small van and erected by one person in three minutes. Manufactured using industrial grade components for frequent use. Intuitive gravity latches make rung-by-rung height adjustment effortless allowing the tower to be quickly deployed to your desired height. Compact closed dimensions of 1.34m opens up to 3.1m x 2.0m platform.

Features

- Revolutionary Telescopic design can be erected in less than 3 minutes by one person
- Industrial strength design and components for frequent use
- Effortless multi-height adjustment up to a 2.8m platform height
- Two components only, tower frame and folding, anti-slip platform with integrated toe-boards
- Compacts down to fit inside a small trade van
- 4 x Locking heavy-duty castors
- Stabiliser supports are millimetre adjustable for precise levelling
- No loose components to forget or leave behind

Product Dimensions

SKU	Platform Height	Overall Height (mm)	Approx. Working Height ¹ (mm)	Stabiliser Length x Width (mm)	Nett Weight (kg)
3010-035	2000	3100	3600	n/a x n/a	68.0
3010-036	2800	4400	4400	n/a x n/a	75.0

¹ Working height is calculated as 1,600mm plus platform height or last climbing tread, whichever is appropriate. Ladders set at an angle of 75° degrees.

Shipping Dimensions

SKU	Barcode	Shipping Length (mm)	Shipping Width (mm)	Shipping Depth (mm)	Shipping Volume (m³)	Gross Weight (kg)
3010-035	3178740162009	1340	820	980	1.077	68.0
3010-036	3178740162016	1410	920	980	1.271	75.0

Please note that products marked 'Special Order' cannot be cancelled and are non-returnable once orders are acknowledged and placed.

This document is presented as a guide only; It is subject to change without notice and as such is not legally binding, nor does it form part of any contract.