


PDF technical sheet 6412NR




Single row deep groove ball bearings

Product definition	
d	60 mm
D	150 mm
B	35 mm
a min	4.65 mm
a max	4.90 mm
Ca min	7.42 mm
Ca max	7.67 mm
rs min	2.10 mm
rNs min	0.50 mm
D3 max	145.24 mm
b min	3.10 mm
b max	3.40 mm
r0 max	0.60 mm
D4 max	159.70 mm
f	2.77 mm
Snap ring reference	R150
Radial clearance class	CN
Mass	2.77 kg
Brand	NTN



Product performance	
Dynamic load, C	102 kN
Static load, C0	64.50 kN
Fatigue limit load, Cu	2.85 kN
f0	12.6
Nlim (oil)	5,700 Tr/min
Nlim (grease)	4,800 Tr/min
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.37 Hz
Characteristic rolling element frequency, BSF	3.63 Hz
Characteristic outer ring frequency, BPF0	2.60 Hz
Characteristic inner ring frequency, BPF1	4.40 Hz



Abutment dimensions

da min	71 mm
Da max	139 mm
ra max	2 mm
rNa max	0.50 mm
Db min	162 mm

Calculation factors

Equivalent dynamic radial load

$$P = X \cdot Fr + Y \cdot Fa$$

$\frac{f_0 F_a}{C_0}$	e	$F_a / Fr \leq e$		$F_a / Fr > e$	
		X	Y	X	Y
0.172	0.19	1	0	0.56	2.3
0.345	0.22				1.99
0.689	0.26				1.71
1.03	0.28				1.55
1.38	0.3				1.45
2.07	0.34				1.31
3.45	0.38				1.15
5.17	0.42				1.04
6.89	0.44				1

Equivalent static radial load

$$P_0 = X_0 \cdot Fr + Y_0 \cdot Fa$$

X_0	Y_0
0.6	0.5

For single or DT bearing arrangement:

If $P_0 < Fr$, then use $P_0 = Fr$