

PDF technical sheet 6208NRC3



Single row deep groove ball bearings

Product definition	
d	40 mm
D	80 mm
B	18 mm
a min	3.07 mm
a max	3.28 mm
Ca min	4.67 mm
Ca max	4.98 mm
rs min	1.10 mm
rNs min	0.50 mm
D3 max	76.81 mm
b min	1.90 mm
b max	2.20 mm
r0 max	0.60 mm
D4 max	86.60 mm
f	1.70 mm
Snap ring reference	R80
Radial clearance class	C3
Mass	0.37 kg
Brand	NTN



Product performance	
Dynamic load, C	29.10 kN
Static load, C0	17.80 kN
Fatigue limit load, Cu	0.81 kN
f0	14
Nlim (oil)	10,000 Tr/min
Nlim (grease)	8,700 Tr/min
Min operating temperature, Tmin	-60 °C
Characteristic cage frequency, FTF	0.40 Hz
Characteristic rolling element frequency, BSF	4.84 Hz
Characteristic outer ring frequency, BPF0	3.61 Hz
Characteristic inner ring frequency, BPF1	5.39 Hz



Abutment dimensions

da min	46.50 mm
Da max	73.50 mm
ra max	1 mm
rNa max	0.50 mm
Db min	88 mm

Calculation factors

Equivalent dynamic radial load

$$P = X \cdot Fr + Y \cdot Fa$$

$\frac{f_0 F_a}{C_0}$	e	Fa / Fr ≤ e		Fa / Fr > e	
		X	Y	X	Y
0.172	0.19	1	0	0.56	2.3
0.345	0.22				1.99
0.689	0.26				1.71
1.03	0.28				1.55
1.38	0.3				1.45
2.07	0.34				1.31
3.45	0.38				1.15
5.17	0.42				1.04
6.89	0.44				1

Equivalent static radial load

$$P_0 = X_0 \cdot Fr + Y_0 \cdot Fa$$

X_0	Y_0
0.6	0.5

For single or DT bearing arrangement:

If $P_0 < Fr$, then use $P_0 = Fr$