

PDF technical sheet 7017CVUJ74



High precision angular contact ball bearings

High precision angular contact ball bearing, laminated resin cage centred on outer ring

Product definition	
d	85 mm
D	130 mm
B	22 mm
d1	99.30 mm
D1	115.70 mm
D2	122.49 mm
a	25 mm
Contact angle, α	15 °
rs min	1.10 mm
r1s min	0.60 mm
f0	15.881
Precision class	P4
Mass	0.90 kg
Brand	SNR



Product performance	
Dynamic load, C	60.20 kN
Static load, C0	58.70 kN
Fatigue limit load, Cu	3 kN
Nlim (oil)	16,500 Tr/min
Nlim (grease)	10,500 Tr/min
Axial displacement K Factor	0.98
Preload level	7
Peload value	310 kN
axial rigidity	100 N/ μ m
radial rigidity	581 N/ μ m
Min operating temperature, Tmin	-30 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.44 Hz
Characteristic rolling element frequency, BSF	7.85 Hz
Characteristic outer ring frequency, BPF0	9.23 Hz
Characteristic inner ring frequency, BPF1	11.77 Hz



Abutment dimensions

da min	92 mm
db min	92 mm
Da max	123 mm
Db max	123 mm
r1a max	0.60 mm
ra max	1 mm
D6	103.70 mm

Calculation factors

Equivalent dynamic radial load

$$P = X \cdot Fr + Y \cdot Fa$$

Series			e	Single or DT bearing arrangement				DB or DF arrangement			
				Fa / Fr ≤ e		Fa / Fr > e		Fa / Fr ≤ e		Fa / Fr > e	
				X	Y	X	Y	X	Y	X	Y
70 (NTN & SNR) 72 (NTN & SNR) 78 (NTN) 79 (NTN) 719 (SNR)	15°	0.178	0.38	1	0	0.44	1.47	1	1.65	0.72	2.39
		0.357	0.4				1.4		1.57		2.28
		0.714	0.43				1.3		1.46		2.11
		1.07	0.46				1.23		1.38		2
		1.43	0.47				1.19		1.34		1.93
		2.14	0.5				1.12		1.26		1.82
		3.57	0.55				1.02		1.14		1.66
		5.35	0.56						1.12		1.63
		7.14	0.56				1		1.12		1.63
	25°		0.68			0.41	0.87		0.92	0.67	1.41
	30°		0.8			0.39	0.76		0.78	0.63	1.24

Equivalent static radial load

$$Po = Xo \cdot Fr + Yo \cdot Fa$$

Series			Single or DT bearing arrangement		DB or DF arrangement	
			X ₀	Y ₀	X ₀	Y ₀
70 (NTN & SNR) 72 (NTN & SNR) 78 (NTN) 79 (NTN) 719 (SNR)	15°		0.5	0.46	1	0.92
	25°			0.38		0.76
	30°			0.33		0.66

For single or DT bearing arrangement :

If $Po < Fr$, then use $Po = Fr$