

PDF technical sheet 6310L1C3




Single row deep groove ball bearings

Deep groove ball bearing, radial contact, machined cage, open


Product definition

d	50 mm
D	110 mm
B	27 mm
rs min	2 mm
Radial clearance class	C3
Mass	1.07 kg
Brand	NTN



Product performance

Dynamic load, C	62 kN
Static load, C0	38.50 kN
Fatigue limit load, Cu	1.75 kN
f0	13.2
Nlim (oil)	7,500 Tr/min
Nlim (grease)	6,400 Tr/min
Min operating temperature, Tmin	-60 °C
Characteristic cage frequency, FTF	0.38 Hz
Characteristic rolling element frequency, BSF	4.07 Hz
Characteristic outer ring frequency, BPF0	3.07 Hz
Characteristic inner ring frequency, BPF1	4.93 Hz



Abutment dimensions

da min	59 mm
Da max	101 mm
ra max	2 mm

Calculation factors

Equivalent dynamic radial load

$$P = X \cdot Fr + Y \cdot Fa$$

$\frac{f_0 F_a}{C_0}$	e	$F_a / Fr \leq e$		$F_a / Fr > e$	
		X	Y	X	Y
0.172	0.19	1	0	0.56	2.3
0.345	0.22				1.99
0.689	0.26				1.71
1.03	0.28				1.55
1.38	0.3				1.45
2.07	0.34				1.31
3.45	0.38				1.15
5.17	0.42				1.04
6.89	0.44				1

Equivalent static radial load

$$P_0 = X_0 \cdot Fr + Y_0 \cdot Fa$$

X_0	Y_0
0.6	0.5

For single or DT bearing arrangement:

If $P_0 < Fr$, then use $P_0 = Fr$