

PDF technical sheet 7310BGC3




Single row or matched pairs of angular contact ball bearings

Angular contact ball bearings, pressed steel cage

Product definition	
d	50 mm
D	110 mm
B	27 mm
a	47 mm
Contact angle, α	40 °
rs min	2 mm
r1s min	1 mm
Radial clearance class	C3
Mass	1.11 kg
Brand	NTN



Product performance	
Dynamic load, C	68 kN
Static load, C0	48 kN
Fatigue limit load, Cu	2.18 kN
Nlim (oil)	8,100 Tr/min
Nlim (grease)	6,000 Tr/min
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.41 Hz
Characteristic rolling element frequency, BSF	4.17 Hz
Characteristic outer ring frequency, BPF0	4.93 Hz
Characteristic inner ring frequency, BPFI	7.07 Hz



Abutment dimensions	
da min	60 mm
db min	55.50 mm
Da max	100 mm
Db max	104.50 mm
r1a max	1 mm
ra max	2 mm

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

	e	Single or DT bearing arrangement				DB or DF arrangement			
		Fa / Fr ≤ e		Fa / Fr > e		Fa / Fr ≤ e		Fa / Fr > e	
		X	Y	X	Y	X	Y	X	Y
30°	0.8	1	0	0.9	0.76	1	0.78	0.63	1.24
40°	1.14			0.35	0.57		0.55	0.57	0.93

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

a	Single or DT bearing arrangement		DB or DF arrangement	
	X ₀	Y ₀	X ₀	Y ₀
30°	0.5	0.33	1	0.66
40°		0.26		0.52

For single or DT bearing arrangement :

If $P_0 < F_r$, then use $P_0 = F_r$