

PDF technical sheet 6810JR



Single row deep groove ball bearings

Deep groove ball bearing, radial contact, pressed steel cage, open

Product definition

d	50 mm
D	65 mm
B	7 mm
rs min	0.30 mm
Radial clearance class	CN
Mass	0.05 kg
Brand	NTN



Product performance

Dynamic load, C	6.60 kN
Static load, C0	6.10 kN
Fatigue limit load, Cu	0.28 kN
f0	16.1
Nlim (oil)	11,000 Tr/min
Nlim (grease)	9,600 Tr/min
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.47 Hz
Characteristic rolling element frequency, BSF	14.42 Hz
Characteristic outer ring frequency, BPF0	11.17 Hz
Characteristic inner ring frequency, BPF1	12.83 Hz



Abutment dimensions

da min	52 mm
Da max	63 mm
ra max	0.30 mm

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

$\frac{f_0 F_a}{C_0}$	e	$F_a / F_r \leq e$		$F_a / F_r > e$	
		X	Y	X	Y
0.172	0.19	1	0	0.56	2.3
0.345	0.22				1.99
0.689	0.26				1.71
1.03	0.28				1.55
1.38	0.3				1.45
2.07	0.34				1.31
3.45	0.38				1.15
5.17	0.42				1.04
6.89	0.44				1

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X_0	Y_0
0.6	0.5

For single or DT bearing arrangement :

If $P_0 < F_r$, then use $P_0 = F_r$