

PDF technical sheet 6844C3



Single row deep groove ball bearings

Deep groove ball bearing, radial contact, pressed steel cage, open


Product definition

d	220 mm
D	270 mm
B	24 mm
rs min	1.50 mm
Radial clearance class	C3
Mass	3 kg
Brand	NTN



Product performance

Dynamic load, C	76.50 kN
Static load, C0	98 kN
Fatigue limit load, Cu	2.85 kN
f0	16
Nlim (oil)	2,400 Tr/min
Nlim (grease)	2,100 Tr/min
Min operating temperature, Tmin	-60 °C
Characteristic cage frequency, FTF	0.47 Hz
Characteristic rolling element frequency, BSF	16.18 Hz
Characteristic outer ring frequency, BPF0	12.67 Hz
Characteristic inner ring frequency, BPF1	14.33 Hz



Abutment dimensions

da min	228 mm
Da max	262 mm
ra max	1.50 mm

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

$\frac{f_0 F_a}{C_0}$	e	$F_a / F_r \leq e$		$F_a / F_r > e$	
		X	Y	X	Y
0.172	0.19	1	0	0.56	2.3
0.345	0.22				1.99
0.689	0.26				1.71
1.03	0.28				1.55
1.38	0.3				1.45
2.07	0.34				1.31
3.45	0.38				1.15
5.17	0.42				1.04
6.89	0.44				1

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X_0	Y_0
0.6	0.5

For single or DT bearing arrangement :

If $P_0 < F_r$, then use $P_0 = F_r$