

PDF technical sheet 6412C3



Single row deep groove ball bearings

Deep groove ball bearing, radial contact, pressed steel cage, open

Product definition

d	60 mm
D	150 mm
B	35 mm
rs min	2.10 mm
Radial clearance class	C3
Mass	2.77 kg
Brand	NTN



Product performance

Dynamic load, C	102 kN
Static load, C0	64.50 kN
Fatigue limit load, Cu	2.85 kN
f0	12.6
Nlim (oil)	5,700 Tr/min
Nlim (grease)	4,800 Tr/min
Min operating temperature, Tmin	-60 °C
Characteristic cage frequency, FTF	0.37 Hz
Characteristic rolling element frequency, BSF	3.63 Hz
Characteristic outer ring frequency, BPF0	2.60 Hz
Characteristic inner ring frequency, BPF1	4.40 Hz



Abutment dimensions

da min	71 mm
Da max	139 mm
ra max	2 mm

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

$\frac{f_0 F_a}{C_0}$	e	$F_a / F_r \leq e$		$F_a / F_r > e$	
		X	Y	X	Y
0.172	0.19	1	0	0.56	2.3
0.345	0.22				1.99
0.689	0.26				1.71
1.03	0.28				1.55
1.38	0.3				1.45
2.07	0.34				1.31
3.45	0.38				1.15
5.17	0.42				1.04
6.89	0.44				1

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X_0	Y_0
0.6	0.5

For single or DT bearing arrangement:

If $P_0 < F_r$, then use $P_0 = F_r$