

PDF technical sheet 6209HT200ZZ



Single row deep groove ball bearings

TOPLINE deep groove ball bearing, radial contact, pressed steel cage, shields on both sides, applications upto 200 °C.

Product definition	
d	45 mm
D	85 mm
B	19 mm
d1	54.50 mm
D1	75.60 mm
rs min	1.10 mm
Radial clearance class	C4
Mass	0.40 kg
Brand	SNR



Product performance	
Dynamic load, C	32.20 kN
Static load, C0	20.40 kN
Fatigue limit load, Cu	0.93 kN
f0	14.1
Nref	8,700 Tr/min
Nlim	4,600 Tr/min
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	200 °C
Characteristic cage frequency, FTF	0.40 Hz
Characteristic rolling element frequency, BSF	4.92 Hz
Characteristic outer ring frequency, BPF0	3.62 Hz
Characteristic inner ring frequency, BPF1	5.38 Hz



Abutment dimensions

da min	51.50 mm
da max	54.50 mm
Da max	78.50 mm
ra max	1 mm

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

$\frac{f_0 F_a}{C_0}$	e	$F_a / F_r \leq e$		$F_a / F_r > e$	
		X	Y	X	Y
0.172	0.19	1	0	0.56	2.3
0.345	0.22				1.99
0.689	0.26				1.71
1.03	0.28				1.55
1.38	0.3				1.45
2.07	0.34				1.31
3.45	0.38				1.15
5.17	0.42				1.04
6.89	0.44				1

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X_0	Y_0
0.6	0.5

For single or DT bearing arrangement:

If $P_0 < F_r$, then use $P_0 = F_r$