

PDF technical sheet

7911UADG/GNP42U3G




High precision angular contact ball bearings

High precision angular contact ball bearing, moulded polyamide cage centred on balls


Product definition

d	55 mm
D	80 mm
B	13 mm
d1	63.70 mm
d2	61.80 mm
D1	71.40 mm
D2	75.10 mm
a	22.30 mm
Contact angle, α	25 °
rs min	1 mm
r1s min	0.60 mm
f0	16.5
Precision class	P42
Mass	0.18 kg
Brand	NTN



Product performance

Dynamic load, C	18.60 kN
Static load, C0	17.50 kN
Nlim (oil)	24,300 Tr/min
Nlim (grease)	15,000 Tr/min
Preload level	GN
Peload value	186 kN
axial rigidity	149.5 N/ μ m
radial rigidity	320 N/ μ m
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.45 Hz
Characteristic rolling element frequency, BSF	9.37 Hz
Characteristic outer ring frequency, BPF0	10.40 Hz
Characteristic inner ring frequency, BPF1	12.60 Hz



Abutment dimensions

da min	60.50 mm
Da max	74.50 mm
Db max	75.50 mm
r1a max	0.60 mm
ra max	1 mm
D6	64.10 mm

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

Series			e	Single or DT bearing arrangement				DB or DF arrangement			
				Fa / Fr ≤ e		Fa / Fr > e		Fa / Fr ≤ e		Fa / Fr > e	
				X	Y	X	Y	X	Y	X	Y
70 (NTN & SNR) 72 (NTN & SNR) 78 (NTN) 79 (NTN) 719 (SNR)	15°	0.178	0.38	1	0	0.44	1.47	1	1.65	0.72	2.39
		0.357	0.4				1.4		1.57		2.28
		0.714	0.43				1.3		1.46		2.11
		1.07	0.46				1.23		1.38		2
		1.43	0.47				1.19		1.34		1.93
		2.14	0.5				1.12		1.26		1.82
		3.57	0.55				1.02		1.14		1.66
		5.35	0.56						1.12		1.63
		7.14	0.56				1		1.12		1.63
	25°		0.68	1	0	0.41	0.87	1	0.92	0.67	1.41
	30°		0.8								0.78

Equivalent static radial load

$$P_o = X_o.F_r + Y_o.F_a$$

Series			Single or DT bearing arrangement		DB or DF arrangement	
			X _o	Y _o	X _o	Y _o
70 (NTN & SNR) 72 (NTN & SNR) 78 (NTN) 79 (NTN) 719 (SNR)	15°		0.5	0.46	1	0.92
	25°			0.38		0.76
	30°			0.33		0.66

For single or DT bearing arrangement :

If $P_o < F_r$, then use $P_o = F_r$