


## PDF technical sheet ML7006HVUJ84S




### High precision angular contact ball bearings

High precision angular contact ball bearing, high speed series ML, laminated resin cage centred on outer ring


#### Product definition

|                         |          |
|-------------------------|----------|
| d                       | 30 mm    |
| D                       | 55 mm    |
| B                       | 13 mm    |
| d1                      | 38.10 mm |
| d2                      | 36.15 mm |
| D1                      | 48.55 mm |
| D2                      | 50.15 mm |
| a                       | 16 mm    |
| Contact angle, $\alpha$ | 25 °     |
| rs min                  | 1 mm     |
| r1s min                 | 0.60 mm  |
| f0                      | 8.064    |
| Precision class         | P4S      |
| Mass                    | 0.11 kg  |
| Brand                   | SNR      |



#### Product performance

|                                               |                |
|-----------------------------------------------|----------------|
| Dynamic load, C                               | 7.80 kN        |
| Static load, C0                               | 4.50 kN        |
| Fatigue limit load, Cu                        | 0.27 kN        |
| Nlim (oil)                                    | 46,000 Tr/min  |
| Nlim (grease)                                 | 32,000 Tr/min  |
| Axial displacement K Factor                   | 0.76           |
| Preload level                                 | 8              |
| Peloid value                                  | 200 kN         |
| axial rigidity                                | 111 N/ $\mu$ m |
| radial rigidity                               | 237 N/ $\mu$ m |
| Min operating temperature, Tmin               | -30 °C         |
| Max operating temperature, Tmax               | 120 °C         |
| Characteristic cage frequency, FTF            | 0.44 Hz        |
| Characteristic rolling element frequency, BSF | 7.40 Hz        |
| Characteristic outer ring frequency, BPF0     | 8.79 Hz        |
| Characteristic inner ring frequency, BPF1     | 11.21 Hz       |



### Abutment dimensions

|         |          |
|---------|----------|
| da min  | 35.50 mm |
| db min  | 35.50 mm |
| Da max  | 49.50 mm |
| Db max  | 49.50 mm |
| r1a max | 0.60 mm  |
| ra max  | 1 mm     |
| D6      | 40.10 mm |

### Calculation factors

#### Equivalent dynamic radial load

$$P = X \cdot Fr + Y \cdot Fa$$

| Series                                                                |     |       | e    | Single or DT bearing arrangement |   |             |      | DB or DF arrangement |      |             |      |
|-----------------------------------------------------------------------|-----|-------|------|----------------------------------|---|-------------|------|----------------------|------|-------------|------|
|                                                                       |     |       |      | Fa / Fr ≤ e                      |   | Fa / Fr > e |      | Fa / Fr ≤ e          |      | Fa / Fr > e |      |
|                                                                       |     |       |      | X                                | Y | X           | Y    | X                    | Y    | X           | Y    |
| 70 (NTN & SNR)<br>72 (NTN & SNR)<br>78 (NTN)<br>79 (NTN)<br>719 (SNR) | 15° | 0.178 | 0.38 | 1                                | 0 | 0.44        | 1.47 | 1                    | 1.65 | 0.72        | 2.39 |
|                                                                       |     | 0.357 | 0.4  |                                  |   |             | 1.4  |                      | 1.57 |             | 2.28 |
|                                                                       |     | 0.714 | 0.43 |                                  |   |             | 1.3  |                      | 1.46 |             | 2.11 |
|                                                                       |     | 1.07  | 0.46 |                                  |   |             | 1.23 |                      | 1.38 |             | 2    |
|                                                                       |     | 1.43  | 0.47 |                                  |   |             | 1.19 |                      | 1.34 |             | 1.93 |
|                                                                       |     | 2.14  | 0.5  |                                  |   |             | 1.12 |                      | 1.26 |             | 1.82 |
|                                                                       |     | 3.57  | 0.55 |                                  |   |             | 1.02 |                      | 1.14 |             | 1.66 |
|                                                                       |     | 5.35  | 0.56 |                                  |   |             |      |                      | 1.12 |             | 1.63 |
|                                                                       |     | 7.14  | 0.56 |                                  |   |             | 1    |                      | 1.12 |             | 1.63 |
|                                                                       | 25° |       | 0.68 |                                  |   | 0.41        | 0.87 |                      | 0.92 | 0.67        | 1.41 |
|                                                                       | 30° |       | 0.8  |                                  |   | 0.39        | 0.76 |                      | 0.78 | 0.63        | 1.24 |

#### Equivalent static radial load

$$P_0 = X_0 \cdot Fr + Y_0 \cdot Fa$$

| Series                                                                |     |  | Single or DT bearing arrangement |                | DB or DF arrangement |                |
|-----------------------------------------------------------------------|-----|--|----------------------------------|----------------|----------------------|----------------|
|                                                                       |     |  | X <sub>0</sub>                   | Y <sub>0</sub> | X <sub>0</sub>       | Y <sub>0</sub> |
|                                                                       |     |  |                                  |                |                      |                |
| 70 (NTN & SNR)<br>72 (NTN & SNR)<br>78 (NTN)<br>79 (NTN)<br>719 (SNR) | 15° |  | 0.5                              | 0.46           | 1                    | 0.92           |
|                                                                       | 25° |  |                                  | 0.38           |                      | 0.76           |
|                                                                       | 30° |  |                                  | 0.33           |                      | 0.66           |
|                                                                       |     |  |                                  |                |                      |                |

For single or DT bearing arrangement :

If  $P_0 < Fr$ , then use  $P_0 = Fr$