

PDF technical sheet


7918UCG/GNP42U3G




High precision angular contact ball bearings

High precision angular contact ball bearing, moulded polyamide cage centred on balls

Product definition	
d	90 mm
D	125 mm
B	18 mm
d1	101.90 mm
d2	99.30 mm
D1	113.10 mm
D2	118.50 mm
a	23.50 mm
Contact angle, α	15 °
rs min	1.10 mm
r1s min	0.60 mm
f0	16.6
Precision class	P42
Mass	0.56 kg
Brand	NTN



Product performance	
Dynamic load, C	41.50 kN
Static load, C0	46 kN
Nlim (oil)	17,400 Tr/min
Nlim (grease)	10,900 Tr/min
Preload level	GN
Peload value	255 kN
axial rigidity	105 N/ μ m
radial rigidity	600 N/ μ m
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.45 Hz
Characteristic rolling element frequency, BSF	10.33 Hz
Characteristic outer ring frequency, BPF0	12.25 Hz
Characteristic inner ring frequency, BPF1	14.75 Hz



Abutment dimensions

da min	97 mm
Da max	118 mm
Db max	120.50 mm
r1a max	0.60 mm
ra max	1 mm
D6	102.40 mm

Calculation factors

Equivalent dynamic radial load

$$P = X \cdot Fr + Y \cdot Fa$$

Series			e	Single or DT bearing arrangement				DB or DF arrangement			
				Fa / Fr ≤ e		Fa / Fr > e		Fa / Fr ≤ e		Fa / Fr > e	
				X	Y	X	Y	X	Y	X	Y
70 (NTN & SNR) 72 (NTN & SNR) 78 (NTN) 79 (NTN) 719 (SNR)	15°	0.178	0.38	1	0	0.44	1.47	1	1.65	0.72	2.39
		0.357	0.4				1.4		1.57		2.28
		0.714	0.43				1.3		1.46		2.11
		1.07	0.46				1.23		1.38		2
		1.43	0.47				1.19		1.34		1.93
		2.14	0.5				1.12		1.26		1.82
		3.57	0.55				1.02		1.14		1.66
		5.35	0.56						1.12		1.63
		7.14	0.56				1		1.12		1.63
	25°		0.68				0.41		0.92	0.67	1.41
	30°		0.8				0.39		0.78		1.24

Equivalent static radial load

$$Po = Xo \cdot Fr + Yo \cdot Fa$$

Series			Single or DT bearing arrangement		DB or DF arrangement	
			X ₀	Y ₀	X ₀	Y ₀
70 (NTN & SNR) 72 (NTN & SNR) 78 (NTN) 79 (NTN) 719 (SNR)	15°		0.5	0.46	1	0.92
	25°			0.38		0.76
	30°			0.33		0.66

For single or DT bearing arrangement :

If $Po < Fr$, then use $Po = Fr$