

PDF technical sheet


7318B




Single row or matched pairs of angular contact ball bearings

Angular contact ball bearings, pressed steel cage

Product definition	
d	90 mm
D	190 mm
B	43 mm
a	80.50 mm
Contact angle, α	40 °
rs min	3 mm
r1s min	1.10 mm
Mass	5.16 kg
Brand	NTN



Product performance	
Dynamic load, C	156 kN
Static load, C0	135 kN
Fatigue limit load, Cu	5.20 kN
Nlim (oil)	4,500 Tr/min
Nlim (grease)	3,400 Tr/min
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.41 Hz
Characteristic rolling element frequency, BSF	4.28 Hz
Characteristic outer ring frequency, BPF0	4.96 Hz
Characteristic inner ring frequency, BPFI	7.04 Hz



Abutment dimensions	
da min	104 mm
db min	97 mm
Da max	176 mm
Db max	183 mm
r1a max	1 mm
ra max	2.50 mm

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

	e	Single or DT bearing arrangement				DB or DF arrangement			
		Fa / Fr ≤ e		Fa / Fr > e		Fa / Fr ≤ e		Fa / Fr > e	
		X	Y	X	Y	X	Y	X	Y
30°	0.8	1	0	0.9	0.76	1	0.78	0.63	1.24
40°	1.14			0.35	0.57		0.55	0.57	0.93

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

a	Single or DT bearing arrangement		DB or DF arrangement	
	X ₀	Y ₀	X ₀	Y ₀
30°	0.5	0.33	1	0.66
40°		0.26		0.52

For single or DT bearing arrangement :

If $P_0 < F_r$, then use $P_0 = F_r$