

PDF technical sheet 6032C3



Single row deep groove ball bearings

Deep groove ball bearing, radial contact, pressed steel cage, open

Product definition

d	160 mm
D	240 mm
B	38 mm
rs min	2.10 mm
Radial clearance class	C3
Mass	5.05 kg
Brand	NTN



Product performance

Dynamic load, C	143 kN
Static load, C0	144 kN
Fatigue limit load, Cu	4.65 kN
f0	15.9
Nlim (oil)	3,000 Tr/min
Nlim (grease)	2,600 Tr/min
Min operating temperature, Tmin	-60 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.44 Hz
Characteristic rolling element frequency, BSF	8.28 Hz
Characteristic outer ring frequency, BPF0	7.05 Hz
Characteristic inner ring frequency, BPF1	8.95 Hz



Abutment dimensions

da min	171 mm
Da max	229 mm
ra max	2 mm

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

$\frac{f_0 F_a}{C_0}$	e	$F_a / F_r \leq e$		$F_a / F_r > e$	
		X	Y	X	Y
0.172	0.19	1	0	0.56	2.3
0.345	0.22				1.99
0.689	0.26				1.71
1.03	0.28				1.55
1.38	0.3				1.45
2.07	0.34				1.31
3.45	0.38				1.15
5.17	0.42				1.04
6.89	0.44				1

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X_0	Y_0
0.6	0.5

For single or DT bearing arrangement :

If $P_0 < F_r$, then use $P_0 = F_r$