

PDF technical sheet 6014LU



Single row deep groove ball bearings

Deep groove ball bearing, radial contact, pressed steel cage, contact seal on one side

Product definition	
d	70 mm
D	110 mm
B	20 mm
rs min	1.10 mm
Radial clearance class	CN
Mass	0.60 kg
Brand	NTN



Product performance	
Dynamic load, C	38 kN
Static load, C0	31 kN
Fatigue limit load, Cu	1.41 kN
f0	15.6
Nlim (grease)	3,600 Tr/min
Min operating temperature, Tmin	-25 °C
Max operating temperature, Tmax	110 °C
Characteristic cage frequency, FTF	0.43 Hz
Characteristic rolling element frequency, BSF	7.43 Hz
Characteristic outer ring frequency, BPF0	6.07 Hz
Characteristic inner ring frequency, BPF1	7.93 Hz



Abutment dimensions

da min	76.50 mm
da max	80.50 mm
Da max	103.50 mm
ra max	1 mm

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

$\frac{f_0 F_a}{C_0}$	e	$F_a / F_r \leq e$		$F_a / F_r > e$	
		X	Y	X	Y
0.172	0.19	1	0	0.56	2.3
0.345	0.22				1.99
0.689	0.26				1.71
1.03	0.28				1.55
1.38	0.3				1.45
2.07	0.34				1.31
3.45	0.38				1.15
5.17	0.42				1.04
6.89	0.44				1

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X_0	Y_0
0.6	0.5

For single or DT bearing arrangement:

If $P_0 < F_r$, then use $P_0 = F_r$