

PDF technical sheet


7012UCG/GNP42U3G




High precision angular contact ball bearings

High precision angular contact ball bearing, moulded polyamide cage centred on balls

Product definition	
d	60 mm
D	95 mm
B	18 mm
d1	71.90 mm
d2	69.30 mm
D1	83.10 mm
D2	88.60 mm
a	19.40 mm
Contact angle, α	15 °
rs min	1.10 mm
r1s min	0.60 mm
f0	15.7
Precision class	P42
Mass	0.41 kg
Brand	NTN



Product performance	
Dynamic load, C	36.50 kN
Static load, C0	32.50 kN
Nlim (oil)	24,200 Tr/min
Nlim (grease)	15,100 Tr/min
Preload level	GN
Peload value	216 kN
axial rigidity	79.6 N/ μ m
radial rigidity	455 N/ μ m
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.44 Hz
Characteristic rolling element frequency, BSF	7.39 Hz
Characteristic outer ring frequency, BPF0	8.71 Hz
Characteristic inner ring frequency, BPF1	11.29 Hz



Abutment dimensions

da min	67 mm
Da max	88 mm
Db max	90.50 mm
r1a max	0.60 mm
ra max	1 mm
D6	72.40 mm

Calculation factors

Equivalent dynamic radial load

$$P = X \cdot Fr + Y \cdot Fa$$

Series			e	Single or DT bearing arrangement				DB or DF arrangement			
				Fa / Fr ≤ e		Fa / Fr > e		Fa / Fr ≤ e		Fa / Fr > e	
				X	Y	X	Y	X	Y	X	Y
70 (NTN & SNR) 72 (NTN & SNR) 78 (NTN) 79 (NTN) 719 (SNR)	15°	0.178	0.38	1	0	0.44	1.47	1	1.65	0.72	2.39
		0.357	0.4				1.4		1.57		2.28
		0.714	0.43				1.3		1.46		2.11
		1.07	0.46				1.23		1.38		2
		1.43	0.47				1.19		1.34		1.93
		2.14	0.5				1.12		1.26		1.82
		3.57	0.55				1.02		1.14		1.66
		5.35	0.56						1.12		1.63
		7.14	0.56				1		1.12		1.63
	25°		0.68	1	0	0.41	0.87	1	0.92	0.67	1.41
	30°		0.8								0.78

Equivalent static radial load

$$Po = Xo \cdot Fr + Yo \cdot Fa$$

Series			Single or DT bearing arrangement		DB or DF arrangement	
			Xo	Yo	Xo	Yo
70 (NTN & SNR) 72 (NTN & SNR) 78 (NTN) 79 (NTN) 719 (SNR)	15°		0.5	0.46	1	0.92
	25°			0.38		0.76
	30°			0.33		0.66

For single or DT bearing arrangement :

If $Po < Fr$, then use $Po = Fr$