

PDF technical sheet 6044C3



Single row deep groove ball bearings

Deep groove ball bearing, radial contact, pressed steel cage, open


Product definition

d	220 mm
D	340 mm
B	56 mm
rs min	3 mm
Radial clearance class	C3
Mass	15.70 kg
Brand	NTN



Product performance

Dynamic load, C	241 kN
Static load, C0	289 kN
Fatigue limit load, Cu	7.90 kN
f0	15.8
Nlim (oil)	2,200 Tr/min
Nlim (grease)	1,800 Tr/min
Min operating temperature, Tmin	-60 °C
Characteristic cage frequency, FTF	0.44 Hz
Characteristic rolling element frequency, BSF	7.89 Hz
Characteristic outer ring frequency, BPF0	6.57 Hz
Characteristic inner ring frequency, BPF1	8.44 Hz



Abutment dimensions

da min	233 mm
Da max	327 mm
ra max	2.50 mm

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

$\frac{f_0 F_a}{C_0}$	e	$F_a / F_r \leq e$		$F_a / F_r > e$	
		X	Y	X	Y
0.172	0.19	1	0	0.56	2.3
0.345	0.22				1.99
0.689	0.26				1.71
1.03	0.28				1.55
1.38	0.3				1.45
2.07	0.34				1.31
3.45	0.38				1.15
5.17	0.42				1.04
6.89	0.44				1

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X_0	Y_0
0.6	0.5

For single or DT bearing arrangement :

If $P_0 < F_r$, then use $P_0 = F_r$