

PDF technical sheet 6318L1C3



Single row deep groove ball bearings

Deep groove ball bearing, radial contact, machined cage, open

Product definition

d	90 mm
D	190 mm
B	43 mm
rs min	3 mm
Radial clearance class	C3
Mass	4.91 kg
Brand	NTN



Product performance

Dynamic load, C	143 kN
Static load, C0	107 kN
Fatigue limit load, Cu	4.10 kN
f0	13.3
Nlim (oil)	4,200 Tr/min
Nlim (grease)	3,600 Tr/min
Min operating temperature, Tmin	-60 °C
Characteristic cage frequency, FTF	0.39 Hz
Characteristic rolling element frequency, BSF	4.18 Hz
Characteristic outer ring frequency, BPF0	3.09 Hz
Characteristic inner ring frequency, BPF1	4.91 Hz



Abutment dimensions

da min	103 mm
Da max	177 mm
ra max	2.50 mm

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

$\frac{f_0 F_a}{C_0}$	e	$F_a / F_r \leq e$		$F_a / F_r > e$	
		X	Y	X	Y
0.172	0.19	1	0	0.56	2.3
0.345	0.22				1.99
0.689	0.26				1.71
1.03	0.28				1.55
1.38	0.3				1.45
2.07	0.34				1.31
3.45	0.38				1.15
5.17	0.42				1.04
6.89	0.44				1

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X_0	Y_0
0.6	0.5

For single or DT bearing arrangement:

If $P_0 < F_r$, then use $P_0 = F_r$