

tesa® 51970

Transparent double-sided filmic tape

PRODUCT INFORMATION

Product Description

tesa® 51970 is a transparent double-sided tape consisting of a PP-film backing and a tackified adhesive.

tesa® 51970 features especially:

- Excellent combination of high tack and adhesion
- · Secure bond even on critical materials such as PP and PE and rough surfaces
- Good temperature resistance and outdoor suitability

Main Application

- Mounting of plastic and wooden trims
- Mounting of decorative materials and displays
- Mounting of transparent signs and scales

Technical Data

Backing material	PP film	Tensile strength	50 N/cm
Colour	transparent	Type of liner	glassine
Total thickness	220 µm	Colour of liner	brown
Type of adhesive	tackified acrylic	Thickness of liner	71 µm
Elongation at break	150 %		

Adhesion to

13 N/cm	Steel (after 14 days)	13.5 N/cm
11.3 N/cm	ABS (after 14 days)	14.4 N/cm
10.2 N/cm	Aluminium (after 14 days)	12.8 N/cm
12.3 N/cm	PC (after 14 days)	15 N/cm
5.4 N/cm	PE (after 14 days)	6.8 N/cm
9.9 N/cm	PET (after 14 days)	12.5 N/cm
6.8 N/cm	PP (after 14 days)	8.8 N/cm
11.8 N/cm	PS (after 14 days)	13.4 N/cm
10.5 N/cm	PVC (after 14 days)	17 N/cm
	11.3 N/cm 10.2 N/cm 12.3 N/cm 5.4 N/cm 9.9 N/cm 6.8 N/cm 11.8 N/cm	11.3 N/cm ABS (after 14 days) 10.2 N/cm Aluminium (after 14 days) 12.3 N/cm PC (after 14 days) 5.4 N/cm PE (after 14 days) 9.9 N/cm PET (after 14 days) 6.8 N/cm PP (after 14 days) PP (after 14 days) PP (after 14 days) 11.8 N/cm PS (after 14 days)

Properties

Temperature resistance short term	130 °C	Resistance to chemicals	+		
Temperature resistance long term	80 °C	Softener resistance	+		
Tack	+	Static shear resistance at 23°C	+		
Ageing resistance (UV)	+	Static shear resistance at 40°C	+		
Humidity resistance	++	Tack	+		
valuation across relevant tesa® assortment: ++ very good, + good, o medium, - low					

For latest information on this product please visit http://l.tesa.com/?ip=51970

Page 1 of 2 / As of 12/15/15

tesa SE

Quickbornstraße 24 20253 Hamburg Germany Phone: +49 (40) 4909 101

http://www.tesa.com

tesa tape inc. Sa25 Carnegie Boulevard
Charlotte, N.C. 28209
United States of America
Phone: +1 (704) 554 0707
Fax: +1 (704) 553 5634
http://www.tesatape.com

tesa tape Asia Pacific Pte. Ltd.

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.



tesa® 51970

Transparent double-sided filmic tape

PRODUCT INFORMATION

Additional Info

Liner variants: PV0 brown glassine paper (71 µm) PV1 white paper liner (84 µm; 100gr/m²) PV6 red MOPP-film (80 µm)

A fingerlift version (extended liner), tesa® 61970, is also available.

For latest information on this product please visit http://l.tesa.com/?ip=51970

Page 2 of 2 / As of 12/15/15

Quickbornstraße 24 20253 Hamburg Germany Phone: +49 (40) 4909 101

http://www.tesa.com

tesa tape Asia