

PDF technical sheet 6836C3



Single row deep groove ball bearings

Deep groove ball bearing, radial contact, pressed steel cage, open

Product definition

d	180 mm
D	225 mm
B	22 mm
rs min	1.10 mm
Radial clearance class	C3
Mass	2.03 kg
Brand	NTN



Product performance

Dynamic load, C	60.50 kN
Static load, C0	73 kN
Fatigue limit load, Cu	2.33 kN
f0	16.1
Nlim (oil)	3,000 Tr/min
Nlim (grease)	2,600 Tr/min
Min operating temperature, Tmin	-60 °C
Characteristic cage frequency, FTF	0.47 Hz
Characteristic rolling element frequency, BSF	14.94 Hz
Characteristic outer ring frequency, BPF0	11.67 Hz
Characteristic inner ring frequency, BPF1	13.33 Hz



Abutment dimensions

da min	186.50 mm
Da max	218.50 mm
ra max	1 mm

Calculation factors

Equivalent dynamic radial load

$$P = X \cdot Fr + Y \cdot Fa$$

$\frac{f_0 F_a}{C_0}$	e	$F_a / Fr \leq e$		$F_a / Fr > e$	
		X	Y	X	Y
0.172	0.19	1	0	0.56	2.3
0.345	0.22				1.99
0.689	0.26				1.71
1.03	0.28				1.55
1.38	0.3				1.45
2.07	0.34				1.31
3.45	0.38				1.15
5.17	0.42				1.04
6.89	0.44				1

Equivalent static radial load

$$P_0 = X_0 \cdot Fr + Y_0 \cdot Fa$$

X_0	Y_0
0.6	0.5

For single or DT bearing arrangement:

If $P_0 < Fr$, then use $P_0 = Fr$