



PDF technical sheet 6204ZZC3




Single row deep groove ball bearings

Deep groove ball bearing, radial contact, pressed steel cage, shields on both sides

Product definition	
d	20 mm
D	47 mm
B	14 mm
d1	26.50 mm
D1	41.70 mm
rs min	1 mm
Radial clearance class	C3
Mass	0.10 kg
Brand	SNR



Product performance	
Dynamic load, C	13.70 kN
Static load, C0	6.70 kN
Fatigue limit load, Cu	0.42 kN
f0	12.6
Nref	16,000 Tr/min
Nlim	20,000 Tr/min
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.37 Hz
Characteristic rolling element frequency, BSF	3.61 Hz
Characteristic outer ring frequency, BPF0	2.60 Hz
Characteristic inner ring frequency, BPF1	4.41 Hz



Abutment dimensions

da min	25 mm
da max	26.50 mm
Da max	42 mm
ra max	1 mm

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

$\frac{f_0 F_a}{C_0}$	e	$F_a / F_r \leq e$		$F_a / F_r > e$	
		X	Y	X	Y
0.172	0.19	1	0	0.56	2.3
0.345	0.22				1.99
0.689	0.26				1.71
1.03	0.28				1.55
1.38	0.3				1.45
2.07	0.34				1.31
3.45	0.38				1.15
5.17	0.42				1.04
6.89	0.44				1

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X_0	Y_0
0.6	0.5

For single or DT bearing arrangement:

If $P_0 < F_r$, then use $P_0 = F_r$