


PDF technical sheet


7211HG1UJ84




High precision angular contact ball bearings

High precision angular contact ball bearing, laminated resin cage centred on outer ring

Product definition	
d	55 mm
D	100 mm
B	21 mm
d1	69 mm
D1	85.80 mm
D2	93.02 mm
a	29 mm
Contact angle, α	25 °
rs min	1.50 mm
r1s min	1 mm
f0	14.757
Precision class	P4
Mass	0.62 kg
Brand	SNR



Product performance	
Dynamic load, C	52.90 kN
Static load, C0	41 kN
Fatigue limit load, Cu	2.30 kN
Nlim (oil)	18,500 Tr/min
Nlim (grease)	12,500 Tr/min
Axial displacement K Factor	0.56
Preload level	8
Peloid value	1,400 kN
axial rigidity	300 N/ μ m
radial rigidity	588 N/ μ m
Min operating temperature, Tmin	-30 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.42 Hz
Characteristic rolling element frequency, BSF	5.27 Hz
Characteristic outer ring frequency, BPF0	6.25 Hz
Characteristic inner ring frequency, BPF1	8.75 Hz



Abutment dimensions

da min	63.50 mm
db min	63.50 mm
Da max	91.50 mm
Db max	91.50 mm
r1a max	1 mm
ra max	1.50 mm
D6	73.80 mm

Calculation factors

Equivalent dynamic radial load

$$P = X \cdot Fr + Y \cdot Fa$$

Series			e	Single or DT bearing arrangement				DB or DF arrangement			
				Fa / Fr ≤ e		Fa / Fr > e		Fa / Fr ≤ e		Fa / Fr > e	
				X	Y	X	Y	X	Y	X	Y
70 (NTN & SNR) 72 (NTN & SNR) 78 (NTN) 79 (NTN) 719 (SNR)	15°	0.178	0.38	1	0	0.44	1.47	1	1.65	0.72	2.39
		0.357	0.4				1.4		1.57		2.28
		0.714	0.43				1.3		1.46		2.11
		1.07	0.46				1.23		1.38		2
		1.43	0.47				1.19		1.34		1.93
		2.14	0.5				1.12		1.26		1.82
		3.57	0.55				1.02		1.14		1.66
		5.35	0.56						1.12		1.63
		7.14	0.56				1		1.12		1.63
	25°		0.68				0.41		0.87		1.41
	30°		0.8				0.39		0.76		1.24

Equivalent static radial load

$$Po = Xo \cdot Fr + Yo \cdot Fa$$

Series			Single or DT bearing arrangement		DB or DF arrangement	
			X ₀	Y ₀	X ₀	Y ₀
70 (NTN & SNR) 72 (NTN & SNR) 78 (NTN) 79 (NTN) 719 (SNR)	15°		0.5	0.46	1	0.92
	25°			0.38		0.76
	30°			0.33		0.66

For single or DT bearing arrangement :

If $Po < Fr$, then use $Po = Fr$