### Regulation EC No 1907/2006 Art.31

 Productname :
 GEAR & WIRE ROPE LUBE
 Creationdate :
 29.06.17 Version : 1.1

 Ref.Nr.:
 UDS000617\_3\_20170629 (EN)
 Replaces:
 UDS000617\_20170222

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

#### **GEAR & WIRE ROPE LUBE**

Aerosol

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Lubricants

#### 1.3. Details of the supplier of the safety data sheet

CRC Industries UK Ltd.
Ambersil House - Wylds Road
Castlefield Industrial Estate
TA6 4DD Bridgwater Somerset
United Kingdom

Tel.: +44 1278 727200 Fax.: +44 1278 425644 E-mail : hse.uk@crcind.com

### 1.4. Emergency telephone number

(+44)(0)1278 72 7200 (office hours)

## SECTION 2: Hazards identification

## 2.1. Classification of the substance or mixture

# Classification according to Regulation (EC) No 1272/2008

Physical: Aerosols, category 1

Extremely flammable aerosol.

Pressurised container: May burst if heated.

Classification is based on test data.

Health: Skin irritation, category 2 Causes skin irritation.

Specific Target Organ Toxicity - Repeated Exposure Category 2

May cause damage to organs through prolonged or repeated exposure.

Classification based on calculation method.

**Environment:** Hazardous to the aquatic environment, chronic category 3

Harmful to aquatic life with long lasting effects.

Classification based on calculation method.



Ambersil House, Wylds Road, Castlefield Industrial Estate, Bridgwater, Somerset, TA6 4DD

Tel: +44 (0)1278 727200 Fax: +44 (0)1278 425644 web: www.ambersil.com

#### Regulation EC No 1907/2006 Art.31

**GEAR & WIRE ROPE LUBE** Creationdate: 29.06.17 Version: 1.1 Productname: Ref.Nr.: Replaces: UDS000617 20170222 UDS000617\_3\_20170629 (EN)

#### 2.2. Label elements

### Labelling according to Regulation (EC) No 1272/2008

Product identifier: Contains:

Naphtha (petroleum), hydrodesulfurized heavy

Hazard pictogram(s):

Signal word: Danger

Hazard statement(s): H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

H315: Causes skin irritation.

H373: May cause damage to organs through prolonged or repeated exposure

H412: Harmful to aquatic life with long lasting effects.

Precautionary statement(s): P102: Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P260 : Do not breathe dust/fume/gas/mist/vapours/spray.

P410/412: Protect from sunlight. Do not expose to temperatures exceeding

50°C/122°F.

P501-2: Dispose of contents/container to an authorised waste collection point.

### 2.3. Other hazards

No information available

# SECTION 3: Composition/information on ingredients

## 3.1. Substances

Not applicable.

#### 3.2. Mixtures

Hazardous ingredient	Registration number	CAS- nr.	EC-nr	w/w %	Hazard Class and Category	Hazard statement	Notes
Hydrocarbons,C3-4-rich, petroleum distillate Petroleumgas (1,3- butadiene < 0.1%)	01- 2119485926- 20	68512- 91-4	270- 990-9	60- 100	Press. Gas, Flam. Gas	H280,H220	K,G
xylene		1330- 20-7	215- 535-7	5-10	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Asp. Tox. 1	H226,H312,H332,H315,H304	А
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclic	01- 2119475515- 33	-	(927- 510- 4)	5-10	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2	H225,H315,H336,H304,H411	Q



### Regulation EC No 1907/2006 Art.31

**GEAR & WIRE ROPE LUBE** Creationdate: 29.06.17 Version: 1.1 Productname: Ref.Nr.: UDS000617 20170222 UDS000617 3 20170629 (EN) Replaces:

Naphtha (petroleum), hydrodesulfurized heavy	01- 2119458049- 33	64742- 82-1	265- 185-4	1-5	Flam. Liq. 3, STOT SE 3, STOT RE 1, Aquatic Chronic 2, Asp. Tox. 1	H226,H336,H372,H411,H304	В,Р
Amines, coco alkyl	-	61788- 46-3	262- 977-1	0-1	Skin Corr. 1B, Acute Tox. 4, Acute Tox. 1, STOT SE 3, STOT RE 2, Aquatic Acute 1, Aquatic Chronic 1	H314,H302,H304,H335,H373,H400,H410	

#### **Explanation notes**

A: substance with Community workplace exposure limit

B: substance with national established workplace exposure limit

G: exempted from the obligation to register in accordance with art.2(7) of REACH Regulation No 1907/2006

K: not classified as carcinogen, less than 0.1% w/w 1,3-butadiene (Einecs-nr. 203-450-8)

P: not classified as carcinogen, less than 0.1% w/w benzene (Einecs-nr. 200-753-7)

Q: The CAS-no is only an indicative identifier to be used outside the EU for global inventory entries.

(\* Explanation phrases : see chapter 16)

# SECTION 4: First aid measures

### 4.1. Description of first aid measures

Contact with eyes: If substance has got into eyes, immediately wash out with plenty of water

If eye irritation persists: Get medical advice/attention.

Contact with skin: Take off contaminated clothing and wash before reuse.

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation occurs: Get medical advice/attention.

Inhalation: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER or doctor/physician if you feel unwell.

If swallowed do not induce vomiting because of risk of aspiration into the Ingestion:

lungs. If aspiration is suspected obtain immediate medical attention

## 4.2. Most important symptoms and effects, both acute and delayed

Inhalation: Excessive inhalation of solvent vapours may give rise to nausea, headaches

and dizziness

Ingestion: After vomiting of swallowed product aspiration into lungs is likely. Solvents

may induce chemical pneumonia.

Symptoms: sore throat, abdominal pain, nausea, vomiting

Skin contact: Irritating to skin

Symptoms: redness and pain

Eye contact: May cause irritation.

Symptoms: redness and pain

### 4.3. Indication of any immediate medical attention and special treatment needed

General Advice: If you feel unwell, seek medical advice (show the label where possible

If symptoms persist always call a doctor

## SECTION 5: Firefighting measures



Ambersil House, Wylds Road, Castlefield Industrial Estate, Bridgwater, Somerset, TA6 4DD
Tel: +44 (0)1278 727200 Fax: +44 (0)1278 425644 web: www.ambersil.com

### Regulation EC No 1907/2006 Art.31

 Productname :
 GEAR & WIRE ROPE LUBE
 Creationdate :
 29.06.17 Version : 1.1

 Ref.Nr.:
 UDS000617\_3\_20170629 (EN)
 Replaces:
 UDS000617\_20170222

## 5.1. Extinguishing media

foam, carbon dioxide or dry agent

# 5.2. Special hazards arising from the substance or mixture

Aerosols may explode if heated above 50°C Forms hazardous decomposition products CO,CO2

### 5.3. Advice for firefighters

Keep container(s) exposed to fire cool, by spraying with water In case of fire, do not breathe fumes

### SECTION 6: Accidental release measures

## 6.1. Personal precautions, protective equipment and emergency procedures

Shut off all ignition sources Ensure adequate ventilation Wear suitable protective clothing and gloves.

#### 6.2. Environmental precautions

Do not allow to enter public sewers and watercourses

# 6.3. Methods and material for containment and cleaning up

Absorb spillage in suitable inert material

## 6.4. Reference to other sections

For further information see section 8

## SECTION 7: Handling and storage

# 7.1. Precautions for safe handling

Keep away from heat and sources of ignition

Take precautionary measures against static discharges

Equipment should be earthed

Use explosion-proof electrical/ventilating/lighting/.../equipment.

Use only non-sparking tools.

Do not breathe aerosols or vapours.

Ensure adequate ventilation

Avoid contact with skin and eyes.

Wash thoroughly after use

Wear protective gloves/protective clothing/eye protection/face protection.



Tel: +44 (0)1278 727200 Fax: +44 (0)1278 425644 web: www.ambersil.com

### Regulation EC No 1907/2006 Art.31

Productname: **GEAR & WIRE ROPE LUBE** Creationdate: 29.06.17 Version: 1.1 UDS000617\_3\_20170629 (EN) Ref.Nr.: Replaces: UDS000617\_20170222

# 7.2. Conditions for safe storage, including any incompatibilities

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Keep out of reach of children.

## 7.3. Specific end use(s)

Lubricants

# SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

### **Exposure limits:**

Hazardous ingredient	CAS-nr.	method	
EU established exposure limits:			*
xylene	1330-20-7	TWA	50 ppm
		STEL	100 ppm
National established exposure limits, United Kingdom			
xylene	1330-20-7	TWA	50 ppm
		STEL	100 ppm

## 8.2. Exposure controls

Control procedures :	Ensure adequate ventilation Keep away from heat and sources of ignition Take precautionary measures against static discharges
Personal protection :	Take precautions to avoid contact with skin and eyes when handling the product. In all cases handle and use the product in accordance with good industrial hygiene practices. Ensure adequate ventilation
inhalation :	In case of insufficient ventilation, wear suitable respiratory equipment.
recommended respiratory protection:	Air purifying respirator equiped with organic gas/vapor cartridge (type A)
hands and skin :	When handling the product wear chemical-resistant gloves (standard EN 374). Use a reusable glove with a minimum breakthrough time of 30 minutes. The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through.
Recommended gloves:	Nitrile
eyes :	Wear safety eyewear according to EN 166.
Environmental protection:	Avoid release to the environment. Collect spillage.

# SECTION 9: Physical and chemical properties



#### Regulation EC No 1907/2006 Art.31

**GEAR & WIRE ROPE LUBE** Creationdate: 29.06.17 Version: 1.1 Productname: Ref.Nr.: UDS000617 20170222 UDS000617\_3\_20170629 (EN) Replaces:

## 9.1. Information on basic physical and chemical properties

(for aerosols data for the product without propellant)

Propane/butane propelled liquid. Apperance : physical state :

colour: Black.

odour: Characteristic odor. pH: Not applicable.

94 °C Boiling point/range: Flash point: - 4 °C

Evaporation rate: Not available.

Explosion limits: upper limit: 9.4 % lower limit: 0.9 %

Vapour pressure: Not available.

Relative density: 0.862 g/cm3 (@ 20°C). Solubility in water: Insoluble in water

> 200 °C Auto-ignition: Viscosity: Not available.

#### 9.2. Other information

# SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No hazardous reactions known if used for its intended purpose

## 10.2. Chemical stability

Stable

### 10.3. Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose

### 10.4. Conditions to avoid

Avoid overheating

# 10.5. Incompatible materials

Strong oxidising agent

### 10.6. Hazardous decomposition products

CO,CO2

# SECTION 11: Toxicological information



## Regulation EC No 1907/2006 Art.31

Productname: **GEAR & WIRE ROPE LUBE** Creationdate: 29.06.17 Version: 1.1 UDS000617\_20170222 Ref.Nr.: UDS000617\_3\_20170629 (EN) Replaces:

# 11.1. Information on toxicological effects

acute toxicity:	based on available data the classification criteria are not met
skin corrosion/irritation:	Causes skin irritation.
serious eye damage/irritation:	based on available data the classification criteria are not met
respiratory or skin sensitisation:	based on available data the classification criteria are not met
germ cell mutagenicity:	based on available data the classification criteria are not met
carcinogenicity:	based on available data the classification criteria are not met
toxicity for reproduction:	based on available data the classification criteria are not met
STOT-single exposure:	based on available data the classification criteria are not met
STOT repeated exposure:	May cause damage to organs through prolonged or repeated exposure.
aspiration hazard:	based on available data the classification criteria are not met

## Information on likely routes of exposure:

Inhalation :	Inhalation of solvent vapours may give rise to nausea, headaches and dizziness
Ingestion :	After vomiting of swallowed product aspiration into lungs is likely. Solvents may induce chemical pneumonia.
Skin contact :	Irritating to skin
Eye contact :	May cause irritation.

# Toxicological data:

Hazardous ingredient	CAS-nr.	method	
Naphtha (petroleum), hydrodesulfurized heavy	64742-82-1	LD50 oral rat	> 2000 mg/kg
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclic	-	LD50 oral rat	> 5840 mg/kg
		LC50 inhal.rat	23.3 mg/l
		LD50 derm.rat	> 2920 mg/kg

# SECTION 12: Ecological information

# 12.1. Toxicity

Hazardous to the aquatic environment, chronic category 3 Harmful to aquatic life with long lasting effects.

## **Ecotoxicological data:**

Hazardous ingredient	CAS-nr.	method	
Naphtha (petroleum), hydrodesulfurized heavy	64742-82-1	IC50 algae	1 - 10 mg/l
		LC50 fish	10 - 100 mg/l
		EC50 daphnia	10 - 100 mg/l
Hydrocarbons, C7, n-alkanes,isoalkanes, cyclic	-	IC50 algae	10-30 mg/l
		LC50 fish	> 13.4 mg/l
		EC50 daphnia	3 mg/l



## Regulation EC No 1907/2006 Art.31

**GEAR & WIRE ROPE LUBE** Productname: Ref.Nr.: UDS000617\_3\_20170629 (EN)

Creationdate: Replaces:

29.06.17 Version: 1.1 UDS000617 20170222

## 12.2. Persistence and degradability

No information available

# 12.3. Bioaccumulative potential

No information available

### 12.4. Mobility in soil

Insoluble in water

### 12.5. Results of PBT and vPvB assessment

No information available

#### 12.6. Other adverse effects

No information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Product: This material and its container must be disposed of in a safe way.

Do not discharge into drains or the environment, dispose to an authorised

waste collection point.

Contaminated packaging: Disposal should be in accordance with local, state or national legislation

## **SECTION 14: Transport information**

## 14.1. UN number

UN-number: 1950

### 14.2. UN proper shipping name

Proper shipping name: **AEROSOLS** 

### 14.3. Transport hazard class(es)

Class: 2.1 ADR/RID - Classification code:

### 14.4. Packing group

Packing group: Not applicable.



8 / 10

## **CRC Industries UK Limited**

Ambersil House, Wylds Road, Castlefield Industrial Estate, Bridgwater, Somerset, TA6 4DD
Tel: +44 (0)1278 727200 Fax: +44 (0)1278 425644 web: www.ambersil.com

#### Regulation EC No 1907/2006 Art.31

 Productname :
 GEAR & WIRE ROPE LUBE
 Creationdate :
 29.06.17 Version : 1.1

 Ref.Nr.:
 UDS000617\_3\_20170629 (EN)
 Replaces:
 UDS000617\_20170222

#### 14.5. Environmental hazards

ADR/RID - Environmentally hazardous:

IMDG - Marine pollutant: No IATA/ICAO - Environmentally hazardous:

### 14.6. Special precautions for user

ADR/RID - Tunnelcode:	(D)
IMDG - Ems:	F-D, S-U
IATA/ICAO - PAX:	203
IATA/ICAO - CAO	203

## 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable.

# SECTION 15: Regulatory information

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The Safety Data Sheet is compiled according to the current European requirements.

Regulation (EC) No 1907/2006 (REACH) Regulation (EC) No 1272/2008 (CLP)

Dir. 2013/10/EU, 2008/47/EC amendment of the aerosol dispenser directive 75/324/EEC.

## 15.2. Chemical safety assessment

No information available

## SECTION 16: Other information

\*Explanation hazard statements: H220 : Extremely flammable gas.

H225 : Highly flammable liquid and vapour. H226 : Flammable liquid and vapour.

H280 : Contains gas under pressure; may explode if heated.

H302: Harmful if swallowed.

H304: May be fatal if swallowed and enters airways.

H312: Harmful in contact with skin.

H314: Causes severe skin burns and eye damage.

H315 : Causes skin irritation. H332 : Harmful if inhaled.

H335: May cause respiratory irritation. H336: May cause drowsiness or dizziness.

H372: Causes damage to organs through prolonged or repeated exposure. H373: May cause damage to organs through prolonged or repeated exposure



Tel: +44 (0)1278 727200 Fax: +44 (0)1278 425644 web: www.ambersil.com

### Regulation EC No 1907/2006 Art.31

Productname: **GEAR & WIRE ROPE LUBE** Creationdate: 29.06.17 Version: 1.1 UDS000617 20170222 Ref.Nr.: UDS000617 3 20170629 (EN) Replaces:

H400: Very toxic to aquatic life.

H410: Very toxic to aquatic life with long lasting effects. H411: Toxic to aquatic life with long lasting effects.

TWA = time weight average acronyms and synonyms:

STEL = short time exposure limit VOC = volatile organic compounds PBT = persistant bioaccumulative toxic vPvB = very persitant very bioaccumulative

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation.

The information contained herewith is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It does not guarantee any specific properties. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks,no part of these documents may be reproduced by any process without written permission from CRC.

