

1. Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: CHAIN & WIRE LUBRICANT

Article number: R220

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: Tygris Industrial
Unit 31
Kyle Road Industrial Estate
Irvine
Ayshire
KA12 8LE
Tel +44 (0) 1294 311 066
Fax +44 (0) 1294 277 115
Email technical@tygrisindustrial.com

Further information obtainable from: Technical Department

1.4 Emergency telephone number: Tel +44 (0) 1294 311 066

2. Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical and Chemical Hazards
 Human health
 Environment

Flam. Aerosol 1 - H222
 Lact. - H362;STOT SE 3 - H336
 Aquatic Chronic 2 - H411

Classification (1999/45/EEC) F+;R12. N;R51/53. R64, R67.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

2.2. Label elements

Label In Accordance With (EC) No. 1272/2008



Signal Word

Danger

Hazard Statements

H222 Extremely flammable aerosol.
 H336 May cause drowsiness or dizziness.
 H362 May cause harm to breast-fed children.
 H411 Toxic to aquatic life with long lasting effects.

Precautionary Statements

P102 Keep out of reach of children.
 P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 P263 Avoid contact during pregnancy/while nursing.
 P271 Use only outdoors or in a well-ventilated area.
 P261 Avoid breathing vapour/spray.
 P264 Wash contaminated skin thoroughly after handling.
 P501 Dispose of contents/container in accordance with local regulations.

**Supplementary
Precautionary Statements**

P201 Obtain special instructions before use.
 P211 Do not spray on an open flame or other ignition source.
 P251 Pressurized container: Do not pierce or burn, even after use.
 P270 Do not eat, drink or smoke when using this product.
 P302+352 IF ON SKIN: Wash with plenty of soap and water.
 P304+340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
 P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P308+313 IF exposed or concerned: Get medical advice/attention.
 P312 Call a POISON CENTER or doctor/physician if you feel unwell.
 P332+313 If skin irritation occurs: Get medical advice/attention.
 P337+313 If eye irritation persists: Get medical advice/attention.
 P403+233 Store in a well-ventilated place. Keep container tightly closed.
 P410+412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.

2.3. Other hazards

3. Composition/information on ingredients

3.2. Mixtures

BUTANE Index No. CAS-No.: 106-97-8 Classification (EC 1272/2008) Flam. Gas 1 - H220	5-10% REACH Registration No. EC No.: 203-448-7 Classification (67/548/EEC) F+;R12
CHLORINATED PARAFFIN C14-C17 (51%) Index No. CAS-No.: 85535-85-9 Classification (EC 1272/2008) EUH066 Lact. - H362 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410	1-5% REACH Registration No. EC No.: 287-477-0 Classification (67/548/EEC) N;R50/53. R64,R66.
ISOBUTANE Index No. CAS-No.: 75-28-5 Classification (EC 1272/2008) Flam. Gas 1 - H220	1-5% REACH Registration No. EC No.: 200-857-2 Classification (67/548/EEC) F+;R12
MINERAL OIL (REFINED) Index No.: CAS-No.: 64742-52-5 Classification (EC 1272/2008) Not classified.	30-60% REACH Registration No. EC No.: 265-155-0 Classification (67/548/EEC) Not classified.
NAPHTHA (PETROLEUM), HYDROTREATED LIGHT Index No. CAS-No.: 64742-49-0 Classification (EC 1272/2008) Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	10-30% REACH Registration No. 01-2119475514-35-xxxx EC No.: 921-024-6 Classification (67/548/EEC) Xn;R65. Xi;R38. F;R11. N;R51/53. R67.
PROPANE Index No. CAS-No.: 74-98-6 Classification (EC 1272/2008) Flam. Gas 1 - H220	10-30% REACH Registration No. EC No.: 200-827-9 Classification (67/548/EEC) F+;R12

WHITE SPIRIT Index No. CAS-No.: 64742-82-1 Classification (EC 1272/2008) Flam. Liq. 3 - H226 EUH066 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	<1% REACH Registration No. EC No.: 919-446-0 Classification (67/548/EEC) Xn;R65. N;R51/53. R10,R66.
XYLENE Index No. CAS-No.: 1330-20-7 Classification (EC 1272/2008) Flam. Liq. 3 - H226 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Asp. Tox. 1 - H304	<1% REACH Registration No. EC No.: 215-535-7 Classification (67/548/EEC) R10 Xn;R20/21 Xi;R38

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16

4. First aid measures

4.1. Description of first aid measures

General information	Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.
Inhalation	Move the exposed person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Keep the affected person warm and at rest. Get prompt medical attention.
Ingestion	DO NOT INDUCE VOMITING! Rinse mouth thoroughly with water and give large amounts of milk or water to people not unconscious. Get medical attention if any discomfort continues.
Skin contact	Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.
Eye contact	Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

5. Firefighting measures

5.1 Extinguishing Media

Extinguishing media Use: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

5.2. Special hazards arising from the substance or mixture

Unusual Fire & Explosion Hazards Aerosol cans may explode in a fire.

5.3. Advice for firefighters

Special Fire Fighting Procedures Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.2. Environmental precautions

6.3. Methods and material for containment and cleaning up

Wear necessary protective equipment. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Let evaporate. Keep out of confined spaces because of explosion risk. If leakage cannot be stopped, evacuate area.

6.4. Reference to other sections

7. Handling and storage

7.1 Precautions for safe handling

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

7.2. Conditions for safe storage, including any incompatibilities

Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

7.3. Specific end use(s)

8. Exposure controls/personal protection

8.1. Control parameters

Name	STD	TWA - 8 Hrs		STEL - 15 Min	
BUTANE	WEL	600 ppm	1450 mg/m3	750 ppm	1810 mg/m3
ISOBUTANE	WEL	800 ppm		800 ppm	
MINERAL OIL (REFINED)			5 mg/m3		10 mg/m3
NAPHTHA (PETROLEUM), HYDROTREATED LIGHT			1200 mg/m3	60 ppm	216 mg/m3
PROPANE		Asphyxiating	Asphyxiating	Asphyxiating	Asphyxiating
WHITE SPIRIT			600 mg/m3		
XYLENE	WEL	50 ppm(Sk)	220 mg/ m3(Sk)	100 ppm(Sk)	441 mg/ m3(Sk)

WEL = Workplace Exposure Limits

8.2. Exposure controls

Protective equipment



Engineering measures

Provide adequate general and local exhaust ventilation.

Respiratory equipment

No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit. Use chemical cartridge protection with appropriate cartridge.

Hand protection

Use protective gloves.

Eye protection

Wear approved chemical safety goggles where eye exposure is reasonably probable.

Other Protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

Hygiene measures

DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Aerosol
Colour	Typical
Odour	Characteristic.
Flammability Limit - Lower(%)	0.8
Flammability Limit - Upper(%)	9.0

9.2. Other information

10. Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

Stable under normal temperature conditions.

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition. Avoid contact with: Strong oxidising agents. Strong alkalis. Strong mineral acids.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO₂).

11. Toxicological information

11.1. Information on toxicological effects

Inhalation	May cause irritation to the respiratory system. Vapours may cause headache, fatigue, dizziness and nausea. Prolonged inhalation of high concentrations may damage respiratory system.
Ingestion	May cause discomfort if swallowed. May cause stomach pain or vomiting. Gastrointestinal symptoms, including upset stomach.
Skin contact	Prolonged or repeated exposure may cause severe irritation. Acts as a defatting agent on skin. May cause cracking of skin, and eczema.
Eye contact	Irritating to eyes. May cause chemical eye burns.
Route of entry	Inhalation. Skin and/or eye contact.

12. Ecological information

Ecotoxicity

Dangerous for the environment if discharged into watercourses.

12.1. Toxicity

12.2. Persistence and degradability

12.3. Bioaccumulative potential

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

13. Disposal considerations

13.1. Waste treatment methods	Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements.
--------------------------------------	---

14. Transport information
14.1. UN number

UN No. (ADR/RID/ADN) 1950

UN No. (IMDG) 1950

UN No. (ICAO) 1950

14.2. UN proper shipping name

Proper Shipping Name AEROSOLS

14.3. Transport hazard class(es)

ADR/RID/ADN Class 2

ADR/RID/ADN Class Class 2: Gases

ADR Label No. 2.1

IMDG Class 2.1

ICAO Class/Division 2.1

Transport Labels

14.4. Packing group

ADR/RID/ADN Packing group Not Applicable

IMDG Packing group Not Applicable

ICAO Packing group Not applicable.

14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant No.

14.6. Special precautions for user

EMS F-D, S-U

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Uk Regulatory References	The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002. The Control of Substances Hazardous to Health Regulations 2002.
Statutory Instruments	Control of Substances Hazardous to Health. The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716).
Approved Code Of Practice	Classification and Labelling of Substances and Preparations Dangerous for Supply.
Guidance Notes	Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG(108).

15.2. Chemical safety assessment

16. Other information

Risk Phrases In Full	R12 Extremely flammable. R10 Flammable. R20/21 Harmful by inhalation and in contact with skin. R65 Harmful: may cause lung damage if swallowed. R11 Highly flammable R38 Irritating to skin. R64 May cause harm to breastfed babies. R66 Repeated exposure may cause skin dryness or cracking. R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R67 Vapours may cause drowsiness and dizziness. R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Hazard Statements In Full	H372 Causes damage to organs <<Organs>> through prolonged or repeated exposure if inhaled. H315 Causes skin irritation. H222 Extremely flammable aerosol. H220 Extremely flammable gas. H226 Flammable liquid and vapour. H332 Harmful if inhaled. H312 Harmful in contact with skin. H225 Highly flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H336 May cause drowsiness or dizziness. H362 May cause harm to breast-fed children. EUH066 Repeated exposure may cause skin dryness or cracking. H411 Toxic to aquatic life with long lasting effects. H410 Very toxic to aquatic life with long lasting effects. H400 Very toxic to aquatic life.

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.