Regulation EC No 1907/2006 Art.31

 Productname :
 MACHINE OIL FG
 Creationdate :
 29.06.17 Version : 3.0

 Ref.Nr.:
 BDS000677_3_20170629 (EN)
 Replaces:
 BDS000677_20130823

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

MACHINE OIL FG

Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

Lubricants

1.3. Details of the supplier of the safety data sheet

CRC Industries UK Ltd. Ambersil House - Wylds Road Castlefield Industrial Estate TA6 4DD Bridgwater Somerset United Kingdom

Tel.: +44 1278 727200 Fax.: +44 1278 425644 E-mail: hse.uk@crcind.com

1.4. Emergency telephone number

(+44)(0)1278 72 7200 (office hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Physical: Aerosols, category 1

Extremely flammable aerosol.

Pressurised container: May burst if heated.

Classification is based on test data.

Health: Not classified
Classification based on calculation method.
Environment: Not classified
Classification based on calculation method.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008



Regulation EC No 1907/2006 Art.31

MACHINE OIL FG Creationdate: 29.06.17 Version: 3.0 Productname: Ref.Nr.: BDS000677 20130823 BDS000677_3_20170629 (EN) Replaces:

Hazard pictogram(s):

Signal word: Danger

Hazard statement(s): H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

Precautionary statement(s): P102: Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P410/412: Protect from sunlight. Do not expose to temperatures exceeding

50°C/122°F.

Supplemental Hazard

information:

Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

No information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable.

3.2. Mixtures

Hazardous ingredient	Registration number	CAS-nr.	EC-nr	w/w %	Hazard Class and Category	Hazard statement	Notes
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics	01-2119456620- 43	-	(926- 141-6)	50- 75	Asp. Tox. 1	H304	B,Q
white mineral oil (petroleum)	01-2119487078- 27	8042- 47-5	232-455- 8	25- 50		-	В
carbon dioxide	-	124-38- 9	204-696- 9	1-5	Press. Gas	H280	A,G
Explanation notes							

A: substance with Community workplace exposure limit

B: substance with national established workplace exposure limit

G: exempted from the obligation to register in accordance with art.2(7)of REACH Regulation No 1907/2006

Q: The CAS-no is only an indicative identifier to be used outside the EU for global inventory entries.

(* Explanation phrases : see chapter 16)

SECTION 4: First aid measures

4.1. Description of first aid measures

If substance has got into eyes, immediately wash out with plenty of water Contact with eyes :

If eye irritation persists: Get medical advice/attention.



Ambersil House, Wylds Road, Castlefield Industrial Estate, Bridgwater, Somerset, TA6 4DD
Tel: +44 (0)1278 727200 Fax: +44 (0)1278 425644 web: www.ambersil.com

Regulation EC No 1907/2006 Art.31

 Productname :
 MACHINE OIL FG
 Creationdate :
 29.06.17 Version : 3.0

 Ref.Nr.:
 BDS000677_3_20170629 (EN)
 Replaces:
 BDS000677_20130823

Contact with skin : Wash with plenty of soap and water.

If skin irritation occurs: Get medical advice/attention.

Inhalation: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER or doctor/physician if you feel unwell.

Ingestion: If swallowed do not induce vomiting because of risk of aspiration into the

lungs. If aspiration is suspected obtain immediate medical attention

4.2. Most important symptoms and effects, both acute and delayed

Inhalation: Excessive inhalation of solvent vapours may give rise to nausea, headaches

and dizziness

Ingestion: After vomiting of swallowed product aspiration into lungs is likely. Solvents

may induce chemical pneumonia.

Symptoms: sore throat, abdominal pain, nausea, vomiting

Skin contact: May cause irritation.

Symptoms: redness and pain

Eye contact : May cause irritation.

Symptoms: redness and pain

4.3. Indication of any immediate medical attention and special treatment needed

General Advice: If you feel unwell, seek medical advice (show the label where possible

If symptoms persist always call a doctor

SECTION 5: Firefighting measures

5.1. Extinguishing media

foam, carbon dioxide or dry agent

Do not use water jet extinguishing media, due to the risk of spreading fire.

5.2. Special hazards arising from the substance or mixture

Aerosols may explode if heated above 50°C Forms hazardous decomposition products CO,CO2

5.3. Advice for firefighters

Keep container(s) exposed to fire cool, by spraying with water In case of fire, do not breathe fumes

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Shut off all ignition sources
Ensure adequate ventilation
Wear suitable protective clothing and gloves.



Regulation EC No 1907/2006 Art.31

 Productname :
 MACHINE OIL FG
 Creationdate :
 29.06.17 Version : 3.0

 Ref.Nr.:
 BDS000677_3_20170629 (EN)
 Replaces:
 BDS000677_20130823

6.2. Environmental precautions

Do not allow to enter public sewers and watercourses

If polluted water reaches drainage systems or water courses, immediately inform appropriate authorities

6.3. Methods and material for containment and cleaning up

Absorb spillage in suitable inert material

6.4. Reference to other sections

For further information see section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep away from heat and sources of ignition

Take precautionary measures against static discharges

Equipment should be earthed

Use explosion-proof electrical/ventilating/lighting/.../equipment.

Use only non-sparking tools.

Do not breathe aerosols or vapours.

Ensure adequate ventilation

Avoid contact with skin and eyes.

Wash thoroughly after use

Wear protective gloves/protective clothing/eye protection/face protection.

7.2. Conditions for safe storage, including any incompatibilities

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Keep out of reach of children.

7.3. Specific end use(s)

Lubricants

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits:

Hazardous ingredient	CAS-nr.	method	
EU established exposure limits:			
carbon dioxide	124-38-9	TWA	9000 mg/m3
		STEL	1800 mg/m3
National established exposure limits, United Kingdom		-	-



Regulation EC No 1907/2006 Art.31

 Productname :
 MACHINE OIL FG
 Creationdate :
 29.06.17 Version : 3.0

 Ref.Nr.:
 BDS000677_3_20170629 (EN)
 Replaces:
 BDS000677_20130823

carbon dioxide	124-38-9	TWA	5000 ppm
		STEL	15000 ppm

8.2. Exposure controls

Control procedures : Ensure adequate ventilation

Keep away from heat and sources of ignition

Take precautionary measures against static discharges

Personal protection: Take precautions to avoid contact with skin and eyes when handling the

product.

It is good practice to wear gloves and to provide adequate ventilation

whenever using the product.

In all cases handle and use the product in accordance with good industrial

hygiene practices.

inhalation : In case of insufficient ventilation, wear suitable respiratory equipment.

recommended respiratory protection: Air purifying respirator equiped with organic gas/vapor cartridge (type A)

hands and skin:

If handled correctly skin exposure will be accidental. In such case the use of disposable gloves should be sufficient provided they are changed immediately

after a splash or spill may occur. If intentional contact is expected reusable gloves should be used with a breakthrough time greater than the total duration

of the product use.

Recommended gloves: Nitrile

eyes: Wear safety eyewear according to EN 166.

Environmental protection: Avoid release to the environment.

Collect spillage.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

(for aerosols data for the product without propellant)

Apperance : physical state : CO2 propelled liquid. colour : Colorless.

odour:

pH:

Not applicable.

Boiling point/range:

Not available.

Flash point:

Fvaporation rate:

Explosion limits: upper limit:

Not available.

Not available.

Not available.

Not available.

Not available.

Not available.

Relative density: 0.82 g/cm3 (@ 20°C).
Solubility in water: Insoluble in water

Auto-ignition: > 200 °C

Viscosity: 3.91 mPa.s (@ 20°C).

9.2. Other information

VOC = volatile organic compounds

515 g/l



Regulation EC No 1907/2006 Art.31

Productname: Ref.Nr.:

MACHINE OIL FG

BDS000677_3_20170629 (EN)

Creationdate: Replaces:

29.06.17 Version: 3.0 BDS000677 20130823

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reactions known if used for its intended purpose

10.2. Chemical stability

Stable

10.3. Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose

10.4. Conditions to avoid

Avoid overheating

10.5. Incompatible materials

Strong oxidising agent

10.6. Hazardous decomposition products

CO,CO2

SECTION 11: Toxicological information

11.1. Information on toxicological effects

acute toxicity:	based on available data the classification criteria are not met
skin corrosion/irritation:	based on available data the classification criteria are not met
serious eye damage/irritation:	based on available data the classification criteria are not met
respiratory or skin sensitisation:	based on available data the classification criteria are not met
germ cell mutagenicity:	based on available data the classification criteria are not met
carcinogenicity:	based on available data the classification criteria are not met
toxicity for reproduction:	based on available data the classification criteria are not met
STOT-single exposure:	based on available data the classification criteria are not met
STOT repeated exposure:	based on available data the classification criteria are not met
aspiration hazard:	based on available data the classification criteria are not met

Information on likely routes of exposure:

Inhalation:	Inhalation of solvent vapours may give rise to nausea, headaches	and
illilaiauvii .	HIHAIAUUH ULSUIVEHLVADUUIS HIAV UIVE HSE IU HAUSEA. HEAUAGHES	ancı

dizziness

Ingestion: After vomiting of swallowed product aspiration into lungs is likely. Solvents

may induce chemical pneumonia.

Skin contact: Prolonged skin contact will result in defatting of the skin, leading to irritation,



Regulation EC No 1907/2006 Art.31

Productname: MACHINE OIL FG Creationdate: 29.06.17 Version: 3.0 Ref.Nr.: Replaces: BDS000677_20130823 BDS000677_3_20170629 (EN)

and in some cases, dermatitis

Repeated exposure may cause skin dryness or cracking.

Eye contact: May cause irritation.

Toxicological data:

Hazardous ingredient	CAS-nr.	method	
white mineral oil (petroleum)	8042-47-5	LD50 oral rat	> 5000 mg/kg
		LC50 inhal.rat	> 5 mg/l
		LD50 derm.rabit	> 2000 mg/kg
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics	-	LD50 oral rat	> 5000 mg/kg
		LC50 inhal.rat	>5000 mg/kg
		LD50 derm.rabit	> 5000 mg/kg

SECTION 12: Ecological information

12.1. Toxicity

Not classified

Ecotoxicological data:

Hazardous ingredient	CAS-nr.	method	
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics	-	IC50 algae	1000 mg/l
		LC50 fish	1000 mg/l
		EC50 daphnia	1000 mg/l

12.2. Persistence and degradability

No experimental data available

12.3. Bioaccumulative potential

No experimental data available

12.4. Mobility in soil

Insoluble in water

12.5. Results of PBT and vPvB assessment

No information available

12.6. Other adverse effects

No experimental data available



Regulation EC No 1907/2006 Art.31

MACHINE OIL FG Productname:

Ref.Nr.: BDS000677_3_20170629 (EN)

Creationdate: Replaces:

29.06.17 Version: 3.0 BDS000677 20130823

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product: This material and its container must be disposed of in a safe way.

Do not discharge into drains or the environment, dispose to an authorised

waste collection point.

National regulations: Disposal should be in accordance with local, state or national legislation

SECTION 14: Transport information

14.1. UN number

UN-number: 1950

14.2. UN proper shipping name

Proper shipping name: **AEROSOLS**

14.3. Transport hazard class(es)

Class: 2.1 ADR/RID - Classification code: 5F

14.4. Packing group

Not applicable. Packing group:

14.5. Environmental hazards

ADR/RID - Environmentally No hazardous: IMDG - Marine pollutant: No IATA/ICAO - Environmentally No hazardous:

14.6. Special precautions for user

ADR/RID - Tunnelcode: (D) IMDG - Ems: F-D, S-U IATA/ICAO - PAX: 203 IATA/ICAO - CAO 203

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable.



Regulation EC No 1907/2006 Art.31

MACHINE OIL FG Productname:

Ref.Nr.: BDS000677 3 20170629 (EN)

Creationdate: Replaces:

29.06.17 Version: 3.0 BDS000677 20130823

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The Safety Data Sheet is compiled according to the current European requirements.

Regulation (EC) No 1907/2006 (REACH) Regulation (EC) No 1272/2008 (CLP)

Dir. 2013/10/EU, 2008/47/EC amendment of the aerosol dispenser directive 75/324/EEC.

European data	
Storage Class:	Storag Class 2B: Aerosol dispensers and lighters
Storage Class:	Storag Class 2B: Aerosol dispensers and lighters
Storage Class:	Storag Class 2B: Aerosol dispensers and lighters
Storage Class:	Storag Class 2B: Aerosol dispensers and lighters

15.2. Chemical safety assessment

No information available

SECTION 16: Other information

*Explanation hazard statements: -:-

H280: Contains gas under pressure; may explode if heated.

H304: May be fatal if swallowed and enters airways.

REVISIONS IN CHAPTRE: 8.2. Exposure controls

TWA = time weight average acronyms and synonyms:

STEL = short time exposure limit VOC = volatile organic compounds PBT = persistant bioaccumulative toxic vPvB = very persitant very bioaccumulative

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation.

The information contained herewith is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It does not guarantee any specific properties. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks,no part of these documents may be reproduced by any process without written permission from CRC.

