

SAFETY DATA SHEET

PROTEAN PTFE DRY FILM LUBRICANT F410

1. Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: PROTEAN PTFE DRY FILM LUBRICANT

Article number: F410

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC24: Lubricants, greases, release products.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: TYGRIS Industrial

Unit 31

Kyle Road Industrial Estate

Irvine Ayrshire KA12 8LE

Tel +44 (0) 1294 311 066 Fax +44 (0) 1294 277 115

Email technical@tygrisindustrial.com

Further information obtainable from:

Technical Department

1.4 Emergency telephone number:

Tel +44 (0) 1294 311 066



Compilation Date: 04/09/2018



SAFETY DATA SHEET

PROTEAN PTFE DRY FILM LUBRICANT F410

2. Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Flam. Aerosol 1: H222; Aquatic Chronic 2: H411; STOT SE 3: H336; -: EUH066;

-: H229

Most important adverse

effects:

Repeated exposure may cause skin dryness or cracking. Extremely flammable aerosol. Pressurised container: May burst if heated. May cause drowsiness or

dizziness. Toxic to aquatic life with long lasting effects.

2.2. Label elements

EUH066: Repeated exposure may cause skin dryness or cracking. Hazard statements:

H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark





Signal word: Danger

Precautionary statements: P102: Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P304+340: IF INHALED: Remove person to fresh air and keep comfortable for

P410+412: Protect from sunlight. Do not expose to temperatures exceeding 50°C.

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

3. Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

PENTANE - REACH registered number(s): 01-2119459286-30

| EINECS | CAS | PBT / WEL | CLP Classification | Percent |
|-----------|----------|-----------|--|---------|
| 203-692-4 | 109-66-0 | - | Flam. Liq. 2: H225; Asp. Tox. 1: H304; STOT SE 3: H336; Aquatic Chronic 2: H411; -: EUH066 | 10-30% |

Compilation Date: 04/09/2018



PROTEAN PTFE DRY FILM LUBRICANT F410

8. Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

PENTANE

Workplace exposure limits:

Respirable dust:

| State | 8 hour TWA | 15 min. STEL | 8 hour TWA | 15 min. STEL |
|-------|------------|--------------|------------|--------------|
| UK | 1800 mg/m3 | - | - | - |

DNEL/PNEC Values

DNEL/PNEC: No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory equipment: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves. Chemically resistant gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Environmental: Not applicable.

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Aerosol
Colour: White

Odour: Characteristic odour

Solubility in water: Insoluble

Also soluble in: Most organic solvents

Flash point°C: -60
Relative density: 0.72

9.2. Other information

Other information: No data available.