

LA-CO Industries, Inc.

B Paintstik® MARKER 1 White, ½ Hex Blue, ½ Hex White, ½ Hex Yellow, 16 Black, 16 Orange, 16 White, 16 Yellow, 3/8 Yellow, Aluminum, Black, Blue, Green, Gray, Orange, Pink, Purple, Red, Silver, White, Yellow

Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 25/09/2015

Revision date:

Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form

: Mixture

Trade name

: B Paintstik® MARKER 1 White, ½ Hex Blue, ½ Hex White, ½ Hex Yellow, 16 Black, 16 Orange, 16 White, 16 Yellow, 3/8 Yellow, Aluminum, Black, Blue, Green, Gray, Orange, Pink, Purple, Red, Silver, White, Yellow

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture

: Marking.

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

LA-CO Industries Europe S.A.S.
Parc Industriel de la Plaine de
l'Ain - Allée des Combes.
01150.BLYES.France.
Phone: +33 (0)4 74 46 23 23
Fax: +33 (0)4 74 46 23 29
E-mail: info@eu.laco.com
Web: http://www.markal.com

1.4. Emergency telephone number

Emergency number : 24-hour emergency: CHEMTREC- U.S. : 1-800-424-9300 International: +1-703-527-3887

EU Member State	Officieel adviesorgaan	Adres	Noodnummer
AUSTRIA	Vergiftungsinformationszentrale (Poisons Information Centre)	Allgemeines Krankenhaus Waehringer Geurtel 18-20 1090 Wien	+43 1 406 43 43
BELARUS	The Belarus Republican Poisons Centre	Kizhevatova str. 58 Minsk 220115	+375 (0)17 201 9158
BELGIUM	Centre Anti-Poisons/Antigifcentrum c/o Hôpital Central de la Base - Reine Astrid	Rue Bruyn 1 B -1120 Bruxelles/Brussel	+32 70 245 245
BULGARIA	Национален токсикологичен информационен център National Clinical Toxicology Centre, Emergency Medical Institute "Pirogov"	21 Tottleben Boulevard 1606 SOFIA	+359 2 9154 409
CROATIA	Poisons Control Centre Institute of Medical Research & Occupational Health	Ksaverska Cesta 2 P.O. Box 291 HR-10000 Zagreb	+385 1 234 8342
CZECH REPUBLIC	Toxikologické informační středisko Clinic For Occupational Medicine, 1st Medical Faculty, Charles University	Na Bojišti 1 120 00 Praha 2	+42 2 2491 9293 +42 2 2491 5402
DENMARK	Giftlinjen Bispebjerg Hospital	Bispebjerg Bakke 23, 60, 1 DK-2400 København NV	+45 82 12 12 12 +45 35 31 55 55
ESTONIA	Mürgistusteabekeskus	Gonsiori 29 15027 Tallinn	+372 626 93 90
FINLAND	Myrkytystietokeskus	P.O.B 340 (Haartmaninkatu 4) HUS SF - 00029 Helsinki	+358 9 471 977
FRANCE	ORFILA		+33 1 45 42 59 59
GERMANY	Berliner Betrieb für Zentrale Gesundheitliche Aufgaben	Oranienburger Strasse 285 13437 Berlin	+49 30 19240
GERMANY	Informations und Beratungszentrum für Vergiftungsfälle	Kirrberger Straße, Gebäude 9 D-66421 Homburg/Saar	+49 6841 19240
GERMANY	Beratungstelle bei Vergiftungen, Klinische Toxikologie und Beratungsstelle bei Vergiftungen	Langenbeckstrasse 1 55131 Mainz	+49 6131 19240
GREECE	Poisons Information Centre	11527 Athens	+30 10 779 3777

B Paintstik® MARKER 1 White, ½ Hex Blue, ½ Hex White, ½ Hex Yellow, 16 Black, 16 Orange, 16 White, 16 Yellow, 3/8 Yellow, Aluminum, Black, Blue, Green, Gray, Orange, Pink, Purple, Red, Silver, White, Yellow

Safety Data Sheet

according to Regulation (EU) 2015/830

HUNGARY	Országos Kémiai Biztonsági Intézet (National Institute of Chemical Safety) Egészségügyi Toxikológiai Tájékoztató Szolgálat (Health Toxicological Information Service)	1437 Budapest PO Box 839 1097 Budapest, Nagyvárad tér 2	+36 80 20 11 99
ICELAND	Eitrunarmiðstöðin	Eitrunarmiðstöðin 108 Reykjavík	+354 543 22 22
IRELAND	National Poisons Information Centre	Beaumont Hospital PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2166
LATVIA	Valsts Toksikoloģijas centra Saindēšanās un zāļu informācijas centrs	2 Hipocrate Street LV 1038 Riga	+371 67 04 24 73
LITHUANIA	Apsinuodijimų kontrolės ir informacijos biuras	Siltnamiu 29 2043 Vilnius	+370 5 236 20 52/+370 687 53 378
MALTA	Medicines & Poisons Info Office	Mater Dei Hospital, Msida MSD 2090 Malta	25450000
NETHERLANDS	Nationaal Vergiftigingen Informatie Centrum National Institute for Public Health and the Environment, NB this service is only available to health professionals	Huispostnummer B.00.118, PO Box 85500 3508 GA Utrecht	+31 30 274 88 88
PORTUGAL	Centro de Informação Antivenenos Instituto Nacional de Emergência Médica (INEM)	Rua Almirante Barroso, 36 1000-013 Lisboa	808 250 143 (for use only in Portugal), +351 21 330 3284
ROMANIA	Biroul pentru Regulamentul Sanitar International si Informare Toxicologica	Str. Dr. Leonte Anastasievici Nr.1-3, Sector 5 50463 Bucuresti	+40 21 318 36 06
SLOVAKIA	Národné toxikologické informačné centrum University Hospital Bratislava	Limbová 5 833 05 Bratislava	+421 2 54 77 4 166
SPAIN	Servicio de Información Toxicológica Instituto Nacional de Toxicología, Departamento de Madrid	Calle Luis Cabrera 9 E-28002 Madrid	+34 91 562 04 20
SWEDEN	Giftinformationscentralen Swedish Poisons Information Centre, Karolinska Hospital	Box 60 500 SE-171 76 Stockholm	+46 8 33 12 31 (International) 112 (National)
SWITZERLAND	Centre Suisse d'Information Toxicologique	Freiestrasse 16 Postfach CH-8028 Zurich	+41 44 251 51 51 (International) 145 (National)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Unknown acute toxicity (CLP: Classification, Labelling, Packaging.) - SDS : 1.1% of the mixture consists of ingredient(s) of unknown acute oral toxicity
1.1% of the mixture consists of ingredient(s) of unknown acute dermal toxicity
1.1% percent of the mixture consists of ingredient(s) of unknown acute inhalation (dust/mist) toxicity

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
limestone	(CAS No) 1317-65-3 (EC no) 215-279-6	30 – 60	Not classified
aluminium powder (pyrophoric)	(CAS No) 7429-90-5 (EC no) 231-072-3 (EC index no) 013-001-00-6	0 – 30	Pyr. Sol. 1, H250 Water-react. 2, H261

B Paintstik® MARKER 1 White, ½ Hex Blue, ½ Hex White, ½ Hex Yellow, 16 Black, 16 Orange, 16 White, 16 Yellow, 3/8 Yellow, Aluminum, Black, Blue, Green, Gray, Orange, Pink, Purple, Red, Silver, White, Yellow

Safety Data Sheet

according to Regulation (EU) 2015/830

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Paraffin waxes and Hydrocarbon waxes	(CAS No) 8002-74-2 (EC no) 232-315-6	0 – 20	Not classified
titanium dioxide	(CAS No) 13463-67-7 (EC no) 236-675-5	0 – 15	Not classified
rosin	(CAS No) 8050-09-7 (EC no) 232-475-7 (EC index no) 650-015-00-7	1 – 5	Skin Sens. 1, H317
Carbon black	(CAS No) 1333-86-4 (EC no) 215-609-9	0 – 5	Carc. 2, H351
Silicon dioxide (cristobalite)	(CAS No) 14808-60-7 (EC no) 238-878-4	0 – 2	Carc. 1A, H350i
Aluminum hydroxide	(CAS No) 21645-51-2 (EC no) 244-492-7	0 – 1	Not classified
4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol <1%)	(CAS No) 2786-76-7 (EC no) 220-509-3	0 – 1	Skin Sens. 1, H317
Silicon dioxide (amorphous)	(CAS No) 7631-86-9 (EC no) 231-545-4	0 – 1	Not classified
Distillates (petroleum), hydrotreated light	(CAS No) 64742-47-8 (EC no) 265-149-8 (EC index no) 649-422-00-2	< 0.1	Asp. Tox. 1, H304
Stoddard solvent (benzene < 0.1%)	(CAS No) 8052-41-3 (EC no) 232-489-3 (EC index no) 649-345-00-4	< 0.1	Flam. Liq. 3, H226 STOT RE 1, H372 Asp. Tox. 1, H304
Naphtha (petroleum), hydrodesulfurized heavy (benzene < 0.1%)	(CAS No) 64742-82-1 (EC no) 265-185-4 (EC index no) 649-330-00-2	< 0.1	STOT RE 1, H372 Asp. Tox. 1, H304
Aluminum oxide	(CAS No) 1344-28-1 (EC no) 215-691-6	< 0.1	Not classified
Zirconium oxide	(CAS No) 1314-23-4 (EC no) 215-227-2 (REACH-no) 01-2119486976-14	< 0.1	Not classified
Iron oxide red	(CAS No) 1309-37-1 (EC no) 215-168-2	< 0.1	Aquatic Chronic 2, H411
nickel dihydroxide	(CAS No) 12054-48-7 (EC no) 235-008-5 (EC index no) 028-008-00-X	< 0.1	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315 Resp. Sens. 1, H334 Skin Sens. 1, H317 Muta. 2, H341 Carc. 1A, H350i Repr. 1B, H360D STOT RE 1, H372 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,6-Di-tert-butyl-4-methylphenol	(CAS No) 128-37-0 (EC no) 204-881-4	< 0.1	STOT RE 2, H373 Aquatic Acute 1, H400

Full text of R- and H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
First-aid measures after skin contact	: Wash with plenty of soap and water.
First-aid measures after eye contact	: In case of contact, immediately flush eyes with plenty of water.
First-aid measures after ingestion	: Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation	: May cause respiratory irritation.
------------------------------------	-------------------------------------

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

B Paintstik® MARKER 1 White, ½ Hex Blue, ½ Hex White, ½ Hex Yellow, 16 Black, 16 Orange, 16 White, 16 Yellow, 3/8 Yellow, Aluminum, Black, Blue, Green, Gray, Orange, Pink, Purple, Red, Silver, White, Yellow

Safety Data Sheet

according to Regulation (EU) 2015/830

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.
Unsuitable extinguishing media : None known.

5.2. Special hazards arising from the substance or mixture

Fire hazard : No particular fire or explosion hazard.

5.3. Advice for firefighters

Firefighting instructions : Keep upwind.
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Use self-contained breathing apparatus. EN469.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Avoid creating or spreading dust.

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Emergency procedures : Ventilate area. Stop leak if safe to do so.

6.2. Environmental precautions

Do not discharge into drains or the environment. Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

For containment : Avoid generating dust. Sweep or shovel into suitable containers.

6.4. Reference to other sections

Section 8: personal protective equipment.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Incompatible products : Strong oxidizers.
Prohibitions on mixed storage : Incompatible materials.
Storage area : Store in dry, cool, well-ventilated area.

7.3. Specific end use(s)

Marking.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

limestone (1317-65-3)		
Belgium	Remark (BE)	(carbonate de)
Hungary	Megjegyzések (HU)	inhalable aerosol
Ireland	OEL (8 hours ref) (mg/m³)	10 mg/m³ total inhalable dust 4 mg/m³ respirable dust
Spain	VLA-ED (mg/m³)	10 mg/m³
Spain	Notes	inhalable aerosol
United Kingdom	WEL TWA (mg/m³)	10 mg/m³ (total dust) 4 mg/m³ (respirable dust)
Switzerland	Remark (CH)	(respirable aerosol)
Aluminum oxide (1344-28-1)		
Austria	MAK (mg/m³)	10 mg/m³ (gemessen als einatembarer Aerosolanteil) 5 mg/m³ (alveolengängiger Anteil)

B Paintstik® MARKER 1 White, ½ Hex Blue, ½ Hex White, ½ Hex Yellow, 16 Black, 16 Orange, 16 White, 16 Yellow, 3/8 Yellow, Aluminum, Black, Blue, Green, Gray, Orange, Pink, Purple, Red, Silver, White, Yellow

Safety Data Sheet

according to Regulation (EU) 2015/830

Aluminum oxide (1344-28-1)		
Austria	MAK Short time value (mg/m³)	20 mg/m³ (gemessen als einatembarer Aerosolanteil) max. 2x60 min./Schicht 10 mg/m³ (alveolengängiger Anteil) max. 2x60 min./Schicht
Belgium	Limit value (mg/m³)	10 mg/m³
Belgium	Remark (BE)	(oxyde d') (en Al)
Denmark	Grænseværdie (langvarig) (mg/m³)	5 mg/m³ (total) 2 mg/m³ (respirabel)
Denmark	Grænseværdie (kortvarig) (mg/m³)	10 mg/m³ (total) 4 mg/m³ (respirabel)
France	VME (mg/m³)	10 mg/m³
France	Note (FR)	(respirable aerosol)
Germany	TRGS 900 Occupational exposure limit value (mg/m³)	3 mg/m³
Germany	Remark (TRGS 900)	(gemessen als alveolengängiger Staubanteil)
Hungary	AK-érték	6 mg/m³
Hungary	Megjegyzések (HU)	(respirable aerosol)
Ireland	OEL (8 hours ref) (mg/m³)	10 mg/m³ (total inhalable dust) 4 mg/m³ (respirable dust)
Lithuania	IPRV (mg/m³)	2 mg/m³
Lithuania	Remark (LT)	(alveolinė frakcija. biūrėk IX skyriaus 3 pastabà.)
Poland	NDS (mg/m³)	2.5 mg/m³ (dymy, pyl calkowity) 1.2 mg/m³ (dymy, pyl respirabilny)
Slovakia	NPHV (priemerná) (mg/m³)	1.5 mg/m³ (respirabilná frakcia) 4 mg/m³ (inhalovateľná frakcia)
Spain	VLA-ED (mg/m³)	10 mg/m³
Sweden	nivågränsvärde (NVG) (mg/m³)	5 mg/m³ (inhalable aerosol) 2 mg/m³ (respirable aerosol)
United Kingdom	WEL TWA (mg/m³)	10 mg/m³ (inhalable aerosol) 4 mg/m³ (respirable aerosol)
Norway	Grenseverdier (AN) (mg/m³)	10 mg/m³
Norway	Merknader (NO)	1)
Switzerland	VME (mg/m³)	3 mg/m³
Switzerland	Remark (CH)	(respirable aerosol)
Aluminum hydroxide (21645-51-2)		
Austria	MAK (ppm)	10 ppm (gemessen als einatembarer Aerosolanteil) 5 ppm (alveolengängiger Anteil)
Austria	MAK Short time value (ppm)	20 ppm (gemessen als einatembarer Aerosolanteil) max. 2x60 min./Schicht 10 ppm (alveolengängiger Anteil) max. 2x60 min./Schicht
Poland	NDS (mg/m³)	2.5 mg/m³ dymy, pyl calkowity 1.2 mg/m³ dymy, pyl respirabilny
Slovakia	NPHV (priemerná) (mg/m³)	1.5 mg/m³ (respirabilná frakcia) 4 mg/m³ (inhalovateľná frakcia)
Switzerland	VME (mg/m³)	3 mg/m³
Switzerland	Remark (CH)	(alveolengängige Fraktion)
titanium dioxide (13463-67-7)		
Belgium	Remark (BE)	(dioxyde de)
Denmark	Grænseværdie (kortvarig) (mg/m³)	12 mg/m³
France	Note (FR)	inhalable aerosol
Ireland	OEL (8 hours ref) (mg/m³)	10 mg/m³ total inhalable dust 4 mg/m³ respirable dust
Slovakia	NPHV (priemerná) (mg/m³)	5 mg/m³
Spain	VLA-ED (mg/m³)	10 mg/m³

B Paintstik® MARKER 1 White, ½ Hex Blue, ½ Hex White, ½ Hex Yellow, 16 Black, 16 Orange, 16 White, 16 Yellow, 3/8 Yellow, Aluminum, Black, Blue, Green, Gray, Orange, Pink, Purple, Red, Silver, White, Yellow

Safety Data Sheet

according to Regulation (EU) 2015/830

titanium dioxide (13463-67-7)		
Spain	Notes	inhalable aerosol
Sweden	nivågränsvärde (NVG) (mg/m³)	5 mg/m³
Sweden	Anmärkning (SE)	total dust, 1
United Kingdom	WEL TWA (mg/m³)	10 mg/m³ inhalable aerosol 4 mg/m³ respirable aerosol
Switzerland	Remark (CH)	(respirable aerosol)
rosin (8050-09-7)		
Ireland	OEL (8 hours ref) (mg/m³)	0.05 mg/m³
Ireland	OEL (15 min ref) (mg/m³)	0.15 mg/m³
Ireland	Notes (IE)	(Sen)
2,6-Di-tert-butyl-4-methylphenol (128-37-0)		
Netherlands	Grenswaarde TGG 8H (mg/m³)	10 mg/m³
Netherlands	Remark (MAC)	valeur limite de l'air
Switzerland	Remark (CH)	(einatembarer Staub)
nickel dihydroxide (12054-48-7)		
Finland	Huomautus (FI)	Ni
Spain	Notes	C1
Carbon black (1333-86-4)		
Belgium	Limit value (mg/m³)	3.5 mg/m³
Denmark	Grænseværdie (langvarig) (mg/m³)	3.5 mg/m³
Denmark	Anmærkninger (DK)	K
Finland	HTP-arvo (8h) (mg/m³)	3.5 mg/m³
Finland	HTP-arvo (15 min)	7 mg/m³
France	VME (mg/m³)	3.5 mg/m³
Ireland	OEL (8 hours ref) (mg/m³)	3.5 mg/m³
Ireland	OEL (15 min ref) (mg/m³)	7 mg/m³
Spain	VLA-ED (mg/m³)	3.5 mg/m³
Sweden	nivågränsvärde (NVG) (mg/m³)	3 mg/m³
United Kingdom	Local name	Carbon black
United Kingdom	WEL TWA (mg/m³)	3.5 mg/m³
United Kingdom	WEL STEL (mg/m³)	7 mg/m³
Norway	Grenseverdier (AN) (mg/m³)	3.5 mg/m³
aluminium powder (pyrophoric) (7429-90-5)		
Belgium	Limit value (mg/m³)	1 mg/m³
Belgium	Remark (BE)	(Aluminium, métal et composés insolubles, fraction alvéolaire)
Denmark	Grænseværdie (kortvarig) (mg/m³)	4 mg/m³ (respirabel) 10 mg/m³ (total)
Finland	HTP-arvo (8h) (mg/m³)	2 mg/m³
Finland	Huomautus (FI)	(Alumiini, liukoiset yhdisteet)
France	VME (mg/m³)	5 mg/m³ (pulvérulent) 10 mg/m³ (métal)
Germany	TRGS 903 (BGW)	200 µg/l
Germany	Remark (TRGS 903)	Aluminium (Urin; Expositionsende bzw. Schichtende)
Hungary	Megjegyzések (HU)	(respirabilis por)
Ireland	OEL (8 hours ref) (mg/m³)	1 mg/m³
Ireland	Notes (IE)	(respirable dust)

B Paintstik® MARKER 1 White, ½ Hex Blue, ½ Hex White, ½ Hex Yellow, 16 Black, 16 Orange, 16 White, 16 Yellow, 3/8 Yellow, Aluminum, Black, Blue, Green, Gray, Orange, Pink, Purple, Red, Silver, White, Yellow

Safety Data Sheet

according to Regulation (EU) 2015/830

aluminium powder (pyrophoric) (7429-90-5)		
Lithuania	IPRV (mg/m³)	2 mg/m³ (alveoline frakcija) 1 mg/m³ (Aliuminis (metalas) ir jo tirpus junginiai, kaip Al) 5 mg/m³ (ákvepiamoji frakcija)
Netherlands	Grenswaarde TGG 8H (mg/m³)	10 mg/m³
Poland	NDS (mg/m³)	2.5 mg/m³ (dymy, pyl calkowity) 1.2 mg/m³ (dymy, pyl respirabilny)
Slovakia	NPHV (priemerná) (mg/m³)	2 mg/m³
Slovakia	NPHV (priemerná) (ppm)	60 µg/g creatinine (Hlinik, M,a) 25 µg/g creatinine (Celkový, M,,d) 150 µg/g creatinine (Celkový,M,b)
Spain	VLA-ED (mg/m³)	10 mg/m³ (inhalable aerosol) 5 mg/m³ (respirable aerosol)
Sweden	nivågränsvärde (NVG) (mg/m³)	1 mg/m³ (Aluminium, lösliga föreningar, som Al) 5 mg/m³ (totaldamm, som Al) 2 mg/m³ (respirabelt damm, som Al)
United Kingdom	WEL TWA (mg/m³)	10 mg/m³ (inhalable dust) 4 mg/m³ (respirable dust)
Norway	Merknader (NO)	(Aluminiumpulver, pyroteknikk)
Switzerland	VME (mg/m³)	3 mg/m³
Switzerland	Remark (CH)	(alveolengängiger Staub)
Silicon dioxide (cristobalite) (14808-60-7)		
Austria	MAK (mg/m³)	0.15 mg/m³
Austria	Remark (AT)	(alveolengängige Fraktion; Jahres-Miw)
Belgium	Limit value (mg/m³)	0.1 mg/m³
Belgium	Remark (BE)	(poussières alvéolaires)
Denmark	Grænseværdie (langvarig) (mg/m³)	0.3 mg/m³ (inhalable aerosol) 0.1 mg/m³ (K, respirable aerosol)
Denmark	Grænseværdie (kortvarig) (mg/m³)	0.6 mg/m³ (inhalable aerosol) 0.2 mg/m³ (K, respirable aerosol)
Finland	HTP-arvo (8h) (mg/m³)	0.05 mg/m³
Finland	Huomautus (FI)	(alveolijae)
France	VME (mg/m³)	0.1 mg/m³
France	Note (FR)	(poussières alvéolaires de quartz)
Hungary	AK-érték	0.15 mg/m³
Hungary	Megjegyzések (HU)	(respirable aerosol)
Ireland	OEL (8 hours ref) (mg/m³)	0.1 mg/m³
Lithuania	IPRV (mg/m³)	0.1 mg/m³
Lithuania	Remark (LT)	(Piūrėk IX skyriaus 3 pastabà)
Netherlands	Grenswaarde TGG 8H (mg/m³)	0.075 mg/m³
Netherlands	Remark (MAC)	(Voor respirabel stof) (kankerverwekkende stoff)
Poland	NDS (mg/m³)	2 mg/m³ (krzemionke powyzej 50%; pyl calkowity) 0.3 mg/m³ (krzemionke powyzej 50%; pyl respirabilny) 2 mg/m³ (krzemionke od 2% do 50%; pyl calkowity) 0.3 mg/m³ (krzemionke od 2% do 50%; pyl respirabilny)
Slovakia	NPHV (priemerná) (mg/m³)	0.1 mg/m³
Slovakia	Upozornenie (SK)	(Dokázaný karcinogén pre ludi, R)
Spain	VLA-ED (mg/m³)	0.1 mg/m³
Spain	Notes	(respirable aerosol)
Sweden	nivågränsvärde (NVG) (mg/m³)	0.1 mg/m³
Sweden	Anmärkning (SE)	(respirabelt damm; M, 1)
Switzerland	VME (mg/m³)	0.15 mg/m³

B Paintstik® MARKER 1 White, ½ Hex Blue, ½ Hex White, ½ Hex Yellow, 16 Black, 16 Orange, 16 White, 16 Yellow, 3/8 Yellow, Aluminum, Black, Blue, Green, Gray, Orange, Pink, Purple, Red, Silver, White, Yellow

Safety Data Sheet

according to Regulation (EU) 2015/830

Silicon dioxide (cristobalite) (14808-60-7)		
Switzerland	Remark (CH)	(respirable aerosol)
Paraffin waxes and Hydrocarbon waxes (8002-74-2)		
Belgium	Remark (BE)	(cire de) (fumées)
Poland	Remark (PL)	dymy
Slovakia	NPHV (priemerná) (mg/m³)	2 mg/m³
Spain	VLA-ED (mg/m³)	2 mg/m³
United Kingdom	Remark (WEL)	(fume)
Switzerland	Remark (CH)	(alveolengängiger Staub)
Silicon dioxide (amorphous) (7631-86-9)		
Austria	MAK (mg/m³)	4 mg/m³
Austria	Remark (AT)	(einatembare Fraktion)
Finland	HTP-arvo (8h) (mg/m³)	5 mg/m³
Germany	TRGS 900 Occupational exposure limit value (mg/m³)	4 mg/m³
Germany	Remark (TRGS 900)	(einatembare Fraktion)
Ireland	OEL (8 hours ref) (mg/m³)	2.4 mg/m³ 6 mg/m³ (total inhalable dust)
Spain	VLA-ED (mg/m³)	10 mg/m³
Spain	Notes	(respirable aerosol)
United Kingdom	WEL TWA (mg/m³)	6 mg/m³ (inhalable aerosol) 2.4 mg/m³ (respirable aerosol)
Switzerland	VME (mg/m³)	4 mg/m³
Switzerland	Remark (CH)	(einatembarer Staub)
Zirconium oxide (1314-23-4)		
Denmark	Grænseværdie (langvarig) (mg/m³)	5 mg/m³ as Zr
Finland	HTP-arvo (8h) (mg/m³)	5 mg/m³ as Zr
Norway	Grenseverdier (AN) (mg/m³)	5 mg/m³ as Zr
Iron oxide red (1309-37-1)		
Belgium	Remark (BE)	(trioxyde de; fumées, en Fe)
Denmark	Grænseværdie (kortvarig) (mg/m³)	7 mg/m³
Denmark	Anmærkninger (DK)	(Jernoxid, total dust)
Finland	Huomautus (FI)	(Fe)
Hungary	Megjegyzések (HU)	(respirabilis por)
Ireland	OEL (8 hours ref) (mg/m³)	5 mg/m³ (Iron oxide, fume as Fe) 10 mg/m³ (Rouge total inhalable dust) 4 mg/m³ (Rouge total respirable dust)
Ireland	OEL (15 min ref) (mg/m³)	10 mg/m³ (Iron oxide, fume as Fe)
Lithuania	Remark (LT)	(Pliurėk IX skyriaus 3 pastabà.)
Poland	Remark (PL)	(dymy)
Slovakia	NPHV (priemerná) (mg/m³)	1.5 mg/m³ (respirabilná frakcia) 4 mg/m³ (inhalovateľná frakcia)
Spain	Notes	(Óxido de hierro(III) (polvo y humos), como Fe)
Sweden	Anmärkning (SE)	(Järnoxid, respirabelt damm)
United Kingdom	WEL TWA (mg/m³)	10 mg/m³ (Rouge, inhalable fraction) 4 mg/m³ (Rouge, respirable fraction) 5 mg/m³ (fume, as Fe)
United Kingdom	WEL STEL (mg/m³)	10 mg/m³ (fume, as Fe)
Norway	Merknader (NO)	(Jern(III)oksid, beregnet som Fe)
Switzerland	Remark (CH)	(alveolengängiger Staub)
Distillates (petroleum), hydrotreated light (64742-47-8)		
Germany	TRGS 900 Occupational exposure limit value (mg/m³)	600 mg/m³

B Paintstik® MARKER 1 White, ½ Hex Blue, ½ Hex White, ½ Hex Yellow, 16 Black, 16 Orange, 16 White, 16 Yellow, 3/8 Yellow, Aluminum, Black, Blue, Green, Gray, Orange, Pink, Purple, Red, Silver, White, Yellow

Safety Data Sheet

according to Regulation (EU) 2015/830

Stoddard solvent (benzene < 0.1%) (8052-41-3)		
Denmark	Grænseværdie (kortvarig) (mg/m³)	290 mg/m³
Denmark	Grænseværdie (kortvarig) (ppm)	50 ppm
Denmark	Anmærkninger (DK)	(Terpentin, mineralsk, max. 20 pct. aromater; 2)
Naphtha (petroleum), hydrodesulfurized heavy (benzene < 0.1%) (64742-82-1)		
Germany	TRGS 900 Occupational exposure limit value (mg/m³)	100 mg/m³
Germany	TRGS 900 Limitation of exposure peaks (mg/m³)	200 mg/m³
Germany	Remark (TRGS 900)	(C9-C15 Aromaten)
Norway	Grenseverdier (AN) (mg/m³)	120 mg/m³
Norway	Grenseverdier (AN) (ppm)	25 ppm
Norway	Merknader (NO)	(White Spirit (aromatinnhold > 22 %))
Switzerland	VME (mg/m³)	525 mg/m³
Switzerland	VME (ppm)	100 ppm

8.2. Exposure controls

Appropriate engineering controls	: Avoid dispersal of dust in the air (ie, clearing dust surfaces with compressed air). Eyewash stations.
Personal protective equipment	: Avoid all unnecessary exposure.
Hand protection	: None under normal use.
Eye protection	: Chemical goggles or safety glasses. EN 166.
Respiratory protection	: None under normal use.
Other information	: Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: A solid crayon-like marker.
Colour	: Variable.
Odour	: Slight, vegetable oil.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: 66 °C
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 204 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Solubility	: insoluble in water.
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

VOC content	: 0 %
-------------	-------

B Paintstik® MARKER 1 White, ½ Hex Blue, ½ Hex White, ½ Hex Yellow, 16 Black, 16 Orange, 16 White, 16 Yellow, 3/8 Yellow, Aluminum, Black, Blue, Green, Gray, Orange, Pink, Purple, Red, Silver, White, Yellow

Safety Data Sheet

according to Regulation (EU) 2015/830

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous Polymerization may occur.

10.4. Conditions to avoid

Heat.

10.5. Incompatible materials

Strong oxidizers.

10.6. Hazardous decomposition products

Aldehydes.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

limestone (1317-65-3)	
LD50 oral rat	6450 mg/kg
ATE CLP (oral)	6450.000 mg/kg bodyweight
Aluminum oxide (1344-28-1)	
LD50 oral rat	> 15900 mg/kg
LC50 inhalation rat (mg/l)	7.6 mg/l/4h
ATE CLP (vapours)	7.600 mg/l/4h
ATE CLP (dust,mist)	7.600 mg/l/4h
titanium dioxide (13463-67-7)	
LD50 oral rat	> 5000 mg/kg
LC50 inhalation rat (mg/l)	> 6.82 mg/l/4h
rosin (8050-09-7)	
LD50 oral rat	2800 mg/kg
LD50 dermal rat	> 2000 mg/kg No mortality observed
ATE CLP (oral)	2800.000 mg/kg bodyweight
2,6-Di-tert-butyl-4-methylphenol (128-37-0)	
LD50 oral rat	6000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
ATE CLP (oral)	6000.000 mg/kg bodyweight
nickel dihydroxide (12054-48-7)	
LD50 oral rat	1515 mg/kg
LD50 dermal rat	> 2 g/kg
LC50 inhalation rat (mg/l)	1200 mg/m³ 4 h
ATE CLP (oral)	1515.000 mg/kg bodyweight
ATE CLP (dust,mist)	1.500 mg/l/4h
Carbon black (1333-86-4)	
LD50 oral rat	> 8000 mg/kg
LC50 inhalation rat (mg/l)	> 4.6 mg/m³ 4 h
aluminium powder (pyrophoric) (7429-90-5)	
LD50 oral rat	> 15900 mg/kg bodyweight
LC50 inhalation rat (Dust/Mist - mg/l/4h)	> 10 mg/l/4h
Paraffin waxes and Hydrocarbon waxes (8002-74-2)	
LD50 oral rat	> 5000 mg/kg No mortality observed
LD50 dermal rat	> 2000 mg/kg No mortality observed

B Paintstik® MARKER 1 White, ½ Hex Blue, ½ Hex White, ½ Hex Yellow, 16 Black, 16 Orange, 16 White, 16 Yellow, 3/8 Yellow, Aluminum, Black, Blue, Green, Gray, Orange, Pink, Purple, Red, Silver, White, Yellow

Safety Data Sheet

according to Regulation (EU) 2015/830

Silicon dioxide (amorphous) (7631-86-9)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 58.8 mg/l/4h
Zirconium oxide (1314-23-4)	
LD50 oral rat	> 5000 mg/kg
LC50 inhalation rat (mg/l)	> 4.3 mg/l/4h
Iron oxide red (1309-37-1)	
LD50 oral rat	> 10000 mg/kg
4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol <1%) (2786-76-7)	
LD50 oral rat	> 15000 mg/kg
LC50 inhalation rat (mg/l)	> 1580 mg/m³ 4 h
Distillates (petroleum), hydrotreated light (64742-47-8)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (Dust/Mist - mg/l/4h)	> 5.28 mg/l/4h
Stoddard solvent (benzene < 0.1%) (8052-41-3)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 10 mg/l/4h
Naphtha (petroleum), hydrodesulfurized heavy (benzene < 0.1%) (64742-82-1)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 7630 mg/m³
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified (No sensitizing reaction was observed for guinea pigs;(Results obtained on a similar product))
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified.
titanium dioxide (13463-67-7)	
NOAEL (chronic, oral, animal/male, 2 years)	5 mg/kg bodyweight rat
nickel dihydroxide (12054-48-7)	
NOAEL (chronic, oral, animal/male, 2 years)	2.2 mg/kg bodyweight read across Nickel Sulphate Hexahydrate
NOAEL (chronic, oral, animal/female, 2 years)	2.2 mg/kg bodyweight read across Nickel Sulphate Hexahydrate
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
2,6-Di-tert-butyl-4-methylphenol (128-37-0)	
NOAEL (oral, rat, 90 days)	25 mg/kg bodyweight/day Digestive, live, urogenital, kidneys, glandular, thyroids, adrenal gland.
Aspiration hazard	: Not classified

SECTION 12: Ecological information

12.1. Toxicity

limestone (1317-65-3)	
LC50 fish 1	> 200 mg/l
Aluminum oxide (1344-28-1)	
EC50 Daphnia 1	> 1470 mg/l

B Paintstik® MARKER 1 White, ½ Hex Blue, ½ Hex White, ½ Hex Yellow, 16 Black, 16 Orange, 16 White, 16 Yellow, 3/8 Yellow, Aluminum, Black, Blue, Green, Gray, Orange, Pink, Purple, Red, Silver, White, Yellow

Safety Data Sheet

according to Regulation (EU) 2015/830

Aluminum oxide (1344-28-1)	
NOEC (acute)	> 50 mg/l
rosin (8050-09-7)	
LC50 fish 1	< 10 mg/l 96 h
EC50 Daphnia 1	911 mg/l 48 h
2,6-Di-tert-butyl-4-methylphenol (128-37-0)	
LC50 fish 1	0.199
EC50 Daphnia 1	0.48 mg/l
EC50 other aquatic organisms 1	0.758 mg/l
NOEC (acute)	0.15 mg/l
nickel dihydroxide (12054-48-7)	
LC50 fish 1	15.3 mg/l 96 h
EC50 Daphnia 1	> 200 µg/l 48 h
Paraffin waxes and Hydrocarbon waxes (8002-74-2)	
LC50 fish 1	> 1000 mg/l
Silicon dioxide (amorphous) (7631-86-9)	
LC50 fish 1	> 10000 mg/l
EC50 Daphnia 1	> 1000 mg/l
Zirconium oxide (1314-23-4)	
LC50 fish 1	> 100 mg/l
EC50 Daphnia 1	> 100 mg/l
Iron oxide red (1309-37-1)	
EC50 Daphnia 1	> 100 mg/l
4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol <1%) (2786-76-7)	
LC50 fish 1	> 500 mg/l 96 h
EC50 Daphnia 1	> 110 mg/l 48 h

12.2. Persistence and degradability

limestone (1317-65-3)	
Persistence and degradability	Not readily biodegradable.
rosin (8050-09-7)	
Biodegradation	71 % 28 d
2,6-Di-tert-butyl-4-methylphenol (128-37-0)	
Persistence and degradability	Not readily biodegradable. May cause long-term adverse effects in the environment.
nickel dihydroxide (12054-48-7)	
Persistence and degradability	Not readily biodegradable.
Carbon black (1333-86-4)	
Persistence and degradability	Not readily biodegradable.
Silicon dioxide (amorphous) (7631-86-9)	
Persistence and degradability	Product persists.
4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol <1%) (2786-76-7)	
Persistence and degradability	Not readily biodegradable.
Biodegradation	0 % 28 d

12.3. Bioaccumulative potential

limestone (1317-65-3)	
Bioaccumulative potential	Does not bioaccumulate significantly.
rosin (8050-09-7)	
Log Pow	3 (3 - 6.2)
2,6-Di-tert-butyl-4-methylphenol (128-37-0)	
Log Pow	5.2

B Paintstik® MARKER 1 White, ½ Hex Blue, ½ Hex White, ½ Hex Yellow, 16 Black, 16 Orange, 16 White, 16 Yellow, 3/8 Yellow, Aluminum, Black, Blue, Green, Gray, Orange, Pink, Purple, Red, Silver, White, Yellow

Safety Data Sheet

according to Regulation (EU) 2015/830

2,6-Di-tert-butyl-4-methylphenol (128-37-0)	
Bioaccumulative potential	This product is not bioaccumulating.
nickel dihydroxide (12054-48-7)	
BCF fish 1	600 - 26500 whole body d.w.; 0 to 26 day exposure
Zirconium oxide (1314-23-4)	
Bioaccumulative potential	Not expected to bioaccumulate.
4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol <1%) (2786-76-7)	
BCF fish 1	53 l/kg
Log Pow	1.28
Distillates (petroleum), hydrotreated light (64742-47-8)	
Log Kow	2.1 - 5
Bioaccumulative potential	Bioaccumulative potential.
Stoddard solvent (benzene < 0.1%) (8052-41-3)	
Log Pow	3.16 - 7.15

12.4. Mobility in soil

2,6-Di-tert-butyl-4-methylphenol (128-37-0)	
Ecology - soil	Absorbs to soil particles and will not be mobile.
Zirconium oxide (1314-23-4)	
Ecology - soil	Partitions to soil.

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.
European List of Waste (LoW) code : For disposal within the EC, the appropriate code according to the European Waste Catalogue (EWC) should be used.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

Not considered a dangerous good for transport regulations

14.2. UN proper shipping name

Proper Shipping Name (ADR) :

14.3. Transport hazard class(es)

Not applicable

14.4. Packing group

Not applicable

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

14.6.1. Overland transport

No additional information available

14.6.2. Transport by sea

No additional information available

14.6.3. Inland waterway transport

Carriage prohibited (ADN) : No

B Paintstik® MARKER 1 White, ½ Hex Blue, ½ Hex White, ½ Hex Yellow, 16 Black, 16 Orange, 16 White, 16 Yellow, 3/8 Yellow, Aluminum, Black, Blue, Green, Gray, Orange, Pink, Purple, Red, Silver, White, Yellow

Safety Data Sheet

according to Regulation (EU) 2015/830

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

VOC content : 0 %

15.1.2. National regulations

Germany

Water hazard class (WGK) : 3 - severe hazard to waters

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out

Zirconium oxide

SECTION 16: Other information

according to Regulation (EU) 2015/830

Indication of changes:

Original Document.

Abbreviations and acronyms:

	ATE: Acute Toxicity Estimate
	CAS (Chemical Abstracts Service) number
	CLP: Classification, Labelling, Packaging.
	EC50: Environmental Concentration associated with a response by 50% of the test population.
	GHS: Globally Harmonized System (of Classification and Labeling of Chemicals).
	LD50: Lethal Dose for 50% of the test population
	OSHA: Occupational Safety & Health Administration
	PBT: Persistent, Bioaccumulative, Toxic
	TWA: Time Weighted Average
	TSCA: Toxic Substances Control Act

Data sources : ESIS (European chemical Substances Information System; accessed at: <http://esis.jrc.ec.europa.eu/index.php?PGM=cla>.
European Chemicals Agency (ECHA) C&L Inventory database. Accessed at <http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database>.
Krister Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition.
National Fire Protection Association. Fire Protection Guide to Hazardous Materials; 10th edition.
REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information : None.

Full text of R-, H- and EUH-statements:

Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 1A	Carcinogenicity (inhalation) Category 1A
Carc. 2	Carcinogenicity, Category 2

B Paintstik® MARKER 1 White, ½ Hex Blue, ½ Hex White, ½ Hex Yellow, 16 Black, 16 Orange, 16 White, 16 Yellow, 3/8 Yellow, Aluminum, Black, Blue, Green, Gray, Orange, Pink, Purple, Red, Silver, White, Yellow

Safety Data Sheet

according to Regulation (EU) 2015/830

Flam. Liq. 3	Flammable liquids, Category 3
Muta. 2	Germ cell mutagenicity, Category 2
Pyr. Sol. 1	Pyrophoric Solids, Category 1
Repr. 1B	Reproductive toxicity, Category 1B
Resp. Sens. 1	Sensitisation — Respiratory, category 1
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Sensitisation — Skin, category 1
STOT RE 1	Specific target organ toxicity — Repeated exposure, Category 1
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
Water-react. 2	Substances and Mixtures which, in contact with water, emit flammable gases, Category 2
H226	Flammable liquid and vapour
H250	Catches fire spontaneously if exposed to air
H261	In contact with water releases flammable gases
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H332	Harmful if inhaled
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled
H341	Suspected of causing genetic defects
H350i	May cause cancer by inhalation
H351	Suspected of causing cancer
H360D	May damage the unborn child
H372	Causes damage to organs through prolonged or repeated exposure
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects
R15	Contact with water liberates extremely flammable gases
R17	Spontaneously flammable in air
R20/22	Harmful by inhalation and if swallowed
R38	Irritating to skin
R40	Limited evidence of a carcinogenic effect
R42	May cause sensitization by inhalation
R43	May cause sensitisation by skin contact
R45	May cause cancer
R46	May cause heritable genetic damage
R48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation
R48/23	Toxic: danger of serious damage to health by prolonged exposure through inhalation
R49	May cause cancer by inhalation
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R61	May cause harm to the unborn child
R65	Harmful: may cause lung damage if swallowed
R68	Possible risk of irreversible effects
F	Highly flammable
N	Dangerous for the environment
T	Toxic
Xi	Irritant
Xn	Harmful

LA-CO EU CLP SDS

SDS Prepared by: The Redstone Group, LLC
6077 Frantz Rd.
Suite 206
Dublin, OH USA 43016
T 614-923-7472

B Paintstik® MARKER 1 White, ½ Hex Blue, ½ Hex White, ½ Hex Yellow, 16 Black, 16 Orange, 16 White, 16 Yellow, 3/8 Yellow, Aluminum, Black, Blue, Green, Gray, Orange, Pink, Purple, Red, Silver, White, Yellow

Safety Data Sheet

according to Regulation (EU) 2015/830

www.redstonegrp.com

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product