

Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 26

SDS No.: 153594

V013.0 Revision: 06.12.2024

printing date: 15.04.2025

Replaces version from: 03.10.2024

LOCTITE AA 3201 LC known as LOCTITE® 3201 ADHESIVE

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE AA 3201 LC known as LOCTITE® 3201 ADHESIVE

UFI: 9X05-AXHS-K208-8UX4

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Ultraviolet adhesive

1.3. Details of the supplier of the safety data sheet

Henkel Ltd

Adhesives

Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

SDSinfo.Adhesive@henkel.com

For Safety Data Sheet updates please visit our website www.mysds.henkel.com or www.henkel-adhesives.com.

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Skin irritation Category 2

H315 Causes skin irritation.

Serious eye irritation Category 2

H319 Causes serious eye irritation.

Skin sensitizer Category 1

H317 May cause an allergic skin reaction.

Toxic to reproduction Category 1B

H360F May damage fertility.

Acute hazards to the aquatic environment Category 1

H400 Very toxic to aquatic life.

Chronic hazards to the aquatic environment Category 1

H410 Very toxic to aquatic life with long lasting effects.

2.2. Label elements

Label elements (CLP):

Page 2 of 26

V013.0

SDS No.: 153594

Hazard pictogram:



Contains Isobornyl acrylate

2-Hydroxyethyl methacrylate

Diphenyl-2,4,6-trimethylbenzoyl phosphine oxide

2-Propenoic acid, 2-methyl-, 2-(2-hydroxyethoxy)ethyl ester

2-Hydroxyethyl acrylate

Signal word: Danger

Hazard statement: H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H410 Very toxic to aquatic life with long lasting effects.

H360F May damage fertility.

Supplemental information Restricted to professional users.

Precautionary statement: P273 Avoid release to the environment.

Prevention P201 Obtain special instructions before use.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statement: P302+P352 IF ON SKIN: Wash with plenty of soap and water.

Response P337+P313 If eye irritation persists: Get medical advice/attention.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P308+P313 IF exposed or concerned: Get medical advice/attention.

2.3. Other hazards

None if used properly.

Care should be taken during the cure of these products by UV radiation to avoid exposure of the skin and especially of the eyes to direct or reflected UV radiation as long term effects could be harmful.

Following substances are present in a concentration \geq the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in a concentration ≥ the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

SDS No.: 153594

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No. EC Number REACH-Reg No.	Concentration	Classification	Specific Conc. Limits, M- factors and ATEs	Add. Information
REACH-Reg No. Isobornyl acrylate 5888-33-5 227-561-6 01-2119957862-25	25-< 50 %	Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M acute = 1 M chronic = 1	
2-Hydroxyethyl methacrylate 868-77-9 212-782-2 01-2119490169-29	10- < 20 %	Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319		
Ethanone, 2,2-dimethoxy-1,2- diphenyl- 24650-42-8 246-386-6 01-2120000336-73	1-< 5 %	Aquatic Chronic 3, H412 Acute Tox. 4, Oral, H302 STOT RE 2, H373		
[3-(2,3- Epoxypropoxy)propyl]trimethox ysilane 2530-83-8 219-784-2 01-2119513212-58	1-< 3 %	Aquatic Chronic 3, H412 Eye Dam. 1, H318		
Diphenyl-2,4,6-trimethylbenzoyl phosphine oxide 75980-60-8 278-355-8 01-2119972295-29	1-< 3 %	Aquatic Chronic 2, H411 Skin Sens. 1B, H317 Repr. 1B, H360Fd		SVHC
methacrylic acid 79-41-4 201-204-4 01-2119463884-26	0,1-< 1 %	Acute Tox. 4, Oral, H302 Acute Tox. 3, Dermal, H311 Acute Tox. 4, Inhalation, H332 Skin Corr. 1A, H314 Eye Dam. 1, H318 STOT SE 3, H335	STOT SE 3; H335; C >= 1 % ===== dermal:ATE = 500 mg/kg inhalation:ATE = 3,19 mg/l;dust/mist	
Camphene 79-92-5 201-234-8	0,1-< 1 %	Aquatic Acute 1, H400 Aquatic Chronic 1, H410 Flam. Sol. 2, H228 Eye Irrit. 2, H319	M acute = 1 M chronic = 1	
1,7,7- Trimethyltricyclo[2,2,1.02,6]hept ane 508-32-7 208-083-7, 208-083-7	0,1-< 1 %	Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M acute = 1 M chronic = 1	
2-Propenoic acid, 2-methyl-, 2- (2-hydroxyethoxy)ethyl ester 2351-43-1	0,1-< 1 %	Eye Irrit. 2, H319 Skin Sens. 1, H317		
2-Hydroxyethyl acrylate 818-61-1 212-454-9 01-2119459345-34	0,1-< 1 %	Acute Tox. 4, Oral, H302 Acute Tox. 3, Dermal, H311 Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 3, H412	Skin Sens. 1; H317; C >= 0,2 % ===== M acute = 1	

If no ATE values are displayed, please refer to LD/LC50 values in Section 11. For full text of the H - statements and other abbreviations see section 16 "Other information".

Page 4 of 26

V013.0

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

SDS No.: 153594

Move to fresh air. If symptoms persist, seek medical advice.

Consideration should be given to the possible effects of a faulty UV source (Stray radiation, ozone).

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

SKIN: Rash, Urticaria.

SKIN: Redness, inflammation.

EYE: Irritation, conjunctivitis.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx) can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes.

Wear protective equipment.

Ensure adequate ventilation.

Keep away from sources of ignition.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Dispose of contaminated material as waste according to Section 13.

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

SDS No.: 153594

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid skin and eye contact.

See advice in section 8

Ventilation will remove any ozone that may be produced by the ultra violet lamp

Hygiene measures:

Good industrial hygiene practices should be observed. Do not eat, drink or smoke while working.

Wash hands before work breaks and after finishing work.

7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction.

Refer to Technical Data Sheet.

7.3. Specific end use(s)

Ultraviolet adhesive

V013.0

SDS No.: 153594

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for

Great Britain

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Silicon dioxide		6	Time Weighted Average		EH40 WEL
112945-52-5			(TWA):		
[SILICA, AMORPHOUS, INHALABLE DUST]					
Silicon dioxide		2,4	Time Weighted Average		EH40 WEL
112945-52-5			(TWA):		
[SILICA, AMORPHOUS, RESPIRABLE					
DUST]					
Silicon dioxide		4	Time Weighted Average		EH40 WEL
112945-52-5			(TWA):		
[Dust, respirable dust]					
Silicon dioxide		10	Time Weighted Average		EH40 WEL
112945-52-5			(TWA):		
[Dust, inhalable dust]					
Methacrylic acid	20	72	Time Weighted Average		EH40 WEL
79-41-4			(TWA):		
[METHACRYLIC ACID]					
Methacrylic acid	40	143	Short Term Exposure	15 minutes	EH40 WEL
79-41-4			Limit (STEL):		
[METHACRYLIC ACID]			·		

Occupational Exposure Limits

Valid for

Ireland

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Silicon dioxide 112945-52-5 [SILICA, AMORPHOUS]		6	Time Weighted Average (TWA):		IR_OEL
Silicon dioxide 112945-52-5 [SILICA, AMORPHOUS]		2,4	Time Weighted Average (TWA):		IR_OEL
Silicon dioxide 112945-52-5 [DUSTS NON-SPECIFIC]		10	Time Weighted Average (TWA):		IR_OEL
Silicon dioxide 112945-52-5 [DUSTS NON-SPECIFIC]		4	Time Weighted Average (TWA):		IR_OEL
Methacrylic acid 79-41-4 [METHACRYLIC ACID]	20	70	Time Weighted Average (TWA):		IR_OEL
Methacrylic acid 79-41-4 [METHACRYLIC ACID]	40	140	Short Term Exposure Limit (STEL):	15 minutes	IR_OEL

Page 7 of 26

V013.0

SDS No.: 153594

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value	Value			Remarks
	- Compartment	periou	mg/l	ppm	mg/kg	others	
Isobornyl acrylate	aqua		0,001 mg/l				
5888-33-5 Isobornyl acrylate	(freshwater)		0.007 ma/l				
18000my1 acrylate 5888-33-5	aqua (intermittent		0,007 mg/l				
	releases)						
Isobornyl acrylate	aqua (marine		0,0001				
5888-33-5	water)		mg/l	1			
Isobornyl acrylate 5888-33-5	sewage treatment plant		2 mg/l				
	(STP)						
Isobornyl acrylate	sediment				0,145		
5888-33-5 Isobornyl acrylate	(freshwater) sediment				mg/kg 0,0145		
5888-33-5	(marine water)				mg/kg		
Isobornyl acrylate	Soil				0,0285		
5888-33-5					mg/kg		
Isobornyl acrylate 5888-33-5	Predator						no potential for bioaccumulation
2-Hydroxyethyl methacrylate	aqua		0,482 mg/l			<u> </u>	oroaccumuration
868-77-9	(freshwater)						
2-Hydroxyethyl methacrylate	aqua (marine		0,482 mg/l				
868-77-9 2-Hydroxyethyl methacrylate	water)		10 m a /1				
868-77-9	sewage treatment plant		10 mg/l				
	(STP)						
2-Hydroxyethyl methacrylate	aqua		1 mg/l				
868-77-9	(intermittent releases)						
2-Hydroxyethyl methacrylate	sediment				3,79 mg/kg		
868-77-9	(freshwater)						
2-Hydroxyethyl methacrylate	sediment				3,79 mg/kg		
868-77-9 2-Hydroxyethyl methacrylate	(marine water) Soil				0,476		
868-77-9	3011				mg/kg		
2-Hydroxyethyl methacrylate	Predator						no potential for
868-77-9							bioaccumulation
2-Hydroxyethyl methacrylate 868-77-9	Marine water - intermittent		1 mg/l				
2,2-Dimethoxy-1,2-diphenylethan-1-one	aqua		0,229 mg/l				
24650-42-8	(freshwater)						
2,2-Dimethoxy-1,2-diphenylethan-1-one	Freshwater -		0,184 mg/l				
24650-42-8 2,2-Dimethoxy-1,2-diphenylethan-1-one	intermittent aqua (marine		0,0229				
24650-42-8	water)		mg/l				
2,2-Dimethoxy-1,2-diphenylethan-1-one	Marine water -		0,0184				
24650-42-8	intermittent		mg/l				
2,2-Dimethoxy-1,2-diphenylethan-1-one 24650-42-8	sewage treatment plant		19,4 mg/l				
2.050 .2 0	(STP)						
2,2-Dimethoxy-1,2-diphenylethan-1-one	sediment				8,87 mg/kg		
24650-42-8 2,2-Dimethoxy-1,2-diphenylethan-1-one	(freshwater) sediment			1	0,887		
2,2-Dimethoxy-1,2-diphenylethan-1-one 24650-42-8	(marine water)				mg/kg		
2,2-Dimethoxy-1,2-diphenylethan-1-one	Soil				1,64 mg/kg		
24650-42-8							
[3-(2,3- Epoxypropoxy)propyl]trimethoxysilane	aqua (freshwater)		0,45 mg/l				
2530-83-8	(IIesiiwatei)						
[3-(2,3-	aqua (marine		0,045 mg/l				
Epoxypropoxy)propyl]trimethoxysilane	water)						
2530-83-8 [3-(2,3-	cawage		8.2 ma/l				
[3-(2,3- Epoxypropoxy)propyl]trimethoxysilane	sewage treatment plant		8,2 mg/l				
2530-83-8	(STP)						
[3-(2,3-	sediment				1,6 mg/kg		
Epoxypropoxy)propyl]trimethoxysilane	(freshwater)						

SDS No.: 153594

Jaran aa a	1	1 1	1	
2530-83-8	sediment		0.16 #	
[3-(2,3- Epoxypropoxy)propyl]trimethoxysilane 2530-83-8	(marine water)		0,16 mg/kg	
[3-(2,3- Epoxypropoxy)propyl]trimethoxysilane	Soil		0,063 mg/kg	
2530-83-8		0.45	18, 1.8	
[3-(2,3- Epoxypropoxy)propyl]trimethoxysilane 2530-83-8	aqua (intermittent releases)	0,45 mg/l		
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide 75980-60-8	aqua (freshwater)	0,0014 mg/l		
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide 75980-60-8	aqua (marine water)	0,00014 mg/l		
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide 75980-60-8	Freshwater - intermittent	0,014 mg/l		
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide 75980-60-8	Marine water - intermittent	0,0014 mg/l		
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide 75980-60-8	sediment (freshwater)		0,115 mg/kg	
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide 75980-60-8	sediment (marine water)		0,0115 mg/kg	
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide 75980-60-8	Soil		0,0222 mg/kg	
methacrylic acid 79-41-4	aqua (freshwater)	0,82 mg/l		
methacrylic acid 79-41-4	Freshwater - intermittent	0,45 mg/l		
methacrylic acid 79-41-4	aqua (marine water)	0,082 mg/l		
methacrylic acid 79-41-4	sewage treatment plant (STP)	100 mg/l		
methacrylic acid 79-41-4	sediment (freshwater)		3,09 mg/kg	
methacrylic acid 79-41-4	sediment (marine water)		0,309 mg/kg	
methacrylic acid 79-41-4	Soil		0,137 mg/kg	
methacrylic acid 79-41-4	Predator		mg/kg	no potential for bioaccumulation
2-Hydroxyethyl acrylate 818-61-1	aqua (freshwater)	0,017 mg/l		
2-Hydroxyethyl acrylate 818-61-1	aqua (marine water)	0,002 mg/l		
2-Hydroxyethyl acrylate 818-61-1	aqua (intermittent releases)	0,036 mg/l		
2-Hydroxyethyl acrylate 818-61-1	sediment (freshwater)		0,064 mg/kg	
2-Hydroxyethyl acrylate 818-61-1	sediment (marine water)		0,006 mg/kg	
2-Hydroxyethyl acrylate 818-61-1	Soil		0,003 mg/kg	
2-Hydroxyethyl acrylate 818-61-1	Sewage	10 mg/l	mg/kg	
2-Hydroxyethyl acrylate 818-61-1	Air			no hazard identified

Page 9 of 26

V013.0

SDS No.: 153594

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Isobornyl acrylate 5888-33-5	Workers	dermal	Long term exposure - systemic effects		1,39 mg/kg	no potential for bioaccumulation
Isobornyl acrylate 5888-33-5	General population	oral	Long term exposure - systemic effects		0,83 mg/kg	no potential for bioaccumulation
Isobornyl acrylate 5888-33-5	General population	dermal	Long term exposure - systemic effects		0,83 mg/kg	no potential for bioaccumulation
2-Hydroxyethyl methacrylate 868-77-9	Workers	dermal	Long term exposure - systemic effects		1,3 mg/kg	no potential for bioaccumulation
2-Hydroxyethyl methacrylate 868-77-9	Workers	Inhalation	Long term exposure - systemic effects		4,9 mg/m3	no potential for bioaccumulation
2-Hydroxyethyl methacrylate 868-77-9	General population	dermal	Long term exposure - systemic effects		0,83 mg/kg	no potential for bioaccumulation
2-Hydroxyethyl methacrylate 868-77-9	General population	Inhalation	Long term exposure - systemic effects		2,9 mg/m3	no potential for bioaccumulation
2-Hydroxyethyl methacrylate 868-77-9	General population	oral	Long term exposure - systemic effects		0,83 mg/kg	no potential for bioaccumulation
2,2-Dimethoxy-1,2-diphenylethan-1-one 24650-42-8	Workers	inhalation	Long term exposure - systemic effects		2,11 mg/m3	
2,2-Dimethoxy-1,2-diphenylethan-1-one 24650-42-8	Workers	dermal	Long term exposure - systemic effects		0,599 mg/kg	
2,2-Dimethoxy-1,2-diphenylethan-1-one 24650-42-8	General population	inhalation	Long term exposure - systemic effects		0,372 mg/m3	
2,2-Dimethoxy-1,2-diphenylethan-1-one 24650-42-8	General population	dermal	Long term exposure - systemic effects		0,214 mg/kg	
2,2-Dimethoxy-1,2-diphenylethan-1-one 24650-42-8	General population	oral	Long term exposure - systemic effects		0,214 mg/kg	
[3-(2,3- Epoxypropoxy)propyl]trimethoxysilane 2530-83-8	Workers	dermal	Long term exposure - systemic effects		10 mg/kg	
[3-(2,3- Epoxypropoxy)propyl]trimethoxysilane 2530-83-8	Workers	Inhalation	Long term exposure - systemic effects		70,5 mg/m3	
[3-(2,3- Epoxypropoxy)propyl]trimethoxysilane 2530-83-8	General population	inhalation	Long term exposure - systemic effects		17,4 mg/m3	
[3-(2,3- Epoxypropoxy)propyl]trimethoxysilane 2530-83-8	General population	dermal	Long term exposure - systemic effects		5 mg/kg	
[3-(2,3- Epoxypropoxy)propyl]trimethoxysilane 2530-83-8	General population	inhalation	Acute/short term exposure - systemic effects		26400 mg/m3	
[3-(2,3- Epoxypropoxy)propyl]trimethoxysilane 2530-83-8	General population	oral	Long term exposure - systemic effects		4 mg/kg	
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide 75980-60-8	Workers	inhalation	Long term exposure - systemic effects		0,822 mg/m3	
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide 75980-60-8	Workers	dermal	Long term exposure - systemic effects		0,233 mg/kg	
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide 75980-60-8	General population	inhalation	Long term exposure - systemic effects		0,145 mg/m3	
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	General population	dermal	Long term exposure -		0,0833 mg/kg	

SDS No.: 153594

75980-60-8			systemic effects		
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide 75980-60-8	General population	oral	Long term exposure - systemic effects	0,0833 mg/kg	
methacrylic acid 79-41-4	Workers	Inhalation	Long term exposure - local effects	88 mg/m3	no potential for bioaccumulation
methacrylic acid 79-41-4	Workers	Inhalation	Long term exposure - systemic effects	29,6 mg/m3	no potential for bioaccumulation
methacrylic acid 79-41-4	Workers	dermal	Long term exposure - systemic effects	4,25 mg/kg	no potential for bioaccumulation
methacrylic acid 79-41-4	General population	Inhalation	Long term exposure - local effects	6,55 mg/m3	no potential for bioaccumulation
methacrylic acid 79-41-4	General population	Inhalation	Long term exposure - systemic effects	6,3 mg/m3	no potential for bioaccumulation
methacrylic acid 79-41-4	General population	dermal	Long term exposure - systemic effects	2,55 mg/kg	no potential for bioaccumulation
2-Hydroxyethyl acrylate 818-61-1	Workers	inhalation	Long term exposure - local effects	2,4 mg/m3	no hazard identified
2-Hydroxyethyl acrylate 818-61-1	General population	inhalation	Long term exposure - local effects	1,2 mg/m3	no hazard identified

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

UV lamp should be designed, installed and operated in such a way as to eliminate exposure of the skin and eyes to stray radiation

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Protective eye equipment should conform to EN166.

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.

Protective eye equipment should conform to EN166.

SDS No.: 153594

Skin protection:

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Delivery form liquid Colour Pale yellow Odor mild, Acrylic Physical state liquid

Melting point Not applicable, Product is a liquid

< -25 °C (< -13 °F) Solidification temperature Initial boiling point > 149 °C (> 300.2 °F) Flammability The product is not flammable.

Explosive limits Not applicable, The product is not flammable. > 93,3 °C (> 199.94 °F); Tagliabue closed cup Flash point

Auto-ignition temperature 485 °C (905 °F)

Decomposition temperature Not applicable, Substance/mixture is not self-reactive, no organic

peroxide and does not decompose under foreseen conditions of use

Not applicable, Product reacts with water.

Viscosity (kinematic) > 20,5 mm2/s

(40 °C (104 °F);)

Solubility (qualitative) Slight

(20 °C (68 °F); Solvent: Water)

Solubility (qualitative) Miscible

(20 °C (68 °F); Solvent: Acetone)

Partition coefficient: n-octanol/water Not applicable Mixture

Vapour pressure < 5 mm hg(20 °C (68 °F))

Vapour pressure < 3,9 mbar

(20 °C (68 °F))

Density 1,09 g/cm3 None

(20 °C (68 °F))

Relative vapour density:

(20 °C)

Particle characteristics Not applicable Product is a liquid

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts with strong oxidants.

Acids.

Reducing agents. Strong bases.

10.2. Chemical stability

Stable under recommended storage conditions.

SDS No.: 153594

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Stable under normal conditions of storage and use.

Protect from direct sunlight.

Avoid contact with acids and oxidizing agents.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

carbon oxides.

Hydrocarbons

nitrogen oxides

Rapid polymerisation may generate excessive heat and pressure.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Species	Method
CAS-No.	type			
Isobornyl acrylate 5888-33-5	LD50	4.350 mg/kg	rat	not specified
2-Hydroxyethyl methacrylate 868-77-9	LD50	5.564 mg/kg	rat	FDA Guideline
Ethanone, 2,2-dimethoxy-1,2-diphenyl-24650-42-8	LD50	1.470 mg/kg	rat	QSAR (Quantitative Structure Activity Relationship)
[3-(2,3- Epoxypropoxy)propyl]tri methoxysilane 2530-83-8	LD50	8.025 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
methacrylic acid 79-41-4	LD50	1.320 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
Camphene 79-92-5	LD50	>= 5.000 mg/kg	rat	Limit Test
2-Propenoic acid, 2- methyl-, 2-(2- hydroxyethoxy)ethyl ester 2351-43-1	LD50	5.564 mg/kg	rat	FDA Guideline
2-Hydroxyethyl acrylate 818-61-1	LD50	540 mg/kg	rat	not specified

V013.0

SDS No.: 153594

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Isobornyl acrylate 5888-33-5	LD50	> 3.000 mg/kg	rabbit	not specified
2-Hydroxyethyl methacrylate 868-77-9	LD50	> 5.000 mg/kg	rabbit	not specified
Ethanone, 2,2-dimethoxy-1,2-diphenyl-24650-42-8	LD50	> 5.000 mg/kg	rat	not specified
[3-(2,3- Epoxypropoxy)propyl]tri methoxysilane 2530-83-8	LD50	4.250 mg/kg	rabbit	equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity)
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
methacrylic acid 79-41-4	LD50	500 - 1.000 mg/kg	rabbit	Dermal Toxicity Screening
methacrylic acid 79-41-4	Acute toxicity estimate (ATE)	500 mg/kg		Expert judgement
2-Propenoic acid, 2- methyl-, 2-(2- hydroxyethoxy)ethyl ester 2351-43-1	LD50	> 5.000 mg/kg	rabbit	not specified

V013.0

SDS No.: 153594

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
[3-(2,3- Epoxypropoxy)propyl]tri methoxysilane 2530-83-8	LC50	> 5,3 mg/l	dust/mist	4 h	rat	equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity)
methacrylic acid 79-41-4	LC50	3,19 - 6,5 mg/l	dust/mist	4 h	rat	equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity)
methacrylic acid 79-41-4	Acute toxicity estimate (ATE)	3,19 mg/l	dust/mist			Expert judgement

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Isobornyl acrylate 5888-33-5	not irritating	24 h	rabbit	other guideline:
2-Hydroxyethyl methacrylate 868-77-9	slightly irritating	24 h	rabbit	Draize Test
[3-(2,3- Epoxypropoxy)propyl]tri methoxysilane 2530-83-8	not irritating	24 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8	not irritating	24 h	rabbit	not specified
methacrylic acid 79-41-4	corrosive	3 min	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Camphene 79-92-5	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
2-Propenoic acid, 2- methyl-, 2-(2- hydroxyethoxy)ethyl ester 2351-43-1	not irritating	24 h	rabbit	Draize Test

V013.0

SDS No.: 153594

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Isobornyl acrylate 5888-33-5	not irritating		rabbit	other guideline:
2-Hydroxyethyl methacrylate 868-77-9	Category 2B (mildly irritating to eyes)		rabbit	Draize Test
[3-(2,3- Epoxypropoxy)propyl]tri methoxysilane 2530-83-8	corrosive		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8	not irritating		rabbit	not specified
methacrylic acid 79-41-4	corrosive		rabbit	Draize Test
Camphene 79-92-5	irritating	24 h	rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
2-Propenoic acid, 2- methyl-, 2-(2- hydroxyethoxy)ethyl ester 2351-43-1	irritating		rabbit	Draize Test

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Isobornyl acrylate 5888-33-5	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
2-Hydroxyethyl methacrylate 868-77-9	not sensitising	Buehler test	guinea pig	Buehler test
2-Hydroxyethyl methacrylate 868-77-9	sensitising	Guinea pig maximisation test	guinea pig	Magnusson and Kligman Method
[3-(2,3- Epoxypropoxy)propyl]tri methoxysilane 2530-83-8	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
methacrylic acid 79-41-4	not sensitising	Buehler test	guinea pig	equivalent or similar to OECD Guideline 406 (Skin Sensitisation)
2-Hydroxyethyl acrylate 818-61-1	sensitising	Mouse local lymphnode assay (LLNA)	mouse	not specified

SDS No.: 153594 V013.0

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of	Metabolic activation /	Species	Method
*		administration	Exposure time	1	0707 0 11 11 151
Isobornyl acrylate 5888-33-5	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Isobornyl acrylate 5888-33-5	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Isobornyl acrylate 5888-33-5	negative	in vitro mammalian cell micronucleus test	with and without		OECD Guideline 487 (In vitro Mammalian Cell Micronucleus Test)
2-Hydroxyethyl methacrylate 868-77-9	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
2-Hydroxyethyl methacrylate 868-77-9	positive	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
2-Hydroxyethyl methacrylate 868-77-9	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
[3-(2,3- Epoxypropoxy)propyl]tri methoxysilane 2530-83-8	A mutagenic potential can not be excluded.	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
methacrylic acid 79-41-4	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay)
2-Hydroxyethyl acrylate 818-61-1	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		not specified
2-Hydroxyethyl methacrylate 868-77-9	negative	oral: gavage		rat	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
2-Hydroxyethyl methacrylate 868-77-9	negative	oral: gavage		Drosophila melanogaster	not specified
[3-(2,3- Epoxypropoxy)propyl]tri methoxysilane 2530-83-8	A mutagenic potential can not be excluded.			mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
methacrylic acid 79-41-4	negative	inhalation		mouse	equivalent or similar to OECD Guideline 478 (Genetic Toxicology: Rodent Dominant Lethal Test)
methacrylic acid 79-41-4	negative	oral: gavage		mouse	equivalent or similar to OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Camphene 79-92-5	negative	oral: gavage		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
2-Hydroxyethyl acrylate 818-61-1	negative	oral: gavage		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

V013.0

SDS No.: 153594

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
2-Hydroxyethyl methacrylate 868-77-9	not carcinogenic	inhalation	2 y 6 h/d, 5 d/w	rat	female	equivalent or similar OECD Guideline 451 (Carcinogenicity Studies)
2-Hydroxyethyl methacrylate 868-77-9	not carcinogenic	inhalation	2 y 6 h/d, 5 d/w	rat	male	equivalent or similar OECD Guideline 451 (Carcinogenicity Studies)
[3-(2,3- Epoxypropoxy)propyl]tri methoxysilane 2530-83-8	not carcinogenic	dermal	lifetime 3 applications/ week	mouse	male	not specified
methacrylic acid 79-41-4	not carcinogenic	inhalation	2 y	mouse	male/female	OECD Guideline 451 (Carcinogenicity Studies)

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
Isobornyl acrylate 5888-33-5	NOAEL P 100 mg/kg NOAEL F1 100 mg/kg	screening	oral: gavage	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
2-Hydroxyethyl methacrylate 868-77-9	NOAEL P $>= 1.000 \text{ mg/kg}$ NOAEL F1 $>= 1.000 \text{ mg/kg}$	screening	oral: gavage	rat	equivalent or similar to OECD Guideline 422 (Combined Repeated Dose Toxicity Study)
[3-(2,3- Epoxypropoxy)propyl]tri methoxysilane 2530-83-8	NOAEL P 1.000 mg/kg	One generation study	oral: gavage	rat	OECD Guideline 415 (One- Generation Reproduction Toxicity Study)
methacrylic acid 79-41-4	NOAEL P 50 mg/kg NOAEL F1 400 mg/kg NOAEL F2 400 mg/kg	Two generation study	oral: gavage	rat	OECD Guideline 416 (Two- Generation Reproduction Toxicity Study)

STOT-single exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances	Assessment	Route of	Target Organs	Remarks
CAS-No.		exposure		
methacrylic acid 79-41-4	May cause respiratory irritation.			

V013.0

SDS No.: 153594

STOT-repeated exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Isobornyl acrylate 5888-33-5	NOAEL 100 mg/kg	oral: gavage	once daily	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
2-Hydroxyethyl methacrylate 868-77-9	NOAEL 100 mg/kg	oral: gavage	49 d daily	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
2-Hydroxyethyl methacrylate 868-77-9	NOAEL 0,352 mg/l	inhalation	90 d 6 h/d, 5 d/w	rat	OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day)
Ethanone, 2,2-dimethoxy- 1,2-diphenyl- 24650-42-8	NOAEL 42,8 mg/kg	oral: unspecified	45 d	rat	QSAR (Quantitative Structure Activity Relationship)
[3-(2,3- Epoxypropoxy)propyl]tri methoxysilane 2530-83-8	NOAEL 1.000 mg/kg	oral: gavage	28 d 5 d / week	rat	OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)
[3-(2,3- Epoxypropoxy)propyl]tri methoxysilane 2530-83-8	NOAEL 0,225 mg/l	inhalation: aerosol	14 d 6 h / d, 4/5 exposures/week	rat	equivalent or similar to OECD Guideline 412 (Repeated Dose Inhalation Toxicity: 28/14-Day)
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8	NOAEL 100 mg/kg	oral: gavage	3 m 5 d/w	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
methacrylic acid 79-41-4		inhalation	90 d 6 h/d, 5 d/w	rat	OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day)
Camphene 79-92-5	LOAEL 1.000 mg/kg	oral: gavage	28 days daily	rat	OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)

Aspiration hazard:

No data available.

11.2 Information on other hazards

not applicable

SDS No.: 153594

SECTION 12: Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Isobornyl acrylate	LC50	0,704 mg/l	96 h	Danio rerio	OECD Guideline 203 (Fish,
5888-33-5					Acute Toxicity Test)
2-Hydroxyethyl methacrylate	LC50	> 100 mg/l	96 h	Oryzias latipes	OECD Guideline 203 (Fish,
868-77-9					Acute Toxicity Test)
Ethanone, 2,2-dimethoxy-1,2-	LC50	29,67 mg/l	96 h	QSAR	QSAR (Quantitative
diphenyl-					Structure Activity
24650-42-8					Relationship)
Ethanone, 2,2-dimethoxy-1,2-	NOEC	3,215 mg/l	30 d	QSAR	QSAR (Quantitative
diphenyl-					Structure Activity
24650-42-8					Relationship)
[3-(2,3-	LC50	55 mg/l	96 h	Cyprinus carpio	EU Method C.1 (Acute
Epoxypropoxy)propyl]trimeth					Toxicity for Fish)
oxysilane					
2530-83-8					
Diphenyl-2,4,6-	LC50	1,4 mg/l	96 h	Cyprinus carpio	OECD Guideline 203 (Fish,
trimethylbenzoyl phosphine					Acute Toxicity Test)
oxide					
75980-60-8					
methacrylic acid	LC50	85 mg/l	96 h	Salmo gairdneri (new name:	EPA OTS 797.1400 (Fish
79-41-4				Oncorhynchus mykiss)	Acute Toxicity Test)
methacrylic acid	NOEC	10 mg/l	35 d	Danio rerio	OECD Guideline 210 (fish
79-41-4					early lite stage toxicity test)
Camphene	LC50	0,72 mg/l	96 h	Brachydanio rerio (new name:	OECD Guideline 203 (Fish,
79-92-5				Danio rerio)	Acute Toxicity Test)
2-Hydroxyethyl acrylate	LC50	4,8 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish,
818-61-1					Acute Toxicity Test)

Toxicity (aquatic invertebrates):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
Isobornyl acrylate 5888-33-5	EC50	1 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
2-Hydroxyethyl methacrylate 868-77-9	EC50	380 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Ethanone, 2,2-dimethoxy-1,2-diphenyl-24650-42-8	EC50	18,387 mg/l	48 h	QSAR	QSAR (Quantitative Structure Activity Relationship)
[3-(2,3- Epoxypropoxy)propyl]trimeth oxysilane 2530-83-8	EC50	324 mg/l	48 h	Simocephalus vetulus	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8	EC50	3,53 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
methacrylic acid 79-41-4	EC50	> 130 mg/l	48 h	Daphnia magna	EPA OTS 797.1300 (Aquatic Invertebrate Acute

V013.0

SDS No.: 153594

					Toxicity Test, Freshwater Daphnids)
Camphene 79-92-5	EC50	0,72 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
2-Hydroxyethyl acrylate 818-61-1	EC50	9,3 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Chronic toxicity (aquatic invertebrates):

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Isobornyl acrylate	NOEC	0,092 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia
5888-33-5		_			magna, Reproduction Test)
2-Hydroxyethyl methacrylate	NOEC	24,1 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia
868-77-9					magna, Reproduction Test)
Ethanone, 2,2-dimethoxy-1,2-	NOEC	2,288 mg/l	21 d	other:	QSAR (Quantitative
diphenyl-					Structure Activity
24650-42-8					Relationship)
[3-(2,3-	NOEC	100 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia
Epoxypropoxy)propyl]trimeth					magna, Reproduction Test)
oxysilane					
2530-83-8					
methacrylic acid	NOEC	53 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia
79-41-4					magna, Reproduction Test)
Camphene	NOEC	0,092 mg/l	21 day	Daphnia magna	OECD 211 (Daphnia
79-92-5					magna, Reproduction Test)
2-Hydroxyethyl acrylate	NOEC	0,86 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia
818-61-1				_	magna, Reproduction Test)

Toxicity (Algae):

SDS No.: 153594 V013.0

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Isobornyl acrylate 5888-33-5	NOEC	0,405 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Isobornyl acrylate 5888-33-5	EC50	1,98 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
2-Hydroxyethyl methacrylate 868-77-9	EC50	836 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
2-Hydroxyethyl methacrylate 868-77-9	NOEC	400 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Ethanone, 2,2-dimethoxy-1,2-diphenyl-24650-42-8	EC50	19,66 mg/l	96 h	other:	QSAR (Quantitative Structure Activity Relationship)
[3-(2,3- Epoxypropoxy)propyl]trimeth oxysilane 2530-83-8	EC50	350 mg/l	96 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
[3-(2,3- Epoxypropoxy)propyl]trimeth oxysilane 2530-83-8	NOEC	130 mg/l	96 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8	EC50	> 2,01 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8	EC10	1,56 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
methacrylic acid 79-41-4	NOEC	8,2 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
methacrylic acid 79-41-4	EC50	45 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Camphene 79-92-5	EC50	1,75 mg/l	72 h	Raphidocelis subcapitata (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Camphene 79-92-5	NOEC	0,07 mg/l	72 h	Raphidocelis subcapitata (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
2-Hydroxyethyl acrylate 818-61-1	EC50	6 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
2-Hydroxyethyl acrylate 818-61-1	NOEC	1 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity (microorganisms):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
2-Hydroxyethyl methacrylate 868-77-9	EC0	> 3.000 mg/l	16 h	Pseudomonas fluorescens	other guideline:
[3-(2,3- Epoxypropoxy)propyl]trimeth oxysilane 2530-83-8	EC50	> 100 mg/l	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8	EC 50	> 1.000 mg/l	30 min		OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
methacrylic acid 79-41-4	EC10	100 mg/l	17 h	Pseudomonas putida	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm-

V013.0

SDS No.: 153594

		ĺ			Test)
Camphene	EC10	490 mg/l	3 h		OECD Guideline 209
79-92-5					(Activated Sludge,
					Respiration Inhibition Test)
2-Hydroxyethyl acrylate	EC10	> 100 mg/l	72 h	activated sludge, domestic	other guideline:
818-61-1					

12.2. Persistence and degradability

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Isobornyl acrylate 5888-33-5	inherently biodegradable	aerobic	73,9 %	60 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Isobornyl acrylate 5888-33-5	not readily biodegradable.	aerobic	57 %	28 d	OECD Guideline 310 (Ready BiodegradabilityCO2 in Sealed Vessels (Headspace Test)
2-Hydroxyethyl methacrylate 868-77-9	readily biodegradable	aerobic	92 - 100 %	14 d	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))
Ethanone, 2,2-dimethoxy-1,2-diphenyl-24650-42-8	not readily biodegradable.	aerobic	3 %	28 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
[3-(2,3- Epoxypropoxy)propyl]trimeth oxysilane 2530-83-8	not readily biodegradable.	aerobic	37 %	28 d	EU Method C.4-A (Determination of the "Ready" BiodegradabilityDissolved Organic Carbon (DOC) Die-Away Test)
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8	not readily biodegradable.	aerobic	0 - 10 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
methacrylic acid 79-41-4	readily biodegradable	aerobic	86 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
methacrylic acid 79-41-4	inherently biodegradable	aerobic	100 %	14 d	OECD Guideline 302 B (Inherent biodegradability: Zahn- Wellens/EMPA Test)
Camphene 79-92-5	not readily biodegradable.	aerobic	78 %	28 day	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Camphene 79-92-5	inherently biodegradable	aerobic	78 %	28 day	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
2-Propenoic acid, 2-methyl-, 2-(2-hydroxyethoxy)ethyl ester 2351-43-1	readily biodegradable	aerobic	92 - 100 %	14 d	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))
2-Hydroxyethyl acrylate 818-61-1	readily biodegradable	aerobic	> 79 - 80 %	28 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)

12.3. Bioaccumulative potential

The table below presents the data of the classified substances present in the mixture.

Hazardous substances		Exposure time	Temperature	Species	Method
CAS-No.	n factor (BCF)				
Isobornyl acrylate 5888-33-5	37	56 h	24 °C	Danio rerio	OECD Guideline 305 (Bioconcentration: Flow-through Fish Test)

V013.0

SDS No.: 153594

12.4. Mobility in soil

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	LogPow	Temperature	Method
CAS-No. Isobornyl acrylate	4,52		OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC
5888-33-5			Method)
2-Hydroxyethyl methacrylate 868-77-9	0,42	25 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
Ethanone, 2,2-dimethoxy-1,2-diphenyl-24650-42-8	2,95	25 °C	QSAR (Quantitative Structure Activity Relationship)
[3-(2,3- Epoxypropoxy)propyl]trimeth oxysilane 2530-83-8	0,5	20 °C	QSAR (Quantitative Structure Activity Relationship)
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8	3,1	23 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
methacrylic acid 79-41-4	0,93	22 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
Camphene 79-92-5	4,35		not specified
2-Hydroxyethyl acrylate 818-61-1	-0,17	25 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)

12.5. Results of PBT and vPvB assessment

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	PBT / vPvB
CAS-No.	
Isobornyl acrylate	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
5888-33-5	Bioaccumulative (vPvB) criteria.
2-Hydroxyethyl methacrylate	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
868-77-9	Bioaccumulative (vPvB) criteria.
Ethanone, 2,2-dimethoxy-1,2-diphenyl-	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
24650-42-8	Bioaccumulative (vPvB) criteria.
[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
2530-83-8	Bioaccumulative (vPvB) criteria.
Diphenyl-2,4,6-trimethylbenzoyl phosphine	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
oxide	Bioaccumulative (vPvB) criteria.
75980-60-8	
methacrylic acid	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
79-41-4	Bioaccumulative (vPvB) criteria.
Camphene	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
79-92-5	Bioaccumulative (vPvB) criteria.
2-Hydroxyethyl acrylate	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
818-61-1	Bioaccumulative (vPvB) criteria.

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

V013.0

SDS No.: 153594

Product disposal:

Do not empty into drains / surface water / ground water.

Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

08 04 09* waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes
for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We
will be happy to advise you.

SECTION 14: Transport information

14.1. UN number or ID number

ADR	3082
RID	3082
ADN	3082
IMDG	3082
IATA	3082

14.2. UN proper shipping name

ADR	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2,2-
	Dimethoxy-1,2-diphenylethan-1-one,Isobornyl acrylate)
RID	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2,2-
	Dimethoxy-1,2-diphenylethan-1-one,Isobornyl acrylate)
ADN	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2,2-
	Dimethoxy-1,2-diphenylethan-1-one,Isobornyl acrylate)
IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2,2-
	Dimethoxy-1,2-diphenylethan-1-one,Isobornyl acrylate)
IATA	Environmentally hazardous substance, liquid, n.o.s. (2,2-Dimethoxy-1,2-

diphenylethan-1-one, Isobornyl acrylate)

14.3. Transport hazard class(es)

ADR	9
RID	9
ADN	9
IMDG	9
IATA	9

14.4. Packing group

ADR	III
RID	III
ADN	III
IMDG	III
IATA	III

14.5. Environmental hazards

ADR	Environmentally Hazardous
RID	Environmentally Hazardous

SDS No.: 153594

ADN Environmentally Hazardous

IMDG Marine Pollutant

IATA Environmentally Hazardous

14.6. Special precautions for user

ADR not applicable
Tunnelcode:
RID not applicable
ADN not applicable
IMDG not applicable
IATA not applicable

The transport classifications in this section apply generally to packed and bulk goods alike. For containers with a net volume of no more than 5 L for liquid substances or a net mass of no more than 5 kg for solid substances per individual or inner package, the exemptions SP 375 (ADR), A197 (IATA), 2.10.2.7 (IMDG), NZ 4.3(10) may be applied, which can result in a deviation from the transport classification for packed goods.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 2024/590):

Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):

Not applicable Persistent organic pollutants (Regulation (EU) 2019/1021):

Not applicable

VOC content < 3 %

(2010/75/EC)

15.2. Chemical safety assessment

A chemical safety assessment has been carried out.

SDS No.: 153594

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H228 Flammable solid.

H302 Harmful if swallowed.

H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H360Fd May damage fertility. Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

ED: Substance identified as having endocrine disrupting properties

EU OEL: Substance with a Union workplace exposure limit
EU EXPLD 1: Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2 Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC: Substance of very high concern (REACH Candidate List)

PBT: Substance fulfilling persistent, bioaccumulative and toxic criteria

PBT/vPvB: Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very

bioaccumulative criteria

vPvB: Substance fulfilling very persistent and very bioaccumulative criteria

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.