

SAPPHIRE HI-TORQUE RANGE

Page: 1

**Revision date:** 05/02/2016

Revision No: 6

## Section 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product name: SAPPHIRE HI-TORQUE RANGE

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Gear Lubricant

## 1.3. Details of the supplier of the safety data sheet

Company name: ROCOL

ROCOL House Swillington Leeds

West Yorkshire LS26 8BS ENGLAND

**Tel:** +44 (0) 113 232 2700 **Fax:** +44 (0) 113 232 2740

Email: <a href="mailto:customer-service@rocol.com">customer-service@rocol.com</a>

## 1.4. Emergency telephone number

Emergency tel: +44 (0) 113 232 2600

### Section 2: Hazards identification

# 2.1. Classification of the substance or mixture

Classification under CLP: Skin Sens. 1A: H317

Most important adverse effects: May cause an allergic skin reaction.

# 2.2. Label elements

Label elements:

Hazard statements: H317: May cause an allergic skin reaction.

Hazard pictograms: GHS07: Exclamation mark



Signal words: Warning

**Precautionary statements:** P261: Avoid breathing dust/fumes/gas/mist/vapours/spray.

P272: Contaminated work clothing should not be allowed out of the workplace.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+352: IF ON SKIN: Wash with plenty of water/.

P333+313: If skin irritation or rash occurs: Get medical attention.

[cont...]

## SAPPHIRE HI-TORQUE RANGE

Page: 2

### 2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

### Section 3: Composition/information on ingredients

### 3.2. Mixtures

### **Hazardous ingredients:**

## MINERAL OIL (NOTE L - LESS THAN 3% DMSO EXTRACT)

EINECS	CAS	PBT / WEL	CLP Classification	Percent
265-090-8	64741-88-4	Substance with a Community	-	20-50%
		workplace exposure limit.		

### SOLVENT REFINED BASE OIL (NOTE L- LESS THAN 3% DMSO EXTRACT)

265-166-0	64742-62-7	Substance with a Community	-	20-50%
		workplace exposure limit.		

### AMINE PHOSPHATE

931-384-6	-	-	Aquatic Chronic 2: H411; Acute Tox. 4:	<1%
			H302; Eye Dam. 1: H318; Skin Sens.	
			1A: H317; Flam. Liq. 3: H226	

### Section 4: First aid measures

### 4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water. Consult a doctor.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

# 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** Exposure may cause coughing or wheezing.

Delayed / immediate effects: Delayed effects can be expected after long-term exposure.

## 4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

## Section 5: Fire-fighting measures

## 5.1. Extinguishing media

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

SAPPHIRE HI-TORQUE RANGE

Page: 3

## 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes.

### 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with

skin and eyes.

### Section 6: Accidental release measures

## 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn

leaking containers leak-side up to prevent the escape of liquid.

## 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

## 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal

by an appropriate method.

### 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

### Section 7: Handling and storage

# 7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Avoid the formation or spread of mists in the air.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

# 7.3. Specific end use(s)

Specific end use(s): No data available.

# Section 8: Exposure controls/personal protection

# 8.1. Control parameters

### Hazardous ingredients:

# MINERAL OIL (NOTE L - LESS THAN 3% DMSO EXTRACT)

### Workplace exposure limits: Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL

## SAPPHIRE HI-TORQUE RANGE

Page: 4

UK	5mg/m3	10mg/m3	-	-
SOLVENT REFINED BASE OIL (NOTE L- LESS THAN 3% DMSO EXTRACT)				

EU	-	5 mg/m3		
----	---	---------	--	--

### **DNEL/PNEC Values**

**DNEL / PNEC** No data available.

### 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area. **Respiratory protection:** Respiratory protection not normally required.

Hand protection: Gloves (oil-resistant). Nitrile gloves. Eye protection: Safety glasses with side-shields. Skin protection: Impermeable protective clothing.

Environmental: No special requirement.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Blue

Odour: Barely perceptible odour

Evaporation rate: Negligible

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Insoluble

Viscosity: Non-viscous

Boiling point/range°C: >300 Melting point/range°C: < -20

Flammability limits %: lower: 1 upper: 6

Flash point°C: > 240 Part.coeff. n-octanol/water: Not applicable. Autoflammability°C: > 200 Vapour pressure: Not applicable. Relative density: 0.85 pH: Not applicable.

VOC g/l: Not applicable.

### 9.2. Other information

Other information: No data available.

# Section 10: Stability and reactivity

## 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

## 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

## SAPPHIRE HI-TORQUE RANGE

Page: 5

## 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

# 10.4. Conditions to avoid

Conditions to avoid: Heat.

## 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

### 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

## **Section 11: Toxicological information**

## 11.1. Information on toxicological effects

### Relevant hazards for product:

Hazard	Route	Basis
Respiratory/skin sensitisation	-	Hazardous: calculated

## Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** Exposure may cause coughing or wheezing.

Delayed / immediate effects: Delayed effects can be expected after long-term exposure.

## Section 12: Ecological information

### 12.1. Toxicity

Ecotoxicity values: No data available.

## 12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

## 12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

## 12.4. Mobility in soil

Mobility: Readily absorbed into soil.

# 12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

## SAPPHIRE HI-TORQUE RANGE

Page: 6

### 12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

### Section 13: Disposal considerations

### 13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Disposal of packaging: Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

NB: The user's attention is drawn to the possible existence of regional or national regulations

regarding disposal.

### **Section 14: Transport information**

Transport class: This product does not require a classification for transport.

### **Section 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

### 15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by

the supplier.

## **Section 16: Other information**

### Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

2015/830.

Compiled in accordance with REACH.

Phrases used in s.2 and s.3: H226: Flammable liquid and vapour.

H302: Harmful if swallowed.

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage.

H411: Toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and

shall be used only as a guide. This company shall not be held liable for any damage resulting

from handling or from contact with the above product.