Regulation EC No 1907/2006 Art.31

Productname: **ZG-90** Creationdate: 10.10.18 Version: 1.2

Ref.Nr.: BDS002295 20180904 BDS002295 3 20181010 (EN) Replaces:

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ZG-90

Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

Paints

1.3. Details of the supplier of the safety data sheet

CRC Industries UK Ltd. Wylds Road Castlefield Industrial Estate TA6 4DD Bridgwater Somerset United Kingdom

Tel.: +44 1278 727200 Fax.: +44 1278 425644 E-mail: hse.uk@crcind.com

1.4. Emergency telephone number

(+44)(0)1278 72 7200 (office hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Physical: Aerosols, category 1

Extremely flammable aerosol.

Pressurised container: May burst if heated.

Classification is based on test data.

Health: Skin irritation, category 2

Causes skin irritation. Eye irritation, category 2 Causes serious eye irritation.

Classification based on calculation method.

Environment: Hazardous to the aquatic environment, chronic category 3

Harmful to aquatic life with long lasting effects.

Classification based on calculation method.



1/11

Regulation EC No 1907/2006 Art.31

 Productname :
 ZG-90
 Creationdate :
 10.10.18 Version : 1.2

 Ref.Nr.:
 BDS002295 3 20181010 (EN)
 Replaces:
 BDS002295 20180904

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008

Hazard pictogram(s):





Signal word: Danger

Hazard statement(s): H222 : Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

H315 : Causes skin irritation.

H319: Causes serious eye irritation.

H412: Harmful to aquatic life with long lasting effects.

Precautionary statement(s): P102 : Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P280 : Wear protective gloves/protective clothing/eye protection/face

protection.

P410/412: Protect from sunlight. Do not expose to temperatures exceeding

50°C/122°F.

P501-2: Dispose of contents/container to an authorised waste collection point.

Supplemental Hazard

information:

Contains:

2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime

May produce an allergic reaction.

2.3. Other hazards

No information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable.

3.2. Mixtures

Hazardous ingredient	Registration number	CAS-nr.	EC-nr	w/w %	Hazard Class and Category	Hazard statement	Notes
dimethyl ether	01-2119472128- 37	115-10- 6	204- 065-8	30-60	Flam. Gas 1, Press. Gas	H220,H280	А
4-methylpentan-2-one; isobutyl methyl ketone	01-2119473980- 30	108-10- 1	203- 550-1	5-10	Flam. Liq. 2, Acute Tox. 4, Eye Irrit. 2, STOT SE 3	H225,H332,H319,H335	А
ethylbenzene	01-2119489370- 35	100-41- 4	202- 849-4	1-5	Flam. Liq. 2, Acute Tox. 4, STOT RE 2, Asp. Tox. 1	H225,H332,H373,H304	А



Regulation EC No 1907/2006 Art.31

Productname: **ZG-90**

Ref.Nr.:

BDS002295 3 20181010 (EN)

Creationdate: Replaces:

10.10.18 Version: 1.2

BDS002295 20180904

1-methoxy-2-propanol; monopropylene glycol methyl ether	01-2119457435- 35	107-98- 2	203- 539-1	1-5	Flam. Liq. 3, STOT SE 3	H226,H336	Α
trizinc bis(orthophosphate)	01-2119485044- 40	7779- 90-0	231- 944-3	<1	Aquatic Acute 1, Aquatic Chronic 1	H400,H410	
2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime	01-2119539477- 28	96-29-7	202- 496-6	<1	Carc. 2, Acute Tox. 4, Eye Dam. 1, Skin Sens. 1	H351,H312,H318,H317	В
2-methoxy-1-methylethyl acetate	01-2119475791- 29	108-65- 6	203- 603-9	0-1	Flam. Liq. 3	H226	Α
Fatty acids, C6-19-branched, zinc salts	01-2119980048- 32	68551- 44-0	271- 378-4	0-1	Aquatic Chronic 2	H411	
xylene	01-2119488216- 32	1330- 20-7	215- 535-7	<12.5	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2	H226,H332,H312,H315	A,W
zinc oxide	01-2119463881- 32	1314- 13-2	215- 222-5	<0.25	Aquatic Acute 1, Aquatic Chronic 1	H400,H410	В
Explanation notes							

B: substance with national established workplace exposure limit

W: Note: substance mentioned on the list of CMR-substances of the Dutch Ministry of Social Affairs and Employment (SZW)

(* Explanation phrases : see chapter 16)

SECTION 4: First aid measures

4.1. Description of first aid measures

Contact with eyes: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Contact with skin: Take off contaminated clothing and wash before reuse.

> IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Inhalation:

Call a POISON CENTER or doctor/physician if you feel unwell.

Ingestion: If swallowed do not induce vomiting because of risk of aspiration into the

lungs. If aspiration is suspected obtain immediate medical attention

4.2. Most important symptoms and effects, both acute and delayed

Inhalation: Excessive inhalation of solvent vapours may give rise to nausea, headaches

and dizziness

Ingestion: After vomiting of swallowed product aspiration into lungs is likely. Solvents

may induce chemical pneumonia.

Symptoms: sore throat, abdominal pain, nausea, vomiting

Skin contact: Irritating to skin

Symptoms: redness and pain

Eye contact: Irritating to eyes

Symptoms: redness and pain, impaired vision

4.3. Indication of any immediate medical attention and special treatment needed

General Advice: If you feel unwell, seek medical advice (show the label where possible



3/11

Regulation EC No 1907/2006 Art.31

Creationdate: Productname: **ZG-90**

10.10.18 Version: 1.2 Ref.Nr.: BDS002295 3 20181010 (EN) Replaces: BDS002295 20180904

If symptoms persist always call a doctor

SECTION 5: Firefighting measures

5.1. Extinguishing media

foam, carbon dioxide or dry agent

Do not use water jet extinguishing media, due to the risk of spreading fire.

5.2. Special hazards arising from the substance or mixture

Aerosols may explode if heated above 50°C Forms hazardous decomposition products CO,CO2

5.3. Advice for firefighters

Keep container(s) exposed to fire cool, by spraying with water In case of fire, do not breathe fumes

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Shut off all ignition sources Ensure adequate ventilation Wear suitable protective clothing and gloves.

6.2. Environmental precautions

Do not allow to enter public sewers and watercourses

If polluted water reaches drainage systems or water courses, immediately inform appropriate authorities

6.3. Methods and material for containment and cleaning up

Absorb spillage in suitable inert material

Place in appropriate container

This material and/or its container must be disposed of as hazardous waste.

6.4. Reference to other sections

For further information see section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling



4/11

Regulation EC No 1907/2006 Art.31

 Productname :
 ZG-90
 Creationdate :
 10.10.18 Version : 1.2

 Ref.Nr.:
 BDS002295_3_20181010 (EN)
 Replaces:
 BDS002295_20180904

Keep away from heat and sources of ignition

Take precautionary measures against static discharges

Equipment should be earthed

Use explosion-proof electrical/ventilating/lighting/.../equipment.

Use only non-sparking tools.

Do not breathe aerosols or vapours.

Ensure adequate ventilation

Avoid contact with skin and eyes.

Wash thoroughly after use

Wear protective gloves/protective clothing/eye protection/face protection.

Eyewash bottles should be available

7.2. Conditions for safe storage, including any incompatibilities

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Keep out of reach of children.

7.3. Specific end use(s)

Paints

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits:

Hazardous ingredient	CAS-nr.	method	
EU established exposure limits:			
ethylbenzene	100-41-4	TWA	100 ppm
		STEL	200 ppm
1-methoxy-2-propanol; monopropylene glycol methyl ether	107-98-2	TWA	100 ppm
		STEL	150 ppm
4-methylpentan-2-one; isobutyl methyl ketone	108-10-1	TWA	20 ppm
		STEL	50 ppm
2-methoxy-1-methylethyl acetate	108-65-6	TWA	50 ppm
		STEL	100 ppm
dimethyl ether	115-10-6	TWA	1000 ppm
xylene	1330-20-7	TWA	50 ppm
		STEL	100 ppm
National established exposure limits, United Kingdom		*	•
ethylbenzene	100-41-4	TWA	100 ppm
		STEL	125 ppm
1-methoxy-2-propanol; monopropylene glycol methyl ether	107-98-2	TWA	100 ppm
		STEL	150 ppm
4-methylpentan-2-one; isobutyl methyl ketone	108-10-1	TWA	50 ppm
		STEL	100 ppm



Regulation EC No 1907/2006 Art.31

Productname: ZG-90 Creationdate: 10.10.18 Version: 1.2 Ref.Nr.: BDS002295 20180904 BDS002295 3 20181010 (EN) Replaces:

2-methoxy-1-methylethyl acetate	108-65-6	TWA	50 ppm
		STEL	100 ppm
dimethyl ether	115-10-6	TWA	400 ppm
		STEL	500 ppm
xylene	1330-20-7	TWA	50 ppm
		STEL	100 ppm
National established exposure limits, Ireland			•
ethylbenzene	100-41-4	TWA	100 ppm
		STEL	200 ppm
1-methoxy-2-propanol; monopropylene glycol methyl ether	107-98-2	TWA	100 ppm
		STEL	150 ppm
4-methylpentan-2-one; isobutyl methyl ketone	108-10-1	TWA	20 ppm
		STEL	50 ppm
2-methoxy-1-methylethyl acetate	108-65-6	TWA	50 ppm
		STEL	100 ppm
dimethyl ether	115-10-6	TWA	1000 ppm
		STEL	-
xylene	1330-20-7	TWA	50 ppm
		STEL	100 ppm
2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime	96-29-7	TWA	3 ppm
		STEL	10 ppm

8.2. Exposure controls

Control procedures: Ensure adequate ventilation

Keep away from heat and sources of ignition

Take precautionary measures against static discharges

Personal protection: Take precautions to avoid contact with skin and eyes when handling the

Ensure adequate ventilation

In all cases handle and use the product in accordance with good industrial

hygiene practices.

inhalation: In case of insufficient ventilation, wear suitable respiratory equipment.

recommended respiratory protection: Air purifying respirator equiped with organic gas/vapor cartridge (type AX)

When handling the product wear chemical-resistant gloves (standard EN 374). hands and skin:

Recommended gloves: **Nitrile**

The breakthrough time of the glove should be longer than the total duration of

product use. If work lasts longer than the breakthrough time, gloves should be

changed part-way through.

Depending on amount and duration of use and the risk of contact with the product the gloves manufacturer can assist you in the selection of the right

glove material and breakthrough time.

Wear safety eyewear according to EN 166. eyes:

Environmental protection: Avoid release to the environment.

Collect spillage.

SECTION 9: Physical and chemical properties



Regulation EC No 1907/2006 Art.31

 Productname :
 ZG-90
 Creationdate :
 10.10.18 Version : 1.2

 Ref.Nr.:
 BDS002295_3_20181010 (EN)
 Replaces:
 BDS002295_20180904

9.1. Information on basic physical and chemical properties

(for aerosols data for the product without propellant)

Apperance: physical state: DME propelled liquid.

colour: See color cap.
Characteristic odor.
pH: Not applicable.

Boiling point/range: Not available.

Flash point: 15 °C (Closed Cup)

Evaporation rate: Not available.

Evaporation limits: upper limit: Not available.

Explosion limits : upper limit : Not available.
lower limit : Not available.
Vapour pressure : Not available.

Relative density: 1.08 g/cm3 (@ 20°C). **Solubility in water:** Insoluble in water

Auto-ignition: > 200 °C
Viscosity: Not available.

9.2. Other information

VOC = volatile organic 618 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reactions known if used for its intended purpose

10.2. Chemical stability

Stable

10.3. Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose

10.4. Conditions to avoid

Avoid overheating

10.5. Incompatible materials

Strong oxidising agent

10.6. Hazardous decomposition products

CO,CO2



7 / 11

Regulation EC No 1907/2006 Art.31

Productname: ZG-90 Creationdate: 10.10.18 Version: 1.2

Ref.Nr.: BDS002295 20180904 BDS002295 3 20181010 (EN) Replaces:

SECTION 11: Toxicological information

11.1. Information on toxicological effects

acute toxicity: based on available data the classification criteria are not met skin corrosion/irritation: Causes skin irritation. serious eye damage/irritation: Causes serious eye irritation. respiratory or skin based on available data the classification criteria are not met sensitisation: based on available data the classification criteria are not met germ cell mutagenicity: based on available data the classification criteria are not met carcinogenicity: based on available data the classification criteria are not met toxicity for reproduction: STOT-single exposure: based on available data the classification criteria are not met STOT repeated exposure: based on available data the classification criteria are not met based on available data the classification criteria are not met aspiration hazard:

Information on likely routes of exposure:

Inhalation: Inhalation of solvent vapours may give rise to nausea, headaches and

dizziness

Ingestion: After vomiting of swallowed product aspiration into lungs is likely. Solvents

may induce chemical pneumonia.

Skin contact: Irritating to skin Eve contact: Irritating to eyes

Toxicological data:

Hazardous ingredient	CAS-nr.	method	
1-methoxy-2-propanol; monopropylene glycol methyl ether	107-98-2	LD50 oral rat	4016 mg/kg
		LC50 inhal.rat	27596 mg/l
		LD50 derm.rabit	2000 mg/kg
4-methylpentan-2-one; isobutyl methyl ketone	108-10-1	LD50 oral rat	2080 mg/kg
2-methoxy-1-methylethyl acetate	108-65-6	LD50 oral rat	> 5000 mg/kg
		LC50 inhal.rat	10.8 mg/l
		LD50 derm.rat	> 5000 mg/kg
		LD50 derm.rabit	> 5000 mg/kg
dimethyl ether	115-10-6	LC50 inhal.rat	309 mg/l
zinc oxide	1314-13-2	LC50 inhal.rat	> 5.7 mg/l
2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime	96-29-7	LD50 oral rat	2326 mg/kg
		LD50 derm.rabit	1000 mg/kg

SECTION 12: Ecological information

12.1. Toxicity



Regulation EC No 1907/2006 Art.31

 Productname :
 ZG-90
 Creationdate :
 10.10.18 Version : 1.2

 Ref.Nr.:
 BDS002295_3_20181010 (EN)
 Replaces:
 BDS002295_20180904

Hazardous to the aquatic environment, chronic category 3 Harmful to aquatic life with long lasting effects.

Ecotoxicological data:

Hazardous ingredient	CAS-nr.	method	
1-methoxy-2-propanol; monopropylene glycol methyl ether	107-98-2	LC50 fish	6812 mg/l
		EC50 daphnia	23300 mg/l
4-methylpentan-2-one; isobutyl methyl ketone	108-10-1	LC50 fish	505 mg/l
2-methoxy-1-methylethyl acetate	108-65-6	LC50 fish	100-180 mg/l
		EC50 daphnia	> 400 mg/l
dimethyl ether	115-10-6	IC50 algae	154.9 mg/l
		LC50 fish	4.1 mg/l
		EC50 daphnia	4.4 mg/l
zinc oxide	1314-13-2	IC50 algae	0.136 mg/l
		LC50 fish	0.169 mg/l
		EC50 daphnia	1.7 mg/l
2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime	96-29-7	IC50 algae	11.8 mg/l
		LC50 fish	> 100 mg/l
		EC50 daphnia	201 mg/l

12.2. Persistence and degradability

No experimental data available

12.3. Bioaccumulative potential

No experimental data available

12.4. Mobility in soil

Insoluble in water

12.5. Results of PBT and vPvB assessment

No information available

12.6. Other adverse effects

No experimental data available GWP (global warming potential): 1

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product : This material and its container must be disposed of in a safe way.



9/11

CRC Industries UK Limited

Tel: +44 (0)1278 727200 Fax: +44 (0)1278 425644 web: www.actioncan.com

Regulation EC No 1907/2006 Art.31

 Productname :
 ZG-90
 Creationdate :
 10.10.18 Version : 1.2

 Ref.Nr.:
 BDS002295 3 20181010 (EN)
 Replaces:
 BDS002295 20180904

Do not discharge into drains or the environment, dispose to an authorised

waste collection point.

National regulations: Disposal should be in accordance with local, state or national legislation

SECTION 14: Transport information

14.1. UN number

UN-number: 1950

14.2. UN proper shipping name

Proper shipping name: AEROSOLS

14.3. Transport hazard class(es)

Class: 2.1 ADR/RID - Classification code: 5F

14.4. Packing group

Packing group: Not applicable.

14.5. Environmental hazards

ADR/RID - Environmentally hazardous:

IMDG - Marine pollutant:

No IATA/ICAO - Environmentally hazardous:

14.6. Special precautions for user

 ADR/RID - Tunnelcode:
 (D)

 IMDG - Ems:
 F-D, S-U

 IATA/ICAO - PAX:
 203

 IATA/ICAO - CAO
 203

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The Safety Data Sheet is compiled according to the current European requirements.



10 / 11

Regulation EC No 1907/2006 Art.31

 Productname :
 ZG-90
 Creationdate :
 10.10.18 Version : 1.2

 Ref.Nr.:
 BDS002295_3_20181010 (EN)
 Replaces:
 BDS002295_20180904

Regulation (EC) No 1907/2006 (REACH) Regulation (EC) No 1272/2008 (CLP)

Dir. 2013/10/EU, 2008/47/EC amendment of the aerosol dispenser directive 75/324/EEC.

15.2. Chemical safety assessment

No information available

SECTION 16: Other information

*Explanation hazard statements: H220 : Extremely flammable gas.

H225: Highly flammable liquid and vapour.

H226 : Flammable liquid and vapour.

H280 : Contains gas under pressure; may explode if heated.

H304: May be fatal if swallowed and enters airways.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction. H318: Causes serious eye damage. H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H335 : May cause respiratory irritation. H336 : May cause drowsiness or dizziness. H351 : Suspected of causing cancer .

H373: May cause damage to organs through prolonged or repeated exposure

.

H400: Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects. H411 : Toxic to aquatic life with long lasting effects.

acronyms and synonyms: TWA = time weight average

STEL = short time exposure limit VOC = volatile organic compounds PBT = persistant bioaccumulative toxic vPvB = very persitant very bioaccumulative

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation.

The information contained herewith is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It does not guarantee any specific properties. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC.

