



Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 17

LOCTITE SI 5940 BK

SDS No. : 165214

V003.1

Revision: 10.08.2023

printing date: 15.04.2025

Replaces version from: 06.06.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE SI 5940 BK

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:
Silicone sealant

1.3. Details of the supplier of the safety data sheet

Henkel Ltd
Adhesives
Wood Lane End
HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

SDSinfo.Adhesive@henkel.com

For Safety Data Sheet updates please visit our website <https://mysds.henkel.com/index.html#/appSelection> or www.henkel-adhesives.com.

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

The substance or mixture is not hazardous according to Regulation (EC) No 1272/2008 (CLP).

2.2. Label elements

Label elements (CLP):

The substance or mixture is not hazardous according to Regulation (EC) No 1272/2008 (CLP).

Supplemental information

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
Safety data sheet available on request.

2.3. Other hazards

None if used properly.
Evolves acetic acid during cure.
Self-classification according to Article 12(b) of (EU) 1272/2008.

Following substances are present in a concentration \geq the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

| | |
|---|----------|
| octamethylcyclotetrasiloxane 556-67-2 | PBT/vPvB |
| Dodecamethylcyclohexasiloxane 540-97-6 | PBT/vPvB |
| Decamethylcyclopentasiloxane 541-02-6 | PBT/vPvB |

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

| Hazardous components CAS-No. EC Number REACH-Reg No. | Concentration | Classification | Specific Conc. Limits, M-factors and ATEs | Add. Information |
|--|---------------|---|---|------------------|
| Titanium dioxide 13463-67-7 236-675-5 01-2119489379-17 | 1- < 5 % | Carc. 2, Inhalation, H351 | | |
| octamethylcyclotetrasiloxane 556-67-2 209-136-7 01-2119529238-36 | 0,1- < 1 % | Aquatic Chronic 1, H410 Repr. 2, H361f Flam. Liq. 3, H226 | M chronic = 10 | SVHC PBT/vPvB |
| Dodecamethylcyclohexasiloxane 540-97-6 208-762-8 01-2119517435-42 | 0,1- < 1 % | Aquatic Chronic 4, H413 | | SVHC PBT/vPvB |
| Decamethylcyclopentasiloxane 541-02-6 208-764-9 01-2119511367-43 | 0,1- < 1 % | | | SVHC PBT/vPvB |

If no ATE values are displayed, please refer to LD/LC50 values in Section 11.

For full text of the H - statements and other abbreviations see section 16 "Other information".

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Prolonged or repeated contact may cause skin irritation.

Prolonged or repeated contact may cause eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media:**

water, carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x) can be released.

Silicon dioxide

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Avoid contact with skin and eyes.

Wear protective equipment.

Ensure adequate ventilation.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Dispose of contaminated material as waste according to Section 13.

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Avoid skin and eye contact.

See advice in section 8

Ensure that workrooms are adequately ventilated.

Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

Good industrial hygiene practices should be observed.

7.2. Conditions for safe storage, including any incompatibilities

Store in a cool, well-ventilated place.

Refer to Technical Data Sheet

Never allow product to get in contact with water during storage

7.3. Specific end use(s)

Silicone sealant

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for
Great Britain

| Ingredient [Regulated substance] | ppm | mg/m ³ | Value type | Short term exposure limit category / Remarks | Regulatory list |
|--|-----|-------------------|-----------------------------------|--|-----------------|
| Silicon dioxide 112945-52-5 [SILICA, AMORPHOUS, INHALABLE DUST] | | 6 | Time Weighted Average (TWA): | | EH40 WEL |
| Silicon dioxide 112945-52-5 [SILICA, AMORPHOUS, RESPIRABLE DUST] | | 2,4 | Time Weighted Average (TWA): | | EH40 WEL |
| Silicon dioxide 112945-52-5 [Dust, respirable dust] | | 4 | Time Weighted Average (TWA): | | EH40 WEL |
| Silicon dioxide 112945-52-5 [Dust, inhalable dust] | | 10 | Time Weighted Average (TWA): | | EH40 WEL |
| Acetic acid 64-19-7 [ACETIC ACID] | 10 | 25 | Time Weighted Average (TWA): | Indicative | ECTLV |
| Acetic acid 64-19-7 [ACETIC ACID] | 20 | 50 | Short Term Exposure Limit (STEL): | Indicative | ECTLV |
| Acetic acid 64-19-7 [ACETIC ACID] | 10 | 25 | Time Weighted Average (TWA): | | EH40 WEL |
| Acetic acid 64-19-7 [ACETIC ACID] | 20 | 50 | Short Term Exposure Limit (STEL): | 15 minutes | EH40 WEL |
| Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE, RESPIRABLE] | | 4 | Time Weighted Average (TWA): | | EH40 WEL |
| Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE, TOTAL INHALABLE] | | 10 | Time Weighted Average (TWA): | | EH40 WEL |

Occupational Exposure Limits

Valid for
Ireland

| Ingredient [Regulated substance] | ppm | mg/m ³ | Value type | Short term exposure limit category / Remarks | Regulatory list |
|--|-----|-------------------|-----------------------------------|--|-----------------|
| Silicon dioxide 112945-52-5 [SILICA, AMORPHOUS] | | 6 | Time Weighted Average (TWA): | | IR_OEL |
| Silicon dioxide 112945-52-5 [SILICA, AMORPHOUS] | | 2,4 | Time Weighted Average (TWA): | | IR_OEL |
| Silicon dioxide 112945-52-5 [DUSTS NON-SPECIFIC] | | 10 | Time Weighted Average (TWA): | | IR_OEL |
| Silicon dioxide 112945-52-5 [DUSTS NON-SPECIFIC] | | 4 | Time Weighted Average (TWA): | | IR_OEL |
| Acetic acid 64-19-7 [ACETIC ACID] | 10 | 25 | Time Weighted Average (TWA): | Indicative OELV | IR_OEL |
| Acetic acid 64-19-7 [ACETIC ACID] | 10 | 25 | Time Weighted Average (TWA): | Indicative | ECTLV |
| Acetic acid 64-19-7 [ACETIC ACID] | 20 | 50 | Short Term Exposure Limit (STEL): | Indicative | ECTLV |

| | | | | | |
|--|----|----|--------------------------------------|-------------------------------|--------|
| Acetic acid 64-19-7 [ACETIC ACID] | 20 | 50 | Short Term Exposure Limit (STEL): | 15 minutes Indicative OELV | IR_OEL |
| Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE] | | 10 | Time Weighted Average (TWA): | | IR_OEL |
| Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE] | | 4 | Time Weighted Average (TWA): | | IR_OEL |

Predicted No-Effect Concentration (PNEC):

| Name on list | Environmental Compartment | Exposure period | Value | | | | Remarks |
|---|------------------------------------|--------------------|-----------------|-----|------------|--------|---------|
| | | | mg/l | ppm | mg/kg | others | |
| Octamethylcyclotetrasiloxane 556-67-2 | aqua (freshwater) | | 0,0015 mg/l | | | | |
| Octamethylcyclotetrasiloxane 556-67-2 | aqua (marine water) | | 0,00015 mg/l | | | | |
| Octamethylcyclotetrasiloxane 556-67-2 | sewage treatment plant (STP) | | 10 mg/l | | | | |
| Octamethylcyclotetrasiloxane 556-67-2 | sediment (freshwater) | | | | 3 mg/kg | | |
| Octamethylcyclotetrasiloxane 556-67-2 | sediment (marine water) | | | | 0,3 mg/kg | | |
| Octamethylcyclotetrasiloxane 556-67-2 | oral | | | | 41 mg/kg | | |
| Octamethylcyclotetrasiloxane 556-67-2 | Soil | | | | 0,84 mg/kg | | |
| Dodecamethylcyclohexasiloxane 540-97-6 | sediment (freshwater) | | | | 13,5 mg/kg | | |
| Dodecamethylcyclohexasiloxane 540-97-6 | oral | | | | 66,7 mg/kg | | |
| Dodecamethylcyclohexasiloxane 540-97-6 | sediment (marine water) | | | | 1,35 mg/kg | | |
| Decamethylcyclopentasiloxane 541-02-6 | aqua (freshwater) | | 0,0012 mg/l | | | | |
| Decamethylcyclopentasiloxane 541-02-6 | aqua (marine water) | | 0,00012 mg/l | | | | |
| Decamethylcyclopentasiloxane 541-02-6 | sewage treatment plant (STP) | | 10 mg/l | | | | |
| Decamethylcyclopentasiloxane 541-02-6 | sediment (freshwater) | | | | 11 mg/kg | | |
| Decamethylcyclopentasiloxane 541-02-6 | Soil | | | | 2,54 mg/kg | | |
| Decamethylcyclopentasiloxane 541-02-6 | oral | | | | 16 mg/kg | | |
| Decamethylcyclopentasiloxane 541-02-6 | sediment (marine water) | | | | 1,1 mg/kg | | |

Derived No-Effect Level (DNEL):

| Name on list | Application Area | Route of Exposure | Health Effect | Exposure Time | Value | Remarks |
|---|--------------------|-------------------|---|---------------|-------------------------|---------|
| Titanium dioxide 13463-67-7 | Workers | inhalation | Long term exposure - local effects | | 0,17 mg/m ³ | |
| Titanium dioxide 13463-67-7 | General population | inhalation | Long term exposure - local effects | | 0,028 mg/m ³ | |
| Octamethylcyclotetrasiloxane 556-67-2 | Workers | inhalation | Long term exposure - systemic effects | | 73 mg/m ³ | |
| Octamethylcyclotetrasiloxane 556-67-2 | Workers | inhalation | Long term exposure - local effects | | 73 mg/m ³ | |
| Octamethylcyclotetrasiloxane 556-67-2 | General population | inhalation | Long term exposure - systemic effects | | 13 mg/m ³ | |
| Octamethylcyclotetrasiloxane 556-67-2 | General population | inhalation | Long term exposure - local effects | | 13 mg/m ³ | |
| Octamethylcyclotetrasiloxane 556-67-2 | General population | oral | Long term exposure - systemic effects | | 3,7 mg/kg | |
| Dodecamethylcyclohexasiloxane 540-97-6 | Workers | inhalation | Long term exposure - local effects | | 1,22 mg/m ³ | |
| Dodecamethylcyclohexasiloxane 540-97-6 | Workers | inhalation | Acute/short term exposure - local effects | | 6,1 mg/m ³ | |
| Dodecamethylcyclohexasiloxane 540-97-6 | General population | inhalation | Long term exposure - local effects | | 0,3 mg/m ³ | |
| Dodecamethylcyclohexasiloxane 540-97-6 | General population | inhalation | Acute/short term exposure - local effects | | 1,5 mg/m ³ | |
| Decamethylcyclopentasiloxane 541-02-6 | Workers | inhalation | Long term exposure - systemic effects | | 97,3 mg/m ³ | |
| Decamethylcyclopentasiloxane 541-02-6 | Workers | inhalation | Long term exposure - local effects | | 24,2 mg/m ³ | |
| Decamethylcyclopentasiloxane 541-02-6 | General population | oral | Long term exposure - systemic effects | | 5 mg/kg | |
| Decamethylcyclopentasiloxane 541-02-6 | General population | inhalation | Long term exposure - systemic effects | | 17,3 mg/m ³ | |
| Decamethylcyclopentasiloxane 541-02-6 | General population | inhalation | Long term exposure - local effects | | 4,3 mg/m ³ | |

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

This recommendation should be matched to local conditions.

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.

Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.

Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties
9.1. Information on basic physical and chemical properties

| | |
|---|---|
| Delivery form | paste |
| Colour | black |
| Odor | Acetic acid |
| Physical state | liquid |
| Melting point | Not applicable, Product is a liquid |
| Solidification temperature | < -50 °C (< -58 °F) |
| Initial boiling point | > 100 °C (> 212 °F) |
| Flammability | The product is not flammable. |
| Explosive limits | Not applicable, The product is not flammable. |
| Flash point | > 100 °C (> 212 °F); Closed cup |
| Auto-ignition temperature | Not applicable, The product is not flammable. |
| Decomposition temperature | Not applicable, Substance/mixture is not self-reactive, no organic peroxide and does not decompose under foreseen conditions of use |
| pH | Not applicable, Product is non-soluble (in water). |
| Viscosity (kinematic) (40 °C (104 °F);) | > 20,5 mm ² /s |
| Solubility (qualitative) (20 °C (68 °F); Solvent: Water) | Partially soluble |
| Solubility (qualitative) (Solvent: Acetone) | Partially soluble |
| Partition coefficient: n-octanol/water | Not applicable |
| Vapour pressure (20 °C (68 °F)) | Mixture < 0,13 mbar |
| Density (20 °C (68 °F)) | 1,02 g/cm ³ None |
| Relative vapour density: (20 °C) | > 1 |
| Particle characteristics | Not applicable Product is a liquid |

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts with oxidants, acids and lyes

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Stable under normal conditions of storage and use.
Excessive heat.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

carbon oxides.
None if used for intended purpose.
Evolves acetic acid during cure.

SECTION 11: Toxicological information

General toxicological information:

Acetic acid is liberated slowly upon contact with moisture.
Acetic acid released during polymerisation of acetoxycuring RTV silicones is irritating to the eyes

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Species | Method |
|---|---------------|---------------|---------|---|
| Titanium dioxide 13463-67-7 | LD50 | > 5.000 mg/kg | rat | OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure) |
| octamethylcyclotetrasiloxane 556-67-2 | LD50 | > 4.800 mg/kg | rat | equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity) |
| Dodecamethylcyclohexasiloxane 540-97-6 | LD50 | > 2.000 mg/kg | rat | OECD Guideline 423 (Acute Oral toxicity) |
| Decamethylcyclopentasiloxane 541-02-6 | LD50 | > 5.000 mg/kg | rat | equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity) |

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Species | Method |
|---|---------------|----------------|---------|---|
| Titanium dioxide 13463-67-7 | LD50 | > 10.000 mg/kg | rabbit | not specified |
| octamethylcyclotetrasiloxane 556-67-2 | LD50 | > 2.375 mg/kg | rat | equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity) |
| Dodecamethylcyclohexasiloxane 540-97-6 | LD50 | > 2.000 mg/kg | rat | OECD Guideline 402 (Acute Dermal Toxicity) |
| Decamethylcyclopentasiloxane 541-02-6 | LD50 | > 2.000 mg/kg | rabbit | equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity) |

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Test atmosphere | Exposure time | Species | Method |
|--|---------------|-------------|-----------------|------------------|---------|--|
| Titanium dioxide 13463-67-7 | LC50 | > 6,82 mg/l | dust | 4 h | rat | not specified |
| octamethylcyclotetrasiloxane 556-67-2 | LC50 | 36 mg/l | dust/mist | 4 h | rat | OECD Guideline 403 (Acute Inhalation Toxicity) |
| Decamethylcyclopentasiloxane 541-02-6 | LC50 | 8,67 mg/l | dust/mist | 4 h | rat | OECD Guideline 403 (Acute Inhalation Toxicity) |

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Exposure time | Species | Method |
|---|----------------|------------------|---------|---|
| Titanium dioxide 13463-67-7 | not irritating | 4 h | rabbit | OECD Guideline 404 (Acute Dermal Irritation / Corrosion) |
| octamethylcyclotetrasiloxane 556-67-2 | not irritating | | rabbit | equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion) |
| Dodecamethylcyclohexasiloxane 540-97-6 | not irritating | 4 h | rabbit | OECD Guideline 404 (Acute Dermal Irritation / Corrosion) |
| Decamethylcyclopentasiloxane 541-02-6 | not irritating | 24 h | rabbit | equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion) |

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Exposure time | Species | Method |
|---|----------------|------------------|---------|--|
| Titanium dioxide 13463-67-7 | not irritating | | rabbit | OECD Guideline 405 (Acute Eye Irritation / Corrosion) |
| octamethylcyclotetrasiloxane 556-67-2 | not irritating | | rabbit | equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion) |
| Dodecamethylcyclohexasiloxane 540-97-6 | not irritating | | rabbit | OECD Guideline 405 (Acute Eye Irritation / Corrosion) |
| Decamethylcyclopentasiloxane 541-02-6 | not irritating | | rabbit | equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion) |

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Test type | Species | Method |
|---|-----------------|------------------------------------|------------|--|
| Titanium dioxide 13463-67-7 | not sensitising | Mouse local lymphnode assay (LLNA) | mouse | equivalent or similar to OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay) |
| Titanium dioxide 13463-67-7 | not sensitising | Buehler test | guinea pig | OECD Guideline 406 (Skin Sensitisation) |
| octamethylcyclotetrasiloxane 556-67-2 | not sensitising | Guinea pig maximisation test | guinea pig | OECD Guideline 406 (Skin Sensitisation) |
| Dodecamethylcyclohexasiloxane 540-97-6 | not sensitising | Guinea pig maximisation test | guinea pig | OECD Guideline 406 (Skin Sensitisation) |
| Decamethylcyclopentasiloxane 541-02-6 | not sensitising | Mouse local lymphnode assay (LLNA) | mouse | equivalent or similar to OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay) |

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Type of study / Route of administration | Metabolic activation / Exposure time | Species | Method |
|---|---------------|--|---|----------------|---|
| Titanium dioxide 13463-67-7 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| Titanium dioxide 13463-67-7 | negative | in vitro mammalian chromosome aberration test | with and without | | OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) |
| Titanium dioxide 13463-67-7 | negative | mammalian cell gene mutation assay | with and without | | OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) |
| Titanium dioxide 13463-67-7 | negative | in vitro mammalian cell micronucleus test | without | | equivalent or similar to OECD Guideline 487 (In vitro Mammalian Cell Micronucleus Test) |
| octamethylcyclotetrasilox ane 556-67-2 | negative | bacterial gene mutation assay | with and without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| octamethylcyclotetrasilox ane 556-67-2 | negative | in vitro mammalian chromosome aberration test | with and without | | equivalent or similar to OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) |
| octamethylcyclotetrasilox ane 556-67-2 | negative | mammalian cell gene mutation assay | with and without | | equivalent or similar to OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) |
| Dodecamethylcyclohexasi loxane 540-97-6 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| Dodecamethylcyclohexasi loxane 540-97-6 | negative | mammalian cell gene mutation assay | with and without | | OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) |
| Decamethylcyclopentasil oxane 541-02-6 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| Decamethylcyclopentasil oxane 541-02-6 | negative | in vitro mammalian chromosome aberration test | with and without | | OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) |
| Decamethylcyclopentasil oxane 541-02-6 | negative | mammalian cell gene mutation assay | with and without | | equivalent or similar to OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) |
| Titanium dioxide 13463-67-7 | negative | oral: gavage | | rat | OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test) |
| octamethylcyclotetrasilox ane 556-67-2 | negative | inhalation | | rat | equivalent or similar to OECD Guideline 475 (Mammalian Bone Marrow Chromosome Aberration Test) |
| octamethylcyclotetrasilox ane 556-67-2 | negative | oral: gavage | | rat | equivalent or similar to OECD Guideline 478 (Genetic Toxicology: Rodent Dominant Lethal Test) |
| Dodecamethylcyclohexasi loxane 540-97-6 | negative | intraperitoneal | | mouse | OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test) |
| Decamethylcyclopentasil oxane 541-02-6 | negative | inhalation | | rat | OECD Guideline 486 (Unscheduled DNA Synthesis (UDS) Test with Mammalian Liver Cells in vivo) |
| Decamethylcyclopentasil oxane 541-02-6 | negative | inhalation: vapour | | rat | OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test) |

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous components CAS-No. | Result | Route of application | Exposure time / Frequency of treatment | Species | Sex | Method |
|--|------------------|-------------------------|---|---------|-------------|---|
| Titanium dioxide 13463-67-7 | not carcinogenic | oral: feed | 103 w daily | rat | male/female | not specified |
| Decamethylcyclotetrasiloxane 541-02-6 | not carcinogenic | inhalation: vapour | 2 y 6 h/d, 5 d/w | rat | male/female | EPA OPPTS 870.4300 (Combined Chronic Toxicity / Carcinogenicity) |

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result / Value | Test type | Route of application | Species | Method |
|---|---|-----------------------------|-------------------------|---------|---|
| Titanium dioxide 13463-67-7 | NOAEL P \geq 1.000 mg/kg NOAEL F1 \geq 1.000 mg/kg | one- generation study | oral: feed | rat | OECD Guideline 443 (Extended One-Generation Reproductive Toxicity Study) |
| octamethylcyclotetrasiloxane 556-67-2 | NOAEL P 300 ppm NOAEL F1 300 ppm | two- generation study | inhalation | rat | equivalent or similar to OECD Guideline 416 (Two- Generation Reproduction Toxicity Study) |
| Dodecamethylcyclohexasiloxane 540-97-6 | NOAEL P 1.000 mg/kg NOAEL F1 1.000 mg/kg | screening | oral: gavage | rat | OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test) |
| Decamethylcyclotetrasiloxane 541-02-6 | NOAEL P \geq 2,496 mg/l NOAEL F1 \geq 2,496 mg/l NOAEL F2 \geq 2,496 mg/l | two- generation study | inhalation: vapour | rat | EPA OPPTS 870.3800 (Reproduction and Fertility Effects) |

STOT-single exposure:

No data available.

STOT-repeated exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result / Value | Route of application | Exposure time / Frequency of treatment | Species | Method |
|---|-------------------------|-------------------------|--|---------|---|
| Titanium dioxide 13463-67-7 | NOAEL > 1.000 mg/kg | oral: gavage | 92 d daily | rat | OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents) |
| octamethylcyclotetrasiloxane 556-67-2 | LOAEL 35 ppm | inhalation | 6 h nose only inhalation 5 days/week for 13 weeks | rat | OECD Guideline 412 (Repeated Dose Inhalation Toxicity: 28/14-Day) |
| octamethylcyclotetrasiloxane 556-67-2 | NOAEL 960 mg/kg | dermal | 3 w 5 d/w | rabbit | equivalent or similar to OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study) |
| Dodecamethylcyclohexasiloxane 540-97-6 | NOAEL 1.000 mg/kg | oral: gavage | 29 d daily, 7 d/w | rat | OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test) |
| Decamethylcyclopentasiloxane 541-02-6 | NOAEL >= 1.000 mg/kg | oral: gavage | 13 w daily | rat | OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents) |
| Decamethylcyclopentasiloxane 541-02-6 | NOAEL >= 2,42 mg/l | inhalation: vapour | 2 y 6 h/d, 5 d/w | rat | equivalent or similar to OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies) |
| Decamethylcyclopentasiloxane 541-02-6 | NOAEL >= 1.600 mg/kg | oral: gavage | 28 d 6 h/d, 7 d/w | rat | equivalent or similar to OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study) |

Aspiration hazard:

No data available.

11.2 Information on other hazards

not applicable

SECTION 12: Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

Self-classification according to Article 12(b) of (EU) 1272/2008.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|---|---------------|--------------------------------|---------------|--|--|
| Titanium dioxide 13463-67-7 | LC50 | Toxicity > Water solubility | 48 h | Leuciscus idus | OECD Guideline 203 (Fish, Acute Toxicity Test) |
| octamethylcyclotetrasiloxane 556-67-2 | NOEC | 0,0044 mg/l | 93 d | Salmo gairdneri (new name: Oncorhynchus mykiss) | EPA OPPTS 797.1600 (Fish Early Life Stage Toxicity Test) |
| octamethylcyclotetrasiloxane 556-67-2 | LC50 | Toxicity > Water solubility | 96 h | Oncorhynchus mykiss | EPA OTS 797.1400 (Fish Acute Toxicity Test) |
| Dodecamethylcyclohexasiloxane 540-97-6 | NOEC | Toxicity > Water solubility | 90 d | Oncorhynchus mykiss | OECD Guideline 210 (fish early life stage toxicity test) |
| Decamethylcyclopentasiloxane 541-02-6 | LC50 | Toxicity > Water solubility | 96 h | Leuciscus idus | OECD Guideline 204 (Fish, Prolonged Toxicity Test: 14-day Study) |
| Decamethylcyclopentasiloxane 541-02-6 | NOEC | Toxicity > Water solubility | 90 d | Oncorhynchus mykiss | OECD Guideline 210 (fish early life stage toxicity test) |

Toxicity (aquatic invertebrates):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|--|---------------|--------------------------------|---------------|---------------|---|
| Titanium dioxide 13463-67-7 | EC50 | Toxicity > Water solubility | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |
| octamethylcyclotetrasiloxane 556-67-2 | EC50 | Toxicity > Water solubility | 48 h | Daphnia magna | EPA OTS 797.1300 (Aquatic Invertebrate Acute Toxicity Test, Freshwater Daphnids) |
| Decamethylcyclopentasiloxane 541-02-6 | EC50 | Toxicity > Water solubility | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |

Chronic toxicity (aquatic invertebrates):

The table below presents the data of the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|---|---------------|--------------------------------|---------------|---------------|--|
| Titanium dioxide 13463-67-7 | NOEC | Toxicity > Water solubility | 21 d | Daphnia magna | OECD Guideline 202 (Daphnia sp. Chronic Immobilisation Test) |
| octamethylcyclotetrasiloxane 556-67-2 | NOEC | 7.9 µg/l | 21 d | Daphnia magna | EPA OTS 797.1330 (Daphnid Chronic Toxicity Test) |
| Dodecamethylcyclohexasiloxane 540-97-6 | NOEC | Toxicity > Water solubility | 21 d | Daphnia magna | OECD 211 (Daphnia magna, Reproduction Test) |
| Decamethylcyclopentasiloxane 541-02-6 | NOEC | Toxicity > Water solubility | 21 d | Daphnia magna | OECD 211 (Daphnia magna, Reproduction Test) |

| | | | | | |
|----------|--|--|--|--|--|
| 541-02-6 | | | | | |
|----------|--|--|--|--|--|

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|--|---------------|--------------------------------|---------------|---|--|
| Titanium dioxide 13463-67-7 | EC50 | Toxicity > Water solubility | 72 h | Pseudokirchneriella subcapitata | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Titanium dioxide 13463-67-7 | NOEC | Toxicity > Water solubility | 72 h | Pseudokirchneriella subcapitata | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| octamethylcyclotetrasiloxane 556-67-2 | EC50 | Toxicity > Water solubility | 96 h | Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata) | EPA OTS 797.1050 (Algal Toxicity, Tiers I and II) |
| octamethylcyclotetrasiloxane 556-67-2 | EC10 | 0,022 mg/l | 96 h | Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata) | EPA OTS 797.1050 (Algal Toxicity, Tiers I and II) |
| Dodecamethylcyclhexasiloxane 540-97-6 | NOEC | Toxicity > Water solubility | 72 h | Pseudokirchneriella subcapitata | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Dodecamethylcyclhexasiloxane 540-97-6 | EC50 | Toxicity > Water solubility | 72 h | Pseudokirchneriella subcapitata | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Decamethylcyclopentasiloxane 541-02-6 | NOEC | Toxicity > Water solubility | 96 h | Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata) | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Decamethylcyclopentasiloxane 541-02-6 | EC50 | Toxicity > Water solubility | 96 h | Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata) | OECD Guideline 201 (Alga, Growth Inhibition Test) |

Toxicity (microorganisms):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|--|---------------|--------------------------------|---------------|----------------------------|--|
| Titanium dioxide 13463-67-7 | EC0 | Toxicity > Water solubility | 24 h | Pseudomonas fluorescens | DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm- Test) |
| octamethylcyclotetrasiloxane 556-67-2 | EC50 | Toxicity > Water solubility | 3 h | activated sludge | ISO 8192 (Test for Inhibition of Oxygen Consumption by Activated Sludge) |
| Decamethylcyclopentasiloxane 541-02-6 | EC50 | > 2.000 mg/l | 3 h | activated sludge, domestic | EU Method C.11 (Biodegradation: Activated Sludge Respiration Inhibition Test) |

12.2. Persistence and degradability

The table below presents the data of the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Test type | Degradability | Exposure time | Method |
|--|----------------------------|-----------|---------------|------------------|--|
| octamethylcyclotetrasiloxane 556-67-2 | not readily biodegradable. | aerobic | 3,7 % | 29 d | OECD Guideline 310 (Ready BiodegradabilityCO ₂ in Sealed Vessels (Headspace Test) |
| Dodecamethylcyclhexasiloxane 540-97-6 | not readily biodegradable. | aerobic | 4,47 % | 28 d | OECD Guideline 310 (Ready BiodegradabilityCO ₂ in Sealed Vessels (Headspace Test) |
| Decamethylcyclopentasiloxane 541-02-6 | not readily biodegradable. | aerobic | 0,14 % | 28 d | OECD Guideline 310 (Ready BiodegradabilityCO ₂ in Sealed Vessels (Headspace Test) |

12.3. Bioaccumulative potential

The table below presents the data of the classified substances present in the mixture.

| Hazardous substances CAS-No. | Bioconcentration factor (BCF) | Exposure time | Temperature | Species | Method |
|---|-------------------------------|---------------|-------------|------------------------|---|
| octamethylcyclotetrasiloxane 556-67-2 | 12.400 | 28 d | | Pimephales promelas | EPA OTS 797.1520 (Fish Bioconcentration Test-Rainbow Trout) |
| Dodecamethylcyclohexasiloxane 540-97-6 | 1.160 | 49 d | | Pimephales promelas | OECD Guideline 305 (Bioconcentration: Flow-through Fish Test) |
| Decamethylcyclopentasiloxane 541-02-6 | 7.060 | 35 d | | Pimephales promelas | OECD Guideline 305 (Bioconcentration: Flow-through Fish Test) |

12.4. Mobility in soil

The table below presents the data of the classified substances present in the mixture.

| Hazardous substances CAS-No. | LogPow | Temperature | Method |
|---|--------|-------------|------------------|
| octamethylcyclotetrasiloxane 556-67-2 | 6,98 | 21,7 °C | other guideline: |
| Dodecamethylcyclohexasiloxane 540-97-6 | 8,87 | 23,6 °C | other guideline: |
| Decamethylcyclopentasiloxane 541-02-6 | 8,07 | 24,6 °C | other guideline: |

12.5. Results of PBT and vPvB assessment

The table below presents the data of the classified substances present in the mixture.

| Hazardous substances CAS-No. | PBT / vPvB |
|---|---|
| Titanium dioxide 13463-67-7 | According to Annex XIII of regulation (EC) 1907/2006 a PBT and vPvB assessment shall not be conducted for inorganic substances. |
| octamethylcyclotetrasiloxane 556-67-2 | Fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |
| Dodecamethylcyclohexasiloxane 540-97-6 | Fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |
| Decamethylcyclopentasiloxane 541-02-6 | Fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Do not empty into drains / surface water / ground water.

Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

08 04 10 Waste adhesives and sealants other than those mentioned in 08 04 09.

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information**14.1. UN number or ID number**

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.2. UN proper shipping name

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.3. Transport hazard class(es)

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.4. Packing group

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.5. Environmental hazards

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.6. Special precautions for user

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009):

Not applicable

Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):

Not applicable

Persistent organic pollutants (Regulation (EU) 2019/1021):

Not applicable

VOC content
(2010/75/EC)

< 5 %

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H226 Flammable liquid and vapour.

H351 Suspected of causing cancer.

H361f Suspected of damaging fertility.

H410 Very toxic to aquatic life with long lasting effects.

H413 May cause long lasting harmful effects to aquatic life.

| | |
|-------------|---|
| ED: | Substance identified as having endocrine disrupting properties |
| EU OEL: | Substance with a Union workplace exposure limit |
| EU EXPLD 1: | Substance listed in Annex I, Reg (EC) No. 2019/1148 |
| EU EXPLD 2 | Substance listed in Annex II, Reg (EC) No. 2019/1148 |
| SVHC: | Substance of very high concern (REACH Candidate List) |
| PBT: | Substance fulfilling persistent, bioaccumulative and toxic criteria |
| PBT/vPvB: | Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very bioaccumulative criteria |
| vPvB: | Substance fulfilling very persistent and very bioaccumulative criteria |

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.