

### 3. Composition/information on ingredients

#### 3.2. Mixtures

##### Hazardous ingredients:

NAPHTHA (PETROLEUM) , HYDROTREATED LIGHT  
 Registration Number: 01-2119475514-35-xxxx

| EC        | CAS        | Index number | CLP Classification                                                                                                | Percent |
|-----------|------------|--------------|-------------------------------------------------------------------------------------------------------------------|---------|
| 921-024-6 | 64742-49-0 | -            | Flam. Liq. 2 - H225<br>Skin Irrit. 2 - H315<br>STOT SE 3 - H336<br>Asp. Tox. 1 - H304<br>Aquatic Chronic 2 - H411 | 10-30%  |

##### MINERAL OIL (REFINED)

|           |            |   |                 |       |
|-----------|------------|---|-----------------|-------|
| 265-155-0 | 64742-52-5 | - | Not classified. | 5-10% |
|-----------|------------|---|-----------------|-------|

##### BUTANE

|           |          |   |                    |       |
|-----------|----------|---|--------------------|-------|
| 203-448-7 | 106-97-8 | - | Flam. Gas 1 - H220 | 5-10% |
|-----------|----------|---|--------------------|-------|

##### XYLENE

|           |           |   |                                                                                                                                                                                           |       |
|-----------|-----------|---|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|
| 215-535-7 | 1330-20-7 | - | Flam. Liq. 3 - H226<br>Acute Tox. 4 - H312, H332<br>Skin Irrit. 2 - H315<br>Eye Irrit. 2 - H319<br>STOT SE 3 - H335<br>STOT RE 2 - H373<br>Asp. Tox. 1 - H304<br>Aquatic Chronic 3 - H412 | 5-10% |
|-----------|-----------|---|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|

##### WHITE SPIRIT

|           |            |   |                                                                                                                         |       |
|-----------|------------|---|-------------------------------------------------------------------------------------------------------------------------|-------|
| 919-446-0 | 64742-82-1 | - | Flam. Liq. 3 - H226<br>EUH066<br>STOT SE 3 - H336<br>STOT RE 2 - H373<br>Asp. Tox. 1 - H304<br>Aquatic Chronic 2 - H411 | 5-10% |
|-----------|------------|---|-------------------------------------------------------------------------------------------------------------------------|-------|

##### ISOBUTANE

|           |         |   |                    |      |
|-----------|---------|---|--------------------|------|
| 200-857-2 | 75-28-5 | - | Flam. Gas 1 - H220 | 1-5% |
|-----------|---------|---|--------------------|------|

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY  
 Registration Number: 01-2119463258-33-xxxx

|           |            |   |                                                                         |      |
|-----------|------------|---|-------------------------------------------------------------------------|------|
| 919-857-5 | 64742-48-9 | - | Flam. Liq. 3 - H226<br>EUH066<br>STOT SE 3 - H336<br>Asp. Tox. 1 - H304 | < 1% |
|-----------|------------|---|-------------------------------------------------------------------------|------|

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

## 8.2. Exposure controls

### Protective equipment:



### Engineering measures:

Provide adequate general and local exhaust ventilation.

### General protective and hygienic measures:

DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

### Respiratory protection:

No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit. Use chemical cartridge protection with appropriate cartridge.

### Hand protection:

Use protective gloves.

### Eye protection:

Wear approved chemical safety goggles where eye exposure is reasonably probable. Use approved safety goggles or face shield.

### Other Protection:

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

## 9. Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

|                      |                            |
|----------------------|----------------------------|
| State:               | Aerosol                    |
| Colour:              | Black                      |
| Odour:               | Characteristic             |
| Solubility:          | Insoluble in water         |
| Flammability limits: | Lower: 3.0 % Upper: 18.6 % |

### 9.2. Other information

## 10. Stability and reactivity

### 10.1. Reactivity

### 10.2. Chemical stability

**Chemical stability:** Stable under normal temperature conditions.

### 10.3. Possibility of hazardous reactions

### 10.4. Conditions to avoid

**Conditions to avoid:** Avoid heat, flames and other sources of ignition. Avoid contact with: Strong oxidising agents. Strong alkalis. Strong mineral acids.

### 10.5. Incompatible materials

### 10.6. Hazardous decomposition products

**Fire creates:** Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).