



Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 21

LOCTITE LB 8023

SDS No. : 153630
V008.1

Revision: 21.11.2024

printing date: 15.04.2025

Replaces version from: 15.12.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE LB 8023

UFI: J15E-5WAX-K201-C3CE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Lubricant

1.3. Details of the supplier of the safety data sheet

Henkel Ltd

Adhesives

Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

SDSinfo.Adhesive@henkel.com

For Safety Data Sheet updates please visit our website www.mysds.henkel.com or www.henkel-adhesives.com.

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Skin irritation

Category 2

H315 Causes skin irritation.

Serious eye damage

Category 1

H318 Causes serious eye damage.

Skin sensitizer

Category 1

H317 May cause an allergic skin reaction.

Specific target organ toxicity - single exposure

Category 3

H335 May cause respiratory irritation.

Target organ: respiratory tract irritation

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Contains

Calcium oxide

Calcium dihydroxide
(C16-C24)Alkylbenzenesulfonic acid, Ca
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts

Sulfonic acids, petroleum, calcium salts

Signal word:

Danger

Hazard statement:

H318 Causes serious eye damage.
H335 May cause respiratory irritation.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.

**Precautionary statement:
Prevention**

P261 Avoid breathing vapors.
P280 Wear protective gloves/eye protection.

**Precautionary statement:
Response**

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

2.3. Other hazards

None if used properly.

Following substances are present in a concentration \geq the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in a concentration \geq the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No. EC Number REACH-Reg No.	Concentration	Classification	Specific Conc. Limits, M- factors and ATEs	Add. Information
Calcium oxide 1305-78-8 215-138-9 01-2119475325-36	10- 20 %	Skin Irrit. 2, Dermal, H315 Eye Dam. 1, H318 STOT SE 3, Inhalation, H335		EU OEL
Calcium dodecylbenzene sulfonate 26264-06-2 247-557-8	1- < 5 %	Skin Irrit. 2, H315 Eye Dam. 1, H318 Acute Tox. 4, Oral, H302 Aquatic Chronic 3, H412		
Calcium dihydroxide 1305-62-0 215-137-3 01-2119475151-45	1- < 3 %	Skin Irrit. 2, Dermal, H315 Eye Dam. 1, H318 STOT SE 3, Inhalation, H335		EU OEL
(C16-C24)Alkylbenzenesulfonic acid, Ca 70024-69-0 274-263-7 01-2119492616-28	1- < 5 %	Skin Sens. 1B, H317	Skin Sens. 1B; H317; C >= 10 %	
Benzenesulfonic acid, C10-16- alkyl derivs., calcium salts 68584-23-6 271-529-4 01-2119492627-25	1- < 5 %	Skin Sens. 1B, H317	Skin Sens. 1B; H317; C >= 10 %	
Sulfonic acids, petroleum, calcium salts 61789-86-4 263-093-9 01-2119488992-18	1- < 5 %	Skin Sens. 1B, H317		

If no ATE values are displayed, please refer to LD/LC50 values in Section 11.
For full text of the H - statements and other abbreviations see section 16 "Other information".

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation:**

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

SKIN: Redness, inflammation.

SKIN: Rash, Urticaria.

After eye contact: Corrosive, may cause permanent damage to eyes (impairment of vision).

RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

water, carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x) can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes.

Wear protective equipment.

Ensure adequate ventilation.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid skin and eye contact.

See advice in section 8

Hygiene measures:

Good industrial hygiene practices should be observed.

Do not eat, drink or smoke while working.

Wash hands before work breaks and after finishing work.

7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction.
Refer to Technical Data Sheet.

7.3. Specific end use(s)

Lubricant

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational Exposure Limits**Valid for
Great Britain

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Calcium oxide 1305-78-8 [CALCIUM OXIDE]		2	Time Weighted Average (TWA):		EH40 WEL
Calcium oxide 1305-78-8 [CALCIUM OXIDE (RESPIRABLE FRACTION)]		1	Time Weighted Average (TWA):	Indicative	ECTLV
Calcium oxide 1305-78-8 [CALCIUM OXIDE (RESPIRABLE FRACTION)]		4	Short Term Exposure Limit (STEL):	Indicative	ECTLV
Calcium oxide 1305-78-8 [CALCIUM OXIDE (RESPIRABLE FRACTION)]		1	Time Weighted Average (TWA):		EH40 WEL
Calcium oxide 1305-78-8 [CALCIUM OXIDE (RESPIRABLE FRACTION)]		4	Short Term Exposure Limit (STEL):	15 minutes	EH40 WEL
Graphite 7782-42-5 [GRAPHITE, INHALABLE DUST]		10	Time Weighted Average (TWA):		EH40 WEL
Graphite 7782-42-5 [GRAPHITE, RESPIRABLE DUST]		4	Time Weighted Average (TWA):		EH40 WEL
Calcium dihydroxide 1305-62-0 [CALCIUM HYDROXIDE]		5	Time Weighted Average (TWA):		EH40 WEL
Calcium dihydroxide 1305-62-0 [CALCIUM DIHYDROXIDE (RESPIRABLE FRACTION)]		4	Short Term Exposure Limit (STEL):	Indicative	ECTLV
Calcium dihydroxide 1305-62-0 [CALCIUM DIHYDROXIDE (RESPIRABLE FRACTION)]		1	Time Weighted Average (TWA):	Indicative	ECTLV
Calcium dihydroxide 1305-62-0 [CALCIUM HYDROXIDE (RESPIRABLE FRACTION)]		1	Time Weighted Average (TWA):		EH40 WEL
Calcium dihydroxide 1305-62-0 [CALCIUM HYDROXIDE (RESPIRABLE FRACTION)]		4	Short Term Exposure Limit (STEL):	15 minutes	EH40 WEL

Occupational Exposure LimitsValid for
Ireland

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Residual oils (petroleum), solvent-refined 64742-01-4 [Mineral oil Pure, Highly & Severely Refined]		5	Time Weighted Average (TWA):		IR_OEL
Calcium oxide 1305-78-8 [CALCIUM OXIDE (RESPIRABLE FRACTION)]		1	Time Weighted Average (TWA):	Indicative	ECTLV

FRACTION)]					
Calcium oxide 1305-78-8 [CALCIUM OXIDE (RESPIRABLE FRACTION)]		4	Short Term Exposure Limit (STEL):	Indicative	ECTLV
Calcium oxide 1305-78-8 [CALCIUM OXIDE (RESPIRABLE FRACTION)]		4	Short Term Exposure Limit (STEL):	15 minutes Indicative OELV	IR_OEL
Calcium oxide 1305-78-8 [CALCIUM OXIDE (RESPIRABLE FRACTION)]		1	Time Weighted Average (TWA):	Indicative OELV	IR_OEL
Calcium oxide 1305-78-8 [CALCIUM OXIDE]		4	Short Term Exposure Limit (STEL):	15 minutes Indicative OELV	IR_OEL
Calcium oxide 1305-78-8 [CALCIUM OXIDE]		1	Time Weighted Average (TWA):	Indicative OELV	IR_OEL
Distillates (petroleum), hydrotreated heavy naphthenic 64742-52-5 [MINERAL OILS THAT HAVE BEEN USED BEFORE IN INTERNAL COMBUSTION ENGINES TO LUBRICATE AND COOL THE MOVING PARTS WITHIN THE ENGINE]				Included in the regulation but with no data values. See regulation for further details	IR_OEL
Distillates (petroleum), hydrotreated heavy naphthenic 64742-52-5 [MINERAL OIL PURE, HIGHLY & SEVERELY REFINED]		5	Time Weighted Average (TWA):		IR_OEL
Distillates (petroleum), hydrotreated heavy naphthenic 64742-52-5 [MINERAL OILS THAT HAVE BEEN USED BEFORE IN INTERNAL COMBUSTION ENGINES TO LUBRICATE AND COOL THE MOVING PARTS WITHIN THE ENGINE]			Skin designation:	Can be absorbed through the skin.	IR_OEL
Graphite 7782-42-5 [GRAPHITE (ALL FORMS EXCEPT FIBRES) (RESPIRABLE FRACTION)]		2	Time Weighted Average (TWA):		IR_OEL
Graphite 7782-42-5 [GRAPHITE (ALL FORMS EXCEPT FIBRES)]		2	Time Weighted Average (TWA):		IR_OEL
Distillates (petroleum), solvent-refined heavy paraffinic 64741-88-4 [MINERAL OILS THAT HAVE BEEN USED BEFORE IN INTERNAL COMBUSTION ENGINES TO LUBRICATE AND COOL THE MOVING PARTS WITHIN THE ENGINE]				Included in the regulation but with no data values. See regulation for further details	IR_OEL
Distillates (petroleum), solvent-refined heavy paraffinic 64741-88-4 [MINERAL OIL PURE, HIGHLY & SEVERELY REFINED]		5	Time Weighted Average (TWA):		IR_OEL
Distillates (petroleum), solvent-refined heavy paraffinic 64741-88-4 [MINERAL OILS THAT HAVE BEEN USED BEFORE IN INTERNAL COMBUSTION ENGINES TO LUBRICATE AND COOL THE MOVING PARTS WITHIN THE ENGINE]			Skin designation:	Can be absorbed through the skin.	IR_OEL
Calcium distearate 1592-23-0 [STEARATES (EXCEPT LEAD STEARATE)]		10	Time Weighted Average (TWA):		IR_OEL
Calcium dihydroxide		4	Short Term Exposure	Indicative	ECTLV

1305-62-0 [CALCIUM DIHYDROXIDE (RESPIRABLE FRACTION)]			Limit (STEL):		
Calcium dihydroxide 1305-62-0 [CALCIUM DIHYDROXIDE (RESPIRABLE FRACTION)]		1	Time Weighted Average (TWA):	Indicative	ECTLV
Calcium dihydroxide 1305-62-0 [CALCIUM DIHYDROXIDE (RESPIRABLE FRACTION)]		4	Short Term Exposure Limit (STEL):	15 minutes Indicative OELV	IR_OEL
Calcium dihydroxide 1305-62-0 [CALCIUM DIHYDROXIDE (RESPIRABLE FRACTION)]		1	Time Weighted Average (TWA):	Indicative OELV	IR_OEL
Calcium dihydroxide 1305-62-0 [CALCIUM DIHYDROXIDE]		4	Short Term Exposure Limit (STEL):	15 minutes Indicative OELV	IR_OEL
Calcium dihydroxide 1305-62-0 [CALCIUM DIHYDROXIDE]		1	Time Weighted Average (TWA):	Indicative OELV	IR_OEL

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
Calcium oxide 1305-78-8	aqua (freshwater)		0,37 mg/l				
Calcium oxide 1305-78-8	aqua (marine water)		0,24 mg/l				
Calcium oxide 1305-78-8	aqua (intermittent releases)		0,37 mg/l				
Calcium oxide 1305-78-8	sewage treatment plant (STP)		2,27 mg/l				
Calcium oxide 1305-78-8	Soil				817,4 mg/kg		
Calcium oxide 1305-78-8	sediment (freshwater)						
Calcium oxide 1305-78-8	sediment (marine water)						
Calcium oxide 1305-78-8	Air						no hazard identified
Calcium oxide 1305-78-8	Predator						no potential for bioaccumulation
Calcium dihydroxide 1305-62-0	aqua (freshwater)		0,49 mg/l				
Calcium dihydroxide 1305-62-0	aqua (marine water)		0,32 mg/l				
Calcium dihydroxide 1305-62-0	aqua (intermittent releases)		0,49 mg/l				
Calcium dihydroxide 1305-62-0	sewage treatment plant (STP)		3 mg/l				
Calcium dihydroxide 1305-62-0	Soil				1080 mg/kg		
Sulfonic acids, petroleum, calcium salts 61789-86-4	aqua (freshwater)		1,00 mg/l				
Sulfonic acids, petroleum, calcium salts 61789-86-4	aqua (marine water)		1,0 mg/l				
Sulfonic acids, petroleum, calcium salts 61789-86-4	sewage treatment plant (STP)		1000,00 mg/l				

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Calcium oxide 1305-78-8	Workers	inhalation	Long term exposure - local effects		1 mg/m ³	no hazard identified
Calcium oxide 1305-78-8	Workers	inhalation	Acute/short term exposure - local effects		4 mg/m ³	no hazard identified
Calcium oxide 1305-78-8	General population	inhalation	Long term exposure - local effects		1 mg/m ³	no hazard identified
Calcium oxide 1305-78-8	General population	inhalation	Acute/short term exposure - local effects		4 mg/m ³	no hazard identified
Calcium dihydroxide 1305-62-0	Workers	Inhalation	Acute/short term exposure - local effects		4 mg/m ³	
Calcium dihydroxide 1305-62-0	Workers	Inhalation	Long term exposure - local effects		1 mg/m ³	
Calcium dihydroxide 1305-62-0	General population	Inhalation	Acute/short term exposure - local effects		4 mg/m ³	
Calcium dihydroxide 1305-62-0	General population	Inhalation	Long term exposure - local effects		1 mg/m ³	

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.

Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Delivery form	paste
Colour	Black
Odor	mild
Physical state	liquid
Melting point	Not applicable, Product is a liquid
Initial boiling point	Not available.
Flammability	Currently under determination
Explosive limits	Currently under determination
Flash point	Not applicable
Auto-ignition temperature	Currently under determination
Decomposition temperature	Not applicable, Substance/mixture is not self-reactive, no organic peroxide and does not decompose under foreseen conditions of use
pH	Not applicable, Product is non-soluble (in water).
Viscosity (kinematic)	Currently under determination
Solubility (qualitative)	Insoluble
(20 °C (68 °F); Solvent: Water)	
Partition coefficient: n-octanol/water	Not applicable
	Mixture
Vapour pressure	Not available.
Density	1,2648 g/cm ³ None
(20 °C (68 °F))	
Relative vapour density:	Not available.
Particle characteristics	Not applicable
	Product is a liquid

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity

10.1. Reactivity

None if used properly.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Stable under normal conditions of storage and use.

10.5. Incompatible materials

None if used properly.

SECTION 11: Toxicological information**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute oral toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Calcium oxide 1305-78-8	LD50	> 2.000 mg/kg	rat	OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure)
Calcium dodecylbenzene sulfonate 26264-06-2	LD50	1.300 mg/kg	rat	other guideline:
Calcium dihydroxide 1305-62-0	LD50	> 7.340 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
(C16- C24)Alkylbenzenesulfoni c acid, Ca 70024-69-0	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts 68584-23-6	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Sulfonic acids, petroleum, calcium salts 61789-86-4	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Calcium oxide 1305-78-8	LD50	> 2.500 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
Calcium dodecylbenzene sulfonate 26264-06-2	LD50	> 4.199 mg/kg	rabbit	not specified
Calcium dihydroxide 1305-62-0	LD50	> 2.500 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
(C16- C24)Alkylbenzenesulfoni c acid, Ca 70024-69-0	LD50	> 5.000 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts 68584-23-6	LD50	> 5.000 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
Sulfonic acids, petroleum, calcium salts 61789-86-4	LD50	> 5.000 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
Calcium oxide 1305-78-8	LC50	> 6,04 mg/l	dust/mist	4 h	rat	OECD Guideline 436 (Acute Inhalation Toxicity: Acute Toxic Class (ATC) Method)

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Calcium oxide 1305-78-8	irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Calcium dodecylbenzene sulfonate 26264-06-2	irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Calcium dihydroxide 1305-62-0	irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
(C16- C24)Alkylbenzenesulfoni c acid, Ca 70024-69-0	not irritating	4 h	rabbit	EPA OPPTS 870.2500 (Acute Dermal Irritation)
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts 68584-23-6	not irritating	4 h	rabbit	EPA OPPTS 870.2500 (Acute Dermal Irritation)
Sulfonic acids, petroleum, calcium salts 61789-86-4	not irritating	4 h	rabbit	EPA OPPTS 870.2500 (Acute Dermal Irritation)

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Calcium oxide 1305-78-8	Category 1 (irreversible effects on the eye)		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Calcium dodecylbenzene sulfonate 26264-06-2	Category 1 (irreversible effects on the eye)		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Calcium dihydroxide 1305-62-0	Category 1 (irreversible effects on the eye)		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
(C16- C24)Alkylbenzenesulfoni c acid, Ca 70024-69-0	not irritating		rabbit	EPA OPPTS 870.2400 (Acute Eye Irritation)
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts 68584-23-6	not irritating		rabbit	EPA OPPTS 870.2400 (Acute Eye Irritation)
Sulfonic acids, petroleum, calcium salts 61789-86-4	not irritating		rabbit	EPA OPPTS 870.2400 (Acute Eye Irritation)

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Calcium oxide 1305-78-8	not sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
(C16- C24)Alkylbenzenesulfoni c acid, Ca 70024-69-0	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts 68584-23-6	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Sulfonic acids, petroleum, calcium salts 61789-86-4	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Calcium oxide 1305-78-8	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Calcium dihydroxide 1305-62-0	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
(C16- C24)Alkylbenzenesulfoni c acid, Ca 70024-69-0	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
(C16- C24)Alkylbenzenesulfoni c acid, Ca 70024-69-0	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
(C16- C24)Alkylbenzenesulfoni c acid, Ca 70024-69-0	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts 68584-23-6	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts 68584-23-6	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts 68584-23-6	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Sulfonic acids, petroleum, calcium salts 61789-86-4	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Sulfonic acids, petroleum, calcium salts 61789-86-4	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Sulfonic acids, petroleum, calcium salts 61789-86-4	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
(C16- C24)Alkylbenzenesulfoni c acid, Ca 70024-69-0	negative	intraperitoneal		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts 68584-23-6	negative	intraperitoneal		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Sulfonic acids, petroleum, calcium salts 61789-86-4	negative	oral: gavage		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

Carcinogenicity

No data available.

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
Calcium oxide 1305-78-8	NOAEL P > 1.000 mg/kg		oral: gavage	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

STOT-single exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Assessment	Route of exposure	Target Organs	Remarks
Calcium dihydroxide 1305-62-0	May cause respiratory irritation.			

STOT-repeated exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Calcium oxide 1305-78-8	NOAEL 1.000 mg/kg	oral: gavage	up to 48 consecutive days daily	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
(C16- C24)Alkylbenzenesulfoni c acid, Ca 70024-69-0	NOAEL 500 mg/kg	oral: gavage	29 d daily	rat	OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts 68584-23-6	NOAEL 500 mg/kg	oral: gavage	29 d daily	rat	OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)
Sulfonic acids, petroleum, calcium salts 61789-86-4	NOAEL 1.000 mg/kg	oral: gavage	28 d daily	rat	OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)

Aspiration hazard:

No data available.

11.2 Information on other hazards

not applicable

SECTION 12: Ecological information**General ecological information:**

Do not empty into drains / surface water / ground water.

12.1. Toxicity**Toxicity (Fish):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Calcium oxide 1305-78-8	LC50	50,6 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Calcium dodecylbenzene sulfonate 26264-06-2	LC50	4,6 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
Calcium dodecylbenzene sulfonate 26264-06-2	NOEC	0,9 mg/l	28 d	Pimephales promelas	other guideline:
Calcium dihydroxide 1305-62-0	LC50	50,6 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
(C16- C24)Alkylbenzenesulfonic acid, Ca 70024-69-0	LC50	Toxicity > Water solubility	96 h	Cyprinodon variegatus	OECD Guideline 203 (Fish, Acute Toxicity Test)
Benzenesulfonic acid, C10- 16-alkyl derivs., calcium salts 68584-23-6	LL50	> 10.000 mg/l	96 h	Cyprinodon variegatus	OECD Guideline 203 (Fish, Acute Toxicity Test)
Sulfonic acids, petroleum, calcium salts 61789-86-4	LL50	> 1.000 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)

Toxicity (aquatic invertebrates):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Calcium oxide 1305-78-8	EC50	49,1 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Calcium dodecylbenzene sulfonate 26264-06-2	EC50	5,88 mg/l	48 h	Daphnia magna	other guideline:
Calcium dihydroxide 1305-62-0	EC50	49,1 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
(C16- C24)Alkylbenzenesulfonic acid, Ca 70024-69-0	EC50	Toxicity > Water solubility	48 h	Daphnia magna	EPA OTS 797.1300 (Aquatic Invertebrate Acute Toxicity Test, Freshwater Daphnids)
Benzenesulfonic acid, C10-16- alkyl derivs., calcium salts 68584-23-6	EC50	> 1.000 mg/l	48 h	Daphnia magna	EPA OTS 797.1300 (Aquatic Invertebrate Acute Toxicity Test, Freshwater Daphnids)
Sulfonic acids, petroleum, calcium salts 61789-86-4	EC50	> 1.000 mg/l	48 h	Daphnia magna	EPA OTS 797.1300 (Aquatic Invertebrate Acute Toxicity Test, Freshwater Daphnids)

Chronic toxicity (aquatic invertebrates):

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Calcium oxide 1305-78-8	NOEC	32 mg/l	14 d	Crangon septemspinosa	OECD Guideline 202 (Daphnia sp. Chronic Immobilisation Test)
Calcium dodecylbenzene sulfonate 26264-06-2	NOEC	1,65 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Calcium dihydroxide 1305-62-0	NOEC	32 mg/l	14 d	Crangon septemspinosa	OECD Guideline 202 (Daphnia sp. Chronic Immobilisation Test)

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Calcium oxide 1305-78-8	EC50	184,57 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Calcium oxide 1305-78-8	NOEC	48 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Calcium dodecylbenzene sulfonate 26264-06-2	EC50	29 mg/l	96 h	Raphidocelis subcapitata (new name: Pseudokirchneriella subcapitata)	other guideline:
Calcium dodecylbenzene sulfonate 26264-06-2	NOEC	0,5 mg/l	96 h	Raphidocelis subcapitata (new name: Pseudokirchneriella subcapitata)	other guideline:
Calcium dihydroxide 1305-62-0	EC50	184,57 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Calcium dihydroxide 1305-62-0	NOEC	48 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
(C16- C24)Alkylbenzenesulfonic acid, Ca 70024-69-0	EC50	Toxicity > Water solubility	72 h	Pseudokirchneriella subcapitata	EPA OTS 797.1050 (Algal Toxicity, Tiers I and II)
(C16- C24)Alkylbenzenesulfonic acid, Ca 70024-69-0	NOEC	Toxicity > Water solubility	72 h	Pseudokirchneriella subcapitata	EPA OTS 797.1050 (Algal Toxicity, Tiers I and II)
Benzenesulfonic acid, C10-16- alkyl derivs., calcium salts 68584-23-6	EC50	> 1.000 mg/l	72 h	Pseudokirchneriella subcapitata	EPA OTS 797.1050 (Algal Toxicity, Tiers I and II)
Benzenesulfonic acid, C10-16- alkyl derivs., calcium salts 68584-23-6	NOEC	1.000 mg/l	72 h	Pseudokirchneriella subcapitata	EPA OTS 797.1050 (Algal Toxicity, Tiers I and II)
Sulfonic acids, petroleum, calcium salts 61789-86-4	NOELR	100 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
Sulfonic acids, petroleum, calcium salts 61789-86-4	EL50	> 100 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity (microorganisms):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Calcium oxide 1305-78-8	EC20	229,2 mg/l	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Calcium dihydroxide 1305-62-0	EC20	229,2 mg/l	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
(C16- C24)Alkylbenzenesulfonic acid, Ca 70024-69-0	EC50	> 10.000 mg/l	3 h	activated sludge of a predominantly industrial sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Sulfonic acids, petroleum, calcium salts 61789-86-4	EC50	> 10.000 mg/l	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

12.2. Persistence and degradability

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Calcium dodecylbenzene sulfonate 26264-06-2	readily biodegradable	aerobic	> 75 %	11 d	OECD Guideline 301 E (Ready biodegradability: Modified OECD Screening Test)
(C16-C24)Alkylbenzenesulfonic acid, Ca 70024-69-0	not readily biodegradable.	aerobic	8 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts 68584-23-6	not readily biodegradable.	aerobic	8 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Sulfonic acids, petroleum, calcium salts 61789-86-4	not readily biodegradable.	aerobic	8 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)

12.3. Bioaccumulative potential

No substance data available.
No data available.

12.4. Mobility in soil

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	LogPow	Temperature	Method
Calcium dodecylbenzene sulfonate 26264-06-2	4,77		QSAR (Quantitative Structure Activity Relationship)
Sulfonic acids, petroleum, calcium salts 61789-86-4	22,12	25 °C	QSAR (Quantitative Structure Activity Relationship)

12.5. Results of PBT and vPvB assessment

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	PBT / vPvB
Calcium oxide 1305-78-8	According to Annex XIII to Regulation (EC) No 1907/2006, a PBT and vPvB assessment shall not be conducted for inorganic substances.
Calcium dihydroxide 1305-62-0	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
(C16-C24)Alkylbenzenesulfonic acid, Ca 70024-69-0	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts 68584-23-6	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Sulfonic acids, petroleum, calcium salts 61789-86-4	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Do not empty into drains / surface water / ground water.

Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

14 06 03 Other solvents and solvent mixtures

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information

14.1. UN number or ID number

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.2. UN proper shipping name

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.3. Transport hazard class(es)

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.4. Packing group

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.5. Environmental hazards

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.6. Special precautions for user

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 2024/590):

Not applicable

Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):

Not applicable

Persistent organic pollutants (Regulation (EU) 2019/1021):

Not applicable

VOC content
(2010/75/EC)

< 3 %

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H302 Harmful if swallowed.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.
H412 Harmful to aquatic life with long lasting effects.

ED:	Substance identified as having endocrine disrupting properties
EU OEL:	Substance with a Union workplace exposure limit
EU EXPLD 1:	Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2	Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC:	Substance of very high concern (REACH Candidate List)
PBT:	Substance fulfilling persistent, bioaccumulative and toxic criteria
PBT/vPvB:	Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very bioaccumulative criteria
vPvB:	Substance fulfilling very persistent and very bioaccumulative criteria

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,
Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.