

The Timken Company


4500 Mt Pleasant St. NW N. Canton, OH 44720

Phone: (234) 262-3000

E-Mail: <u>CustomerCAD@timken.com</u> • Web site: <u>www.timken.com</u>

Part Number UCF307, UCF 300 Four-Bolt Flanged Mounted Bearings - Set Screw Locking






<u>Specifications</u> | <u>Dimensions</u> | <u>Basic Load Ratings</u>


Specifications –						
	Bearing Number	UC307				
	Shaft Size d	35 mm				
	Locking Style	Set Screw Locking				
	Housing Construction	Four-Bolt Square Flange				

Dimensions -						
	Total Length L	135 mm 5.315 in				
	Housing Width A	36 mm 1.417 in				
	olt Hole Spacing J	100 mm 3.937 in				

Bolt Hole Size N	19 mm 0.748 in
Flange Thickness A1	16 mm 0.63 in
Center of Bearing from Housing End A2	20 mm 0.787 in
Inner Ring Width B	48 mm 1.890 in
Center of Bearing from Bearing End S	19 mm 0.748 in
Dimension A0	49 mm 1.922 in
Bolt Size	M16
Grease Nipple Size	A 1/4-28UNF

Basic Load Ratings –						
Static Load Rating	19300 N 4339 lbf					
Dynamic Load Rati	33400 N 7509 lbf					





Bearing Number	UC307			
Load Ratings - C _r	7509	lbf	33400	N
Load Ratings - C _{0r}	4339	lbf	19300	N
Weight	5.1	lb	2.3	kg
Bolt Size	M16			

THE TIMKEN COMPANY
NORTH CANTON, OHIO USA

UCF307

UCF 300 Four-Bolt Flanged Mounted Bearings - Set Screw Locking

Every reasonable effort has been made to ensure the accuracy of the information contained in this writing, but no liability is accepted for errors, omissions or for any other reason.

FOR DISCUSSION ONLY