

Shaft diameter mm inches	RHP designation		Dimensions (mm)							ISO Load ratings		Rec. max. speed rev/min	Mass (approx.) kg
	1000G Series	1100 Series	D	C	B	s	d1	M	r	dynamic Cr newtons	static Cor newtons		
55	1060-55G	1160-55	110.000	22.00	65.10	25.44	76.00	10.00	1.50	48000	33000	2800	1.47
60	1060-60G	1160-60											
2 3/16	1060-2 3/16G	1160-2 3/16											
2 1/4	1060-2 1/4G	1160-2 1/4											
2 3/8	1060-2 3/8G	1160-2 3/8											
2 1/2	1060-2 1/2G	1160-2 1/2											
60	1065-60G	1165-60	120.000	23.00	65.10	25.44	82.50	10.00	1.50	57500	40000	2600	2.02
65	1065-65G	1165-65											
2 1/2	1065-2 1/2G	1165-2 1/2											
60	1070-60G	1170-60	125.000	24.00	74.60	30.24	89.00	12.00	1.50	61000	45000	2450	2.27
65	1070-65G	1170-65											
70	1070-70G	1170-70											
2 1/16	1070-2 1/16G	1170-2 1/16											
2 1/2	1070-2 1/2G	1170-2 1/2											
2 3/8	1070-2 3/8G	1170-2 3/8											
2 1/16	1070-2 1/16G	1170-2 1/16											
65	1075-65G	1175-65	130.000	25.00	77.80	33.34	94.00	12.00	1.50	66000	49500	2300	2.61
70	1075-70G	1175-70											
75	1075-75G	1175-75											
2 1/16	1075-2 1/16G	1175-2 1/16											
2 3/4	1075-2 3/4G	1175-2 3/4											
2 7/8	1075-2 7/8G	1175-2 7/8											
2 1/16	1075-2 1/16G	1175-2 1/16											
3	1075-3G	1175-3											
75	1080-75G	1180-75	140.000	26.00	82.60	33.34	100.00	12.00	2.00	71500	54500	2150	3.23
80	1080-80G	1180-80											
2 1/16	1080-2 1/16G	1180-2 1/16											
3	1080-3G	1180-3											
3 3/16	1080-3 3/16G	1180-3 3/16											
3 1/4	1080-3 1/4G	1180-3 1/4											
80	1085-80G	1185-80	150.000	28.00	85.70	34.15	107.10	12.00	2.00	83000	64000	2000	3.74
85	1085-85G	1185-85											
3 3/16	1085-3 3/16G	1185-3 3/16											
3 1/4	1085-3 1/4G	1185-3 1/4											
3 3/8	1085-3 3/8G	1185-3 3/8											
3 1/16	1085-3 1/16G	1185-3 1/16											
85	1090-85G	1190-85	160.000	30.00	96.00	39.74	111.50	15.00	2.00	96000	71500	1900	4.99
90	1090-90G	1190-90											
3 1/16	1090-3 1/16G	1190-3 1/16											
3 1/2	1090-3 1/2G	1190-3 1/2											
95	3095-95G		200.000	45.00	117.48	49.31	127.10	16.00	2.50	157000	122000	1600	9.53
100	3095-100G												
3 1/16	3095-3 1/16G												
4	3095-4G												