LUMATI

Side Lever, One Hand, Air Operated and Push Type Grease Guns

Description Images and specifications can be subject to change without notice

Part No.

Mato Lubrication Kit E480

Grease Gun E500, Universal adaptor, Steel Tube E4024 and extra safe rubber hose, supplied with 4 jaw hydraulic coupler, Rigid tube for driveshaft F4020, each with a snap-on coupling, Rigid tube with slide-on connector, Conical and Universal connector. Supplied in carry case.

30 330 40



Standard One Hand Grease Gun, Pistol Grip

For 400gr. Cartridges or 500gr. Bulk Fill. Filler Nipple/Air Release Valve

Delivery tube can be fitted either horizontally or vertically ensuring optimal access for difficult to reach lubrication points. Packaging: Carton.



With 6" (150mm) Rigid Tube and 4 jaw Hydraulic Connector

32 101 20



Professional Air Operated Grease Gun

For 400 gr. Cartridges or 500 gr. Bulk Fill, Filler Nipple/Air Release Valve. Continuous flow with trigger held open. Unique 360 degree swivel head for ease of use. 40:1 Ratio. Air supply recommended. Working pressure 6.2 bar (90 psi). Industrial quality. Worldwide patent.

With 6" (150mm) Rigid Tube and 4 jaw Precision Hydraulic Connector







85gr. Capacity. Its small size makes it easy to fit in a tool box. Dual Outlet for One Hand or Mini Side Lever Action. Pressure Capability: 200bar.

ressure Capability. 2000ar.



With 4" (100mm) Rigid Tube and 4 jaw Standard Hydraulic Connector

32 120 70



For 400 gr. Cartridge or 500 gr. Bulk Fill, Filler Nipple/Air Release Valve. Suitable for use with Silicon Grease. Pressure capability over 300 bar (4,350 psi) with easy one hand operation. Vinyl hand cover provides a comfortable grip. Industrial quality. Package: Carton.



With 9" (225mm) Rubber Hose and 4 jaw Precision Hydraulic

Connector

54-0112



With Universal Connector.

30gr. capacity PT30



125gr. capacity

PT125



Push Type Grease Guns (High Pressure)

High pressure push type grease guns supplied with Universal and Conical connectors, with red protection cap.

Type PT80, 80cc capacity. Pressure 200 bar (zinc plated) 32 608 04



Type PT150, 150cc capacity. Pressure 200 bar (zinc plated) 32 615 04



Type PT300, 300cc capacity. Pressure 200 bar (zinc plated) 32 630 03



Issue 21 MATO GmbH & Co. KG www.lumatic.co.uk 13