

**Check valve**  
**HA-1/8-QS-4**  
Part number: 153446

FESTO



**Data sheet**

 [General operating condition](#)

| Feature                      | Value                                     |
|------------------------------|-------------------------------------------|
| Valve function               | Non-return function                       |
| Pneumatic connection, port 1 | R1/8                                      |
| Pneumatic connection, port 2 | QS-4                                      |
| Type of mounting             | Screw-in                                  |
| Standard nominal flow rate   | 138 l/min                                 |
| Operating pressure           | -1 bar ... 10 bar                         |
| Ambient temperature          | 0 °C ... 60 °C                            |
| Material housing             | Brass, nickel-plated                      |
| Operating medium             | Compressed air to ISO 8573-1:2010 [7:-:-] |
| Symbol                       | 00991455                                  |
| Min. diff. pressure, opening | 0.1 bar                                   |
| Min. diff. pressure, closing | 0.2 bar                                   |

| Feature                            | Value                                                                                      |
|------------------------------------|--------------------------------------------------------------------------------------------|
| Note on operating and pilot medium | Lubricated operation possible (in which case lubricated operation will always be required) |
| LABS (PWIS) conformity             | VDMA24364-B1/B2-L                                                                          |
| Product weight                     | 11 g                                                                                       |
| Note on materials                  | RoHS-compliant                                                                             |