


402 UNIFLEX sockets




American sizes: SAE AS 954, ASME B 107.1, HPQ high performance steel, chrome plated.



Code	"	d ₁ mm	d ₂ mm	d ₃ mm	L mm	t ₁ mm	t ₂ mm	Δg g	
01 14 00 06	6	9.2	12.7	5	32	5.5	10	16	5
01 14 00 07	7	10.4	12.7	6	33.5	6	11.5	16	5
01 14 00 08	8	11.6	12.7	6.7	35	8	13	17	5
01 14 00 09	9	13	12.7	8	36	8	12	20	5
01 14 00 10	10	14.2	12.7	9	38	12	14	38	5

402a UNIFLEX sockets



Code	"	d ₁ mm	d ₂ mm	d ₃ mm	L mm	t ₁ mm	t ₂ mm	Δg g	
01 54 00 14	7/32	8.6	12.7	4.8	32	5.5	10	17	5
01 54 00 16	1/4	9.6	12.7	5.2	32	5.5	10	16	5
01 54 00 18	9/32	11	12.7	6.4	32	6.5	10	19	5
01 54 00 20	5/16	11.6	12.7	6.7	35	8	13	17	5
01 54 00 22	11/32	12.7	12.7	8	35	7.5	11.5	19	5
01 54 00 24	3/8	13.6	12.7	9	38	8.6	13.1	20	5
01 54 00 28	7/16	15.7	12.7	10.5	39.5	10.7	15	23	5
01 54 00 32	1/2	17.3	12.7	12	41.5	11.1	16.5	27	5

402a/5 Set: UNIFLEX sockets



Content:
1/4; 5/16; 3/8; 7/16; 1/2"




Code	Δg g
9601 54 01	101

402aK UNIFLEX sockets



short version, HPQ high performance steel, chrome plated.




Code	"	d ₁ mm	d ₂ mm	d ₃ mm	L mm	t ₁ mm	t ₂ mm	Δg g	
01 54 10 24	3/8	13.6	12.7	6.7	34	9.1	12.0	18	5
01 54 10 34	9/16	19	12.7	13.1	37.5	10.3	11.8	25	5

40aSP Sockets spline-drive



MS-33787, MIL-W-8982, HPQ high performance steel, chrome plated.




Code	Spline size	"	d ₁ mm	d ₂ mm	d ₃ mm	L mm	t ₁ mm	t ₂ mm	Δg g	
01 01 10 07	7	7/32	8.6	10.7	5	22.2	6	14.2	7	1
01 01 10 08	8	1/4	9.5	10.7	5.6	22.2	7	14.2	10	1
01 01 10 09	9	9/32	11.2	11.2	6.6	22.2	8	12.4	10	1
01 01 10 10	10	5/16	11.6	11.6	7.1	22.2	8	12.2	12	1
01 01 10 12	12	3/8	13.8	13.8	8.6	23	8.7	12.6	18	1
01 01 10 14	14	7/16	15.7	15.7	10.4	25	10.7	14.1	24	1

40aLSP Sockets spline-drive



extra deep bolt clearance, MS-33787, MIL-W-8982, HPQ high performance steel, chrome plated.




Code	Spline size	"	d ₁ mm	d ₂ mm	d ₃ mm	L mm	t ₁ mm	t ₂ mm	Δg g	
01 02 10 07	7	7/32	8.6	10.7	5	50.8	6	42.8	18	1
01 02 10 08	8	1/4	9.5	10.7	5.6	50.8	8	42.8	24	1
01 02 10 10	10	5/16	11.6	11.6	7.1	50.8	8	40.8	27	1

402aSP Uniflex sockets spline-drive




MS-33787, MIL-W-8982, HPQ high performance steel, chrome plated.



Code	Spline size	"	d ₁ mm	d ₂ mm	d ₃ mm	L mm	t ₁ mm	t ₂ mm	Δg g	
01 54 20 16	8	1/4	9.5	12.7	5.6	32	6.4	9.8	16	5
01 54 20 20	10	5/16	11.6	12.7	7.1	35	8	13	18	5

41 Screwdriver sockets

for slotted screws, blades to DIN 5264, Chrome Alloy Steel, chrome plated.



Code	⊖	L ₁ mm	L ₂ mm	d mm	a mm	b mm	Δg g	
01 04 00 05	0.5x3	82	57	11.6	0.5	3	20	5
01 04 00 06	0.6x3.5	82	57	11.6	0.6	3.5	31	5
01 04 00 08	0.8x4	82	57	11.6	0.8	4	32	5
01 04 00 10	1x5.5	82	57	11.6	1	5.5	32	5
01 04 00 12	1.2x8	82	57	14	1.2	8	45	5