## Midget & Intermediate Manual and Mechanical Valves

Midget manually	/ OI	perated	valves.	<b>B43</b>	series
wiiaget manaan	, 0	perateu	vaives,	DTO	301103


Symbol	Туре	Actuator	Return	Operating force at 6 bar, N	Size	<b>Weight</b> Kg	Order code
(H	3/2	Button, black	Spring	36	G1/8	0,200	B43003BXS
	3/2	Button, black	Button	13	G1/8	0,200	B43003HXS
(=) 4 2 m/s 1 3 m/s	5/2	Button, black	Spring	36	G1/8	0,240	B43004BXS
F 13 14	5/2	Button, black	Button	13	G1/8	0,240	B43004HXS
(H) 2	3/2	Button, black	Air	13	G1/8	0,200	B43003BXP
T 10	3/2	Button, black	Air or button	13	G1/8	0,200	B43003HXP
F 13 14	5/2	Button, black	Air	13	G1/8	0,240	B43004BXP
F 13 14	5/2	Button, black	Air or button	13	G1/8	0,280	B43004XHP
	3/2	Lock down lever	Spring	9	G1/8	0,202	B43003LS
	3/2	Lock down lever	Spring	9	G1/8	0,242	B43004LS
A 1 10	3/2	Lock down lever	Air	3	G1/8	0,240	B43003LP
A	3/2	Lock down lever	Air	3	G1/8	0,280	B43004LP

**Note:** The standard button colour is black (X) For optional colour buttons change 8th character of order code e.g. B43004HXS = Black button, B43004HZS = Green button, B43004HYS = Red button.

X = Black

Z = Green

Y = Red



All 3/2 type B43 & B53 valves can be connected either as normally closed 3/2 valve (NC) or normally open 3/2 valve (NO) as required, by connecting the primary air supply to port 1 or port 3

