



## Housing units RCJTA25-XL-N (Series RCJTA)

two-bolt flanged housing units, cast iron, adapter sleeve, R seals

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue ordering system ([https://www.schaeffler.de/content.schaeffler.de/en/news\\_media/index.jsp](https://www.schaeffler.de/content.schaeffler.de/en/news_media/index.jsp)) or by telephone on +49 (91 32) 82 - 28 97.

d	25 mm
H	124 mm
U	42,5 mm
A	26,5 mm
A <sub>1</sub>	11 mm
A <sub>2</sub>	19 mm
B <sub>1</sub>	28 mm
d <sub>3 max</sub>	38 mm
J	99 mm
L	70 mm
N	11,5 mm
Q	M6

V	70 mm	
m	0,54 kg	Mass
C <sub>r</sub>	14400 N	Basic dynamic load rating, radial
C <sub>0r</sub>	8100 N	Basic static load rating, radial
	CJT05	Designation of housing
	GSH25-XL-2RSR-B	Designation of bearing
	KASK05	Bearing end cap, closed design. To be ordered separately.
		Slot for bearing end cap



