

Series KQ2: White body
Series KQ : Black body

Guide

Collet

Chuck

Suitable for use with nylon and urethane. Large retaining force.

Has large retaining force while holding force is increased by the collet.

Seal

Can be used for a wide range of pressures from a low vacuum up to a pressure of 1 MPa.

The use of a special profile ensures sealing and reduces resistance when the tube is inserted.

Connection thread

M, R, Rc

Release button

Series KQ2: Light gray

Series KQ : Blue

Light force for removal

When the fitting is removed from the tube, the chuck and collet are released, thus preventing them from biting into the tube excessively.

Tube

Body

O-ring

Stud

Effective when piping in a confined space.

The body and the threaded portion can rotate.
(To the degree for positioning)

PAT.

K ☐

M ☐

H ☐

KK ☐

D ☐

MS ☐

LQ ☐

MQR ☐

T ☐

One-touch IN/OUT connection.
Possible to use in vacuum to -100 kPa



Applicable Tubing

Tubing material	FEP, PFA, Nylon, Soft nylon ⁽¹⁾ , Polyurethane
Tubing O.D.	ø3.2, ø4, ø6, ø8, ø10, ø12, ø16

Note 1) Soft nylon tubing is not compatible with water.

Product's Color

Series	Body	Release button
Series KQ2	White	Light gray
Series KQ	Black	Blue

Specifications

Fluid		Air/Water ⁽²⁾
Operating pressure range ⁽³⁾		-100 kPa to 1 MPa
Proof pressure		3 MPa
Ambient and fluid temperature		-5 to 60°C, Water: 0 to 40°C (No freezing)
Thread	Mounting section	JIS B0203 (Taper thread for piping) JIS B0205 (Metric coarse thread)
	Nut section	JIS B0205 (Metric fine thread)
Seal on the threads		With sealant or none



Note 2) The surge pressure must be under the maximum operating pressure.

Note 3) Do not use the fittings with a leak tester or for vacuum retention because they are not guaranteed for zero leakage.

Principal Parts Material

Body	C3604, PBT, PP
Stud	C3604 (Thread portion)
Chuck	Stainless steel 304
Guide	Stainless steel 304, C3604, PBT
Collet, Release button	POM
Seal, O-ring	NBR
Gasket	Stainless steel 304, NBR



Made to Order
(Refer to page 58 for details.)

Series KQ2

45° Male Elbow: KQ2K

<10-32 UNF>




<NPT>




Applicable tubing O.D. (inch)	Connection thread UNF NPT	Model	H (Width across flats)	Note) øD1	øD2	L1	L2	A*	M	Min. port size	Mass (g)
1/8	10-32 UNF	KQ2K01-32	8	9.6	8	16.5	15	25.5	15.5	2.3	4
	1/8	KQ2K01-34S	11.11		10	16.5	21.6	33	15.5	2.5	9
5/32	10-32 UNF	KQ2K03-32	8	10.4	8	17	14.5	26	16	2.3	4
	1/8	KQ2K03-34S	11.11		10	19.6	32			2.8	9
3/16	1/8	KQ2K05-34S	11.11	11.4	10	18	19.6	32.5	16.5	3.6	10
1/4	10-32 UNF	KQ2K07-32	11.11	13.2	10	19	18	32	17	2.3	8
	1/8	KQ2K07-34S					19.6	34			10
	1/4	KQ2K07-35S	14.29				24	36		4.6	19
	3/8	KQ2K07-36S	17.46				25.4	37.5			32
5/16	1/8	KQ2K09-34S	12.7	15.2	12	20.5	21.1	37	18.5	6	11
	1/4	KQ2K09-35S	14.29				25.5	39			19
	3/8	KQ2K09-36S	17.46				26.9	41			32
	1/2	KQ2K09-37S					27.9	43			25
3/8	1/8	KQ2K11-34S	17.46	17.9	17	23.5	23.1	42	21	6	25
	1/4	KQ2K11-35S					26.5	43			25
	3/8	KQ2K11-36S					27.9	44.5		7	32
	1/2	KQ2K11-37S					32.1	46.5			58
1/2	1/4	KQ2K13-35S	17.46	21.7	17	25.5	27	46.5	22	8	27
	3/8	KQ2K13-36S					28.4	48		9.6	35
	1/2	KQ2K13-37S	22.23				32.6	50			61

<10-32 UNF>



<NPT>



* Reference dimensions after NPT thread installation.
Note) øD1: Max. diameter

Universal Male Elbow: KQ2V

<10-32 UNF>




<NPT>




Applicable tubing O.D. (inch)	Connection thread UNF NPT	Model	H (Width across flats)	Note) øD1	øD2	L1	L2	L3	A*	M	Min. port size	Mass (g)	
1/8	10-32 UNF	KQ2V01-32	8	8.4	9.8	17.2	11	18.5	15	12.7	2.3	5	
	1/8	KQ2V01-34S		9.6	13.4	21.5	13.6	25.6	22.5	15.5	2.5	14	
5/32	10-32 UNF	KQ2V03-32	8	10.4	9.8	20.5	11	18.5	15	16	2.3	6	
	1/8	KQ2V03-34S			13.4	22	13.6	25.6	22.5		2.8	14	
3/16	1/8	KQ2V05-34S	8	11.4	13.4	23	13.6	25.6	22.5	16.5	3.5	15	
1/4	10-32 UNF	KQ2V07-32	8	13.2	13.4	24	12	24	20.5	17	2.3	13	
	1/8	KQ2V07-34S			15.3	23.5	18.5	32	26.5		4.6	15	
	1/4	KQ2V07-35S	11.11		17.6	28.5	14.6	27.6	24.5	18.5	6	24	
	3/8	KQ2V09-34S			20.6	27.5	19.4	35.4	30		46	30	
5/16	1/4	KQ2V09-35S	12.7	15.2	19	35	29.5	30	21	7	40		
	3/8	KQ2V09-36S			20.6	27.5	19.4	35.4			30	48	
	1/4	KQ2V11-35S	12.7		17.9	20.6	30.5	19	35	29.5	22	9	68
3/8	KQ2V11-36S	19.4		35.4				30	30	85			
1/2	3/8	KQ2V13-36S	17.46	21.7				27	35.5	20.4			34.9
	1/2	KQ2V13-37S			23.6	38.1	31			85			

<10-32 UNF>



<NPT>



* Reference dimensions after NPT thread installation.
Note) øD1: Max. diameter

Hexagon Socket Head Universal Male Elbow: KQ2VS

<10-32 UNF>




<NPT>




Applicable tubing O.D. (inch)	Connection thread UNF NPT	Model	H (Width across flats)	(Note) øD1	øD2	L1	L2	L3	A*	M	Min. port size	Mass (g)		
1/8	10-32 UNF	KQ2VS01-32	4	8.4	9.8	17.2	10.9	18.5	15	12.7	2.3	5		
	1/8	KQ2VS01-34S	6.35	9.6	13.4	21.5	13.6	25.6	22.5	15.5	2.5	14		
5/32	10-32 UNF	KQ2VS03-32	4	10.4	9.8	20.5	11	18.5	15	16	2.3	6		
	1/8	KQ2VS03-34S	6.35		13.4	22	13.6	25.6	22.5		2.8	14		
3/16	1/8	KQ2VS05-34S	8	11.4	13.4	23	13.6	25.6	22.5	16.5	3.5	15		
1/4	10-32 UNF	KQ2VS07-32	6.35	13.2	13.4	24	12	24	19	17	2.3	13		
	1/8	KQ2VS07-34S			15.3	23.5	13.6	25.6	22.5		4.6	15		
	1/4	KQ2VS07-35S			8		17.6	28.5	14.6	26.1	23	18.5	6	21
	3/8	KQ2VS09-36S					20.6	27.5	18	29.5	24		27	
5/16	1/8	KQ2VS09-34S	8	15.2	17.6	28.5	14.6	26.1	23	18.5	6	21		
	1/4	KQ2VS09-35S			20.6	27.5	19.4	31.4	26			27		
	3/8	KQ2VS09-36S			20.6	27.5	19.4	31.4	26			39		
	1/4	KQ2VS11-35S			19	31	25.5	26	33					
3/8	1/4	KQ2VS11-35S	8	17.9	20.6	31	19.4	31.4	26	21	7	42		
	3/8	KQ2VS11-36S			20.4	33.4	28.5	29.5	63					
1/2	3/8	KQ2VS13-36S	9.53	21.7	27	34.5	20.4	33.4	28.5	22	9	63		
	1/2	KQ2VS13-37S					23.6	36.6	29.5			81		

<10-32 UNF>



<NPT>



* Reference dimensions after NPT thread installation.
Note) øD1: Max. diameter