

SAFETY SHOES WRANGEL 2 S3 SRC

Item #	EAN	Product
855124	3660338106057	Size 5
855125	3660338106064	Size 6
855127	3660338106088	Size 7
855128	3660338106095	Size 8
855129	3660338106101	Size 9
855130	3660338106118	Size 10
855132	3660338106132	Size 11
855133	3660338106149	Size 12

Description

FULL GRAIN LEATHER LOW CUT SHOES - S3 SRC A

Full grain water resistant leather upper, thickness 1.9 / 2.1.
 Reflective side inserts. On-tip abrasion-resistant leather.
 Optimization of the abrasion resistance, long service life.
 3 layer lining material for better moisture transfer to the outside, high breathability and quick drying.
 Lining forefoot, abrasion resistant and acid perspiration.
 Padded collar ensures comfort and protection against side impact.
 Closes with lacing on 4 pairs of nonmetallic bodkins on padded bellows for good sealing and good protection of the instep. Lace 110 cm.
 First anatomically complete cleanliness and antistatic honeycomb structure for better air circulation.
 Euro Size : 38 - 47



Characteristics Dual density PU sole resistant to oils and hydrocarbons. Profile wrapping for stability in the march deep crampons, self-cleaning and multi directional. Synthetic material safety cap protecting a shock of 200 Joules. Non-metallic anti-perforation midsole complies with standard 12568: 2010, full protection of the foot. Weight: 715 g (weight from one foot in size 42)

Instructions & storage

Safety footwear for professional use. Footwear for general use, outdoor works (Construction, second work, craftsman...) or indoor works (Industry, services, logistic...).

Safety footwear S3 SRC, class I, Ankle boot. Footwear with a protective toe cap providing protection against shocks equivalent to 200 joules and against crushing risks under a maximum 15 kN load, and puncture-proof sole with anti-penetration insert (P). Footwear with antistatic properties (A), energy absorbing heel (E). Water resistant upper (WRU). cleated Outsole resistant to fuel oil (FO). Slip resistant Footwear provided for indoor or outdoor use and for smooth and oily industrial-type floors (SRC). To be stored in its original packing in a dry place, sheltered from sun light.

The GISS guarantee can only be applied optimal-condition shoes, being used without adding up any accessories likely to generate a change in protection, or it cannot be applied when its use is not specified in the current instructions for use. Not to be used for protection against further hazards than defined above. Not to be used within the scope of any other field of activity than that defined in the above-mentioned instructions. A removable insock is provided with this footwear. Testing was carried out on the footwear with the insock in place. Consequently, this footwear must be worn with the insock in place. It may only be replaced by a comparable insock supplied by Delta Plus. This footwear contains no substances known to cause allergic reactions in people with allergic sensitivities.

Standards and certifications Safety footwear S3 SRC, Class I, Comply with the requirements of the European Directive 89/686, special for ergonomics, harmlessness, comfort, airing and flexibility and with the requirements of the European standard EN ISO 20345:2011.