Technical Data







MP100 Multi Purpose Spray Adhesive is a fast drying, strong adhesive.

ADVANTAGES

- Original Formulation
- Fast Tack
- Ideal where instant contact and bonding is required
- Provides high-strength, permanent bonds
- Variable actuator for maximum control and economy

APPLICATIONS

MP100 Multi Purpose Spray Adhesive will provide quick, strong bonds in many areas:

Carpets & Flooring
Chipboard and Concrete

Insulation Materials
Canvas and Leather

Paper, Wood and Cork
Metal, Plastics and Rubber

Apply an even coating to both surfaces to be bonded from 9'' - 12'' (25 – 30cm). Wait until the adhesive is tack-dry and bond the surfaces together using firm pressure.

NB. May affect certain plastics. Always test a small, inconspicuous area before general use. To prevent blockages, invert the can after use and spray clear the nozzle.

TECHNICAL DATA

Appearance : Thick, gelatinous film

Odour : Ethereal/Solvent

SG @ 25°C : 1.16

Pressure @ 25°C : 4 bar

Discharge rate : 1.4g/sec

Polymer Type : Styrene butadiene rubber

Tack Time : Approximately 30 seconds

Bonding Time : Maximum adhesion in 12 - 24 hours

Temperature Range : Up to 50°C (dried film)

Solubility : Soluble in some solvents, insoluble in

water

Recommended solvents : Amberklene FE10, ME20 or LO30

Flammability : Classified as extremely flammable under

the EC Classification, Labelling and Packaging regulation (CLP) 1272/2008

Packaging : 500ml aerosol (12 per carton)

STORAGE

The product may be stored at normal ambient temperatures and has a shelf life of not less than 36 months with correct storage. Aerosols should always be stored below 50° C, away from direct heat and naked flame.

HEALTH AND SAFETY

Health and Safety sheet available separately.

TECHNICAL SERVICE

Ambersil provides a technical support service and maintains a constant programme of research and development. We are able to assist customers by specific product development to meet particular requirements.

MISREPRESENTATION ACT 1967 TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

CRC Industries UK Limited, Wylds Road, Bridgwater, Somerset, TA6 4DD

Tel: +44 (0) 1278 727200 Fax: +44 (0) 1278 425644

Web: www.ambersil.com E-mail: sales.uk@crcind.com

Version 2

Updated: June 2015