




Negative rhombic 80° CNMG / CNGG / CNMA / CNMM

Tiger-tec® Silver



Indexable inserts

		Designation	r mm	f mm	a _p mm	P						M				K			S				
						HC						HC				HC			HC				
						WPP01	WPP05S	WPP10S	WPP20S	WPP30S	WMP20S	WMP20S	WSM01	WSM10S	WSM20S	WSM30S	WKK10S	WKK20S	WKP30S	WSM01	WSM10S	WSM20S	WSM30S
	CNMG120404-MM5	0,4	0,10–0,20	0,5–3,0						☹	☹		☹	☹	☹					☹	☹	☹	
	CNMG120408-MM5	0,8	0,15–0,32	0,8–3,0						☹	☹		☹	☹	☹					☹	☹	☹	
	CNMG120412-MM5	1,2	0,15–0,35	0,8–3,5						☹	☹		☹	☹	☹					☹	☹	☹	
	CNMG120416-MM5	1,6	0,15–0,40	1,0–4,0									☹	☹	☹					☹	☹	☹	
	CNMG160608-MM5	0,8	0,15–0,35	0,8–4,5						☹	☹		☹	☹	☹					☹	☹	☹	
	CNMG160612-MM5	1,2	0,18–0,40	0,8–4,5						☹	☹		☹	☹	☹					☹	☹	☹	
	CNMG160616-MM5	1,6	0,20–0,45	1,0–4,5									☹	☹	☹					☹	☹	☹	
	CNMG120408-MU5	0,8	0,15–0,40	0,6–5,0		☹	☹	☹		☹	☹		☹							☹			
	CNMG120412-MU5	1,2	0,25–0,60	1,0–5,0		☹	☹	☹		☹	☹		☹							☹			
	CNMG090308-MK5	0,8	0,10–0,20	0,2–3,0												☹	☹						
	CNMG120404-MK5	0,4	0,16–0,25	0,6–5,0												☹	☹						
	CNMG120408-MK5	0,8	0,25–0,50	0,8–5,0												☹	☹	☹					
	CNMG120412-MK5	1,2	0,30–0,50	1,2–5,0												☹	☹	☹					
	CNMG120416-MK5	1,6	0,35–0,50	1,5–5,0												☹	☹	☹					
	CNMG160608-MK5	0,8	0,25–0,50	0,8–7,0												☹	☹	☹					
	CNMG160612-MK5	1,2	0,30–0,60	1,2–7,0												☹	☹	☹					
	CNMG160616-MK5	1,6	0,35–0,60	1,5–7,0												☹	☹	☹					
	CNMG190612-MK5	1,2	0,30–0,65	1,2–8,0												☹	☹	☹					
	CNMG190616-MK5	1,6	0,35–0,80	1,5–8,0												☹	☹	☹					
		CNMG120408-NRT	0,8	0,18–0,35	1,0–6,0									☹							☹		☹
CNMG120412-NRT		1,2	0,20–0,40	1,2–6,0																		☹	
CNMG160612-NRT		1,2	0,28–0,55	1,5–7,5																		☹	
CNMG190616-NRT		1,6	0,35–0,70	2,0–9,0										☹						☹		☹	
	CNMG120408-NRS	0,8	0,16–0,35	1,0–4,0						☹	☹	☹	☹	☹	☹				☹	☹	☹	☹	
	CNMG120412-NRS	1,2	0,18–0,40	1,2–4,0						☹	☹	☹	☹	☹	☹				☹	☹	☹	☹	
	CNMG160612-NRS	1,2	0,21–0,45	1,2–6,5						☹	☹		☹	☹	☹				☹	☹	☹	☹	
	CNMG160616-NRS	1,6	0,23–0,50	1,5–6,5									☹	☹	☹				☹	☹	☹		
	CNMG190608-NRS	0,8	0,20–0,45	1,0–8,0									☹	☹	☹				☹	☹	☹		
	CNMG190612-NRS	1,2	0,23–0,50	1,2–8,5									☹	☹	☹				☹	☹	☹		
	CNMG120408-RM5	0,8	0,20–0,40	1,2–5,0			☹	☹		☹	☹		☹	☹	☹				☹	☹	☹	☹	
	CNMG120412-RM5	1,2	0,25–0,50	1,5–5,0			☹	☹		☹	☹		☹	☹	☹				☹	☹	☹	☹	
	CNMG120416-RM5	1,6	0,30–0,55	2,0–5,0																	☹	☹	
	CNMG160608-RM5	0,8	0,22–0,45	1,2–7,0									☹	☹	☹				☹	☹	☹	☹	
	CNMG160612-RM5	1,2	0,25–0,60	1,5–7,0			☹	☹		☹	☹		☹	☹	☹				☹	☹	☹	☹	
	CNMG160616-RM5	1,6	0,30–0,65	2,0–7,0			☹	☹		☹	☹										☹	☹	
	CNMG190612-RM5	1,2	0,25–0,60	1,5–8,0						☹	☹		☹	☹	☹				☹	☹	☹	☹	
	CNMG190616-RM5	1,6	0,30–0,80	2,0–8,0						☹	☹		☹	☹	☹				☹	☹	☹	☹	

See the ISO 1832 designation key for dimensions

HC = Coated carbide
HW = Uncoated carbide