

The Timken Company


4500 Mt Pleasant St. NW N. Canton, OH 44720

Phone: (234) 262-3000

E-Mail: <u>CustomerCAD@timken.com</u> • Web site: <u>www.timken.com</u>

Part Number UCF309, UCF 300 Four-Bolt Flanged Mounted Bearings - Set Screw Locking






<u>Specifications</u> | <u>Dimensions</u> | <u>Basic Load Ratings</u>


Specifications –				
	Bearing Number	UC309		
	Shaft Size d	45 mm		
	Locking Style	Set Screw Locking		
	Housing Construction	Four-Bolt Square Flange		

Din	nensions		-
	Total Length L	160 mm 6.299 in	
	Housing Width A	44 mm 1.732 in	
	olt Hole Spacing J	125 mm 4.921 in	

Bolt Hole Size N	19 mm 0.748 in
Flange Thickness A1	18 mm 0.709 in
Center of Bearing from Housing End A2	25 mm 0.984 in
Inner Ring Width B	57 mm 2.244 in
Center of Bearing from Bearing End S	22 mm 0.866 in
Dimension A0	60 mm 2.359 in
Bolt Size	M16
Grease Nipple Size	A-R1/8

Basi	c Load Ratings		-
	Static Load Rating	29500 N 6632 lbf	
	Dynamic Load Rating	48900 N 10993 lbf	





Bearing Number	UC309			
Load Ratings - C _r	10993	lbf	48900	N
Load Ratings - C _{0r}	6632	lbf	29500	N
Weight	8.8	lb	4	kg
Bolt Size	M16			

THE TIMKEN COMPANY
NORTH CANTON, OHIO USA

UCF309

UCF 300 Four-Bolt Flanged Mounted Bearings - Set Screw Locking

Every reasonable effort has been made to ensure the accuracy of the information contained in this writing, but no liability is accepted for errors, omissions or for any other reason.

FOR DISCUSSION ONLY