


Self-Lube® bearing inserts

1200G and 1300 Series


1200G

With spherical outside diameter and integral set screw lock



1300

With parallel outside diameter and integral set screw lock



Shaft diameter mm inches	RHP designation		Dimensions (mm)							ISO Load ratings		Rec. max. speed rev/min	Mass (approx.) kg
	1200G Series	1300 Series	D	C	B ₁	s ₁	d ₁	M	r	dynamic C _r newtons	static C _{0r} newtons		
12	1217-12G		40.000	12.00	22.38	6.53	24.80	5.00	0.60	9550	4800	7000	0.08
15	1217-15G												
17	1217-17G												
5/8	1217-5/8G												
20	1220-20G	1320-20	47.000	14.00	25.80	7.53	28.30	5.00	1.00	12800	6650	6700	0.10
3/4	1220-3/4G	1320-3/4											
25	1225-25G	1325-25	52.000	15.00	27.30	7.53	34.00	5.00	1.00	14000	7880	6250	0.13
1	1225-1G	1325-1											
30	1230-30G	1330-30	62.000	16.00	31.20	9.03	40.30	5.00	1.00	19500	11300	5300	0.32
1 1/4	1230-1 1/4G	1330-1 1/4											
35	1235-35G	1335-35	72.000	17.00	34.90	9.53	46.90	6.50	1.00	25700	15300	4500	0.43
1 1/4	1235-1 1/4G	1335-1 1/4											
40	1240-40G	1340-40	80.000	18.00	41.20	11.03	52.40	8.00	1.00	32500	19900	4000	0.54
1 1/2	1240-1 1/2G	1340-1 1/2											
45	1245-45G	1345-45	85.000	19.00	41.20	11.04	57.40	8.00	1.00	32500	20500	3700	0.61
1 3/4	1245-1 3/4G	1345-1 3/4											
50	1250-50G	1350-50	90.000	20.00	43.50	11.04	62.40	10.00	1.00	35000	23200	3400	0.76

Please check availability