

GLOBAL SOLUTION OF WORKSHOP

Create your flexible, evolutionary and innovative workspace!



















113AS **COMPACT ADJUSTABLE WRENCHES ACCESSIBLE, LIGHT AND COMFORT** Very high accessibility in confined space. · Ergonomic handle. 113AS

■ 113AS.C - Short adjustable wrenches



Adjustable wrenches

ISO 6787 NF ISO 6787 DIN 3117 ASME B107.100

- . Short handle and thin profile gives optimum accessibility.
- Lightweight = Increased comfort
- Big opening for maximum versatility: up to 41mm.
- Good access to the screw = Easy setting.
- Non-proturing moving jaw at maximum capacity.
- Millimetric graduation.
- Presentation: chromed body and polished head faces.


=0	Α	В	C x C1	Е	E1	E2	E3	E4	L	L1	$\nabla_{\!$
₹	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[g]
113AS.6CPB	33	58	17X19	6.3	9.9	6.7	8.8	7.1	160	25.3	178
113AS.8CPB	40	74	19x23	7	12.1	8.8	10.4	9	200	32.4	328

'HIGH SAFETY' IMPACT WRENCHES 51BS

INNOVATING FASTENING SYSTEM (PATENTED)


- Work safely: no need to hold the wrench.
- Increase productivity: usable single-handed, no accessories require.











- Patented mechanism to lock the wrench on the screw.
- No need to hold the wrench when striking=no risk of injuries, maximum security.
- . Innovative & Easy to use unlock trigger.
- . Hook for work at height.
- Metric sizes from 24 to 80mm.
- · Presentation: black phosphate.

51BS.24 24 45 19.5 32.5 180 510 51BS.27 27 45 19.5 32.5 180 493 51BS.30 30 48 21 33.8 195 607 51BS.32 32 51 21.5 34.2 195 649 51BS.36 36 59 25 37.2 205 904 51BS.41 41 62 26 37.2 231 990 51BS.46 46 71 28 39.0 240 1268 51BS.50 50 75 31 41.0 255 1493 51BS.65 55 80 35 47.5 270 1950 51BS.65 65 93 41 48.0 300 2720 51BS.70 70 102 43 58.0 320 3490	= 0	A [mm]	B [mm]	E [mm]	E1 [mm]	L [mm]	∆∏∆ [g]
51BS.30 30 48 21 33.8 195 607 51BS.32 32 51 21.5 34.2 195 649 51BS.36 36 59 25 37.2 205 904 51BS.41 41 62 26 37.2 231 990 51BS.46 46 71 28 39.0 240 1268 51BS.50 50 75 31 41.0 255 1493 51BS.55 55 80 35 47.5 270 1950 51BS.60 60 85 38 49.5 280 2300 51BS.65 65 93 41 48.0 300 2720	51BS.24	24	45	19.5	32.5	180	510
51BS.32 32 51 21.5 34.2 195 649 51BS.36 36 59 25 37.2 205 904 51BS.41 41 62 26 37.2 231 990 51BS.46 46 71 28 39.0 240 1268 51BS.50 50 75 31 41.0 255 1493 51BS.55 55 80 35 47.5 270 1950 51BS.60 60 85 38 49.5 280 2300 51BS.65 65 93 41 48.0 300 2720	51BS.27	27	45	19.5	32.5	180	493
51BS.36 36 59 25 37.2 205 904 51BS.41 41 62 26 37.2 231 990 51BS.46 46 71 28 39.0 240 1268 51BS.50 50 75 31 41.0 255 1493 51BS.55 55 80 35 47.5 270 1950 51BS.60 60 85 38 49.5 280 2300 51BS.65 65 93 41 48.0 300 2720	51BS.30	30	48	21	33.8	195	607
51BS.41 41 62 26 37.2 231 990 51BS.46 46 71 28 39.0 240 1268 51BS.50 50 75 31 41.0 255 1493 51BS.55 55 80 35 47.5 270 1950 51BS.60 60 85 38 49.5 280 2300 51BS.65 65 93 41 48.0 300 2720	51BS.32	32	51	21.5	34.2	195	649
51BS.46 46 71 28 39.0 240 1268 51BS.50 50 75 31 41.0 255 1493 51BS.55 55 80 35 47.5 270 1950 51BS.60 60 85 38 49.5 280 2300 51BS.65 65 93 41 48.0 300 2720	51BS.36	36	59	25	37.2	205	904
51BS.50 50 75 31 41.0 255 1493 51BS.55 55 80 35 47.5 270 1950 51BS.60 60 85 38 49.5 280 2300 51BS.65 65 93 41 48.0 300 2720	51BS.41	41	62	26	37.2	231	990
51BS.55 55 80 35 47.5 270 1950 51BS.60 60 85 38 49.5 280 2300 51BS.65 65 93 41 48.0 300 2720	51BS.46	46	71	28	39.0	240	1268
51BS.60 60 85 38 49.5 280 2300 51BS.65 65 93 41 48.0 300 2720	51BS.50	50	75	31	41.0	255	1493
51BS.65 65 93 41 48.0 300 2720	51BS.55	55	80	35	47.5	270	1950
	51BS.60	60	85	38	49.5	280	2300
51BS.70 70 102 43 58.0 320 3490	51BS.65	65	93	41	48.0	300	2720
10 102 10 0010 020 0100	51BS.70	70	102	43	58.0	320	3490
51BS.75 75 108 48 60.0 330 3760	51BS.75	75	108	48	60.0	330	3760
51BS.80 80 118 52 63.0 360 4640	51BS.80	80	118	52	63.0	360	4640





13

FACOM www.facom.com www.facom.com













(=)











