## DATASHEET



## **NON-CORROSIVE FITTING**55W 6ft LED High Output NCF

Product Ref: **FNCF6HO** 


## **Technical Features:**


- Manufactured from self-extinguishing V2 polycarbonate
- Polycarbonate UV stabilised diffuser
- Stainless steel diffuser clips
- · Gear tray suspension cords included
- Surface and suspension mounting options (accessories supplied)
- Push fit (loop-in/loop-out) terminal blocks



## **Product Specification**

| Attachment Type       | Polycarbonate Diffuser |
|-----------------------|------------------------|
| Average Life          | 50000 hours            |
| Beam Angle            | 120°                   |
| Class                 | Class 1                |
| Colour                | Grey                   |
| Colour Temperature    | 4000K                  |
| Compliance            | UKCA, CE               |
| CRI                   | >80                    |
| Fixing Centres        | 1355mm                 |
| Frequency             | 50-60Hz                |
| Guarantee             | 5 Years                |
| IK Rating             | IK08                   |
| IP Rating             | IP65                   |
| Lens Colour           | Frosted                |
| Lumens                | 6900lm                 |
| Material              | Polycarbonate          |
| Mounting              | Surface/Suspended      |
| Operating Temperature | -20 - +40°C            |
| Voltage Rating        | 230V                   |
| Wattage               | 55W                    |
| Weight                | 2.300kg                |
| Height                | 83mm                   |
| Length                | 1800mm                 |
| Width                 | 96mm                   |





Errors and omissions excepted (E&OE). All information is subject to change without notice and is correct at the time of print. Refer to issue number and date below.

Tel: +44 (0)1302 769 966