


Technical data

NUKR40/3AS

Cam follower with shaft

Needle roller bearing, cam follower, full-complement cylindrical roller, slot for screwdriver, oil hole, double-side shields, spherical outer ring

Visual(s)



Product definition	
D	40 mm
d1	18 mm
C	20 mm
F	21.5 mm
B	21.5 mm
B1	58 mm
B2	36.5 mm
G	M18X1.5
G1	19 mm
B3	8 mm
C1	0.8 mm
n	6 mm
a	3 mm
e	23 mm
R	500 mm
Dw	4 mm
Lw	6 mm
Maximum tightening torque	76 Nm
Bearing with/without cage	Sans
Radial clearance class	CN
Precision class	P0
Mass	0.24 kg
Brand	NTN

Product performance	
Cr	24.1 kN
C0r	29.1 kN
Track load capacity spherical outer ring	3.85 kN
Nlim (grease)	4,700 Tr/min
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.42 Hz
Characteristic rolling element frequency, BSF	6.22 Hz
Characteristic outer ring frequency, BPF0	8.43 Hz
Characteristic inner ring frequency, BPFI	11.57 Hz